

---

# **Python Frequently Asked Questions**

***Release 3.3.0***

**Guido van Rossum**  
**Fred L. Drake, Jr., editor**

September 29, 2012

**Python Software Foundation**  
Email: [docs@python.org](mailto:docs@python.org)



# CONTENTS

|          |  |           |
|----------|--|-----------|
| <b>1</b> | <b>General Python FAQ</b>  | <b>3</b>  |
| 1.1      | General Information . . . . .  | 3         |
| 1.2      | Python in the real world . . . . .   | 7         |
| <b>2</b> | <b>Programming FAQ</b>   | <b>11</b> |
| 2.1      | General Questions . . . . .  | 13        |
| 2.2      | Core Language . . . . .  | 14        |
| 2.3      | Numbers and strings . . . . .  | 20        |
| 2.4      | Performance . . . . .  | 23        |
| 2.5      | Sequences (Tuples/Lists) . . . . .   | 24        |
| 2.6      | Dictionaries . . . . .   | 26        |
| 2.7      | Objects . . . . .  | 28        |
| 2.8      | Modules . . . . .  | 32        |
| <b>3</b> | <b>Design and History FAQ</b>  | <b>35</b> |
| 3.1      | Why does Python use indentation for grouping of statements? . . . . .  | 35        |
| 3.2      | Why am I getting strange results with simple arithmetic operations? . . . . .  | 35        |
| 3.3      | Why are floating-point calculations so inaccurate? . . . . .   | 35        |
| 3.4      | Why are Python strings immutable? . . . . .  | 36        |
| 3.5      | Why must 'self' be used explicitly in method definitions and calls? . . . . .  | 36        |
| 3.6      | Why can't I use an assignment in an expression? . . . . .  | 37        |
| 3.7      | Why does Python use methods for some functionality (e.g. list.index()) but functions for other (e.g. len(list))? . . . . . | 38        |
| 3.8      | Why is join() a string method instead of a list or tuple method? . . . . .   | 38        |
| 3.9      | How fast are exceptions? . . . . .   | 38        |
| 3.10     | Why isn't there a switch or case statement in Python? . . . . .  | 39        |
| 3.11     | Can't you emulate threads in the interpreter instead of relying on an OS-specific thread implementation? . . . . .         | 39        |
| 3.12     | Why can't lambda forms contain statements? . . . . .   | 40        |
| 3.13     | Can Python be compiled to machine code, C or some other language? . . . . .  | 40        |
| 3.14     | How does Python manage memory? . . . . .   | 40        |
| 3.15     | Why doesn't CPython use a more traditional garbage collection scheme? . . . . .  | 41        |
| 3.16     | Why isn't all memory freed when CPython exits? . . . . .   | 41        |
| 3.17     | Why are there separate tuple and list data types? . . . . .  | 41        |
| 3.18     | How are lists implemented? . . . . .   | 41        |
| 3.19     | How are dictionaries implemented? . . . . .  | 42        |
| 3.20     | Why must dictionary keys be immutable? . . . . .   | 42        |
| 3.21     | Why doesn't list.sort() return the sorted list? . . . . .  | 43        |
| 3.22     | How do you specify and enforce an interface spec in Python? . . . . .  | 43        |
| 3.23     | Why are default values shared between objects? . . . . .   | 44        |
| 3.24     | Why is there no goto? . . . . .  | 45        |
| 3.25     | Why can't raw strings (r-strings) end with a backslash? . . . . .  | 45        |
| 3.26     | Why doesn't Python have a "with" statement for attribute assignments? . . . . .  | 45        |

|          |  |           |
|----------|--|-----------|
| 3.27     | Why are colons required for the if/while/def/class statements?   | 46        |
| 3.28     | Why does Python allow commas at the end of lists and tuples?   | 46        |
| <b>4</b> | <b>Library and Extension FAQ</b>   | <b>49</b> |
| 4.1      | General Library Questions  | 50        |
| 4.2      | Common tasks   | 51        |
| 4.3      | Threads  | 52        |
| 4.4      | Input and Output   | 55        |
| 4.5      | Network/Internet Programming   | 56        |
| 4.6      | Databases  | 58        |
| 4.7      | Mathematics and Numerics   | 58        |
| <b>5</b> | <b>Extending/Embedding FAQ</b>   | <b>61</b> |
| 5.1      | Can I create my own functions in C?  | 61        |
| 5.2      | Can I create my own functions in C++?  | 61        |
| 5.3      | Writing C is hard; are there any alternatives?   | 62        |
| 5.4      | How can I execute arbitrary Python statements from C?  | 62        |
| 5.5      | How can I evaluate an arbitrary Python expression from C?  | 62        |
| 5.6      | How do I extract C values from a Python object?  | 62        |
| 5.7      | How do I use Py_BuildValue() to create a tuple of arbitrary length?  | 62        |
| 5.8      | How do I call an object's method from C?   | 62        |
| 5.9      | How do I catch the output from PyErr_Print() (or anything that prints to stdout/stderr)?                         | 63        |
| 5.10     | How do I access a module written in Python from C?   | 63        |
| 5.11     | How do I interface to C++ objects from Python?   | 64        |
| 5.12     | I added a module using the Setup file and the make fails; why?   | 64        |
| 5.13     | How do I debug an extension?   | 64        |
| 5.14     | I want to compile a Python module on my Linux system, but some files are missing. Why?                           | 64        |
| 5.15     | What does "SystemError: _PyImport_FixupExtension: module yourmodule not loaded" mean?                            | 65        |
| 5.16     | How do I tell "incomplete input" from "invalid input"?   | 65        |
| 5.17     | How do I find undefined g++ symbols __builtin_new or __pure_virtual?   | 68        |
| 5.18     | Can I create an object class with some methods implemented in C and others in Python (e.g. through inheritance)? | 68        |
| <b>6</b> | <b>Python on Windows FAQ</b>   | <b>69</b> |
| 6.1      | How do I run a Python program under Windows?   | 69        |
| 6.2      | How do I make Python scripts executable?   | 72        |
| 6.3      | Why does Python sometimes take so long to start?   | 72        |
| 6.4      | Where is Freeze for Windows?   | 73        |
| 6.5      | Is a *.pyd file the same as a DLL?   | 73        |
| 6.6      | How can I embed Python into a Windows application?   | 73        |
| 6.7      | How do I use Python for CGI?   | 74        |
| 6.8      | How do I keep editors from inserting tabs into my Python source?   | 75        |
| 6.9      | How do I check for a keypress without blocking?  | 75        |
| 6.10     | How do I emulate os.kill() in Windows?   | 75        |
| 6.11     | Why does os.path.isdir() fail on NT shared directories?  | 75        |
| 6.12     | cgi.py (or other CGI programming) doesn't work sometimes on NT or win95!   | 76        |
| 6.13     | Why doesn't os.popen() work in PythonWin on NT?  | 76        |
| 6.14     | Why doesn't os.popen()/win32pipe.popen() work on Win9x?  | 76        |
| 6.15     | PyRun_SimpleFile() crashes on Windows but not on Unix; why?  | 76        |
| 6.16     | Importing _tkinter fails on Windows 95/98: why?  | 76        |
| 6.17     | How do I extract the downloaded documentation on Windows?  | 77        |
| 6.18     | Missing cw3215mt.dll (or missing cw3215.dll)   | 77        |
| 6.19     | Warning about CTL3D32 version from installer   | 77        |
| <b>7</b> | <b>Graphic User Interface FAQ</b>  | <b>79</b> |
| 7.1      | General GUI Questions  | 79        |
| 7.2      | What platform-independent GUI toolkits exist for Python?   | 79        |
| 7.3      | What platform-specific GUI toolkits exist for Python?  | 80        |
| 7.4      | Tkinter questions  | 80        |

|          |  |            |
|----------|--|------------|
| <b>8</b> | <b>“Why is Python Installed on my Computer?” FAQ</b>                   | <b>83</b>  |
| 8.1      | What is Python? . . . . .  | 83         |
| 8.2      | Why is Python installed on my machine? . . . . .                       | 83         |
| 8.3      | Can I delete Python? . . . . .   | 83         |
| <b>A</b> | <b>Glossary</b>  | <b>85</b>  |
| <b>B</b> | <b>About these documents</b>   | <b>93</b>  |
| B.1      | Contributors to the Python Documentation . . . . .                     | 93         |
| <b>C</b> | <b>History and License</b>   | <b>95</b>  |
| C.1      | History of the software . . . . .                                      | 95         |
| C.2      | Terms and conditions for accessing or otherwise using Python . . . . . | 96         |
| C.3      | Licenses and Acknowledgements for Incorporated Software . . . . .      | 98         |
| <b>D</b> | <b>Copyright</b>   | <b>109</b> |
|          | <b>Index</b>   | <b>111</b> |



**Release** 3.3

**Date** September 29, 2012



# GENERAL PYTHON FAQ

## Contents

- General Python FAQ
  - General Information
    - \* What is Python?
    - \* What is the Python Software Foundation?
    - \* Are there copyright restrictions on the use of Python?
    - \* Why was Python created in the first place?
    - \* What is Python good for?
    - \* How does the Python version numbering scheme work?
    - \* How do I obtain a copy of the Python source?
    - \* How do I get documentation on Python?
    - \* I've never programmed before. Is there a Python tutorial?
    - \* Is there a newsgroup or mailing list devoted to Python?
    - \* How do I get a beta test version of Python?
    - \* How do I submit bug reports and patches for Python?
    - \* Are there any published articles about Python that I can reference?
    - \* Are there any books on Python?
    - \* Where in the world is [www.python.org](http://www.python.org) located?
    - \* Why is it called Python?
    - \* Do I have to like "Monty Python's Flying Circus"?
  - Python in the real world
    - \* How stable is Python?
    - \* How many people are using Python?
    - \* Have any significant projects been done in Python?
    - \* What new developments are expected for Python in the future?
    - \* Is it reasonable to propose incompatible changes to Python?
    - \* Is Python Y2K (Year 2000) Compliant?
    - \* Is Python a good language for beginning programmers?

## 1.1 General Information

### 1.1.1 What is Python?

Python is an interpreted, interactive, object-oriented programming language. It incorporates modules, exceptions, dynamic typing, very high level dynamic data types, and classes. Python combines remarkable power with very clear syntax. It has interfaces to many system calls and libraries, as well as to various window systems, and is extensible in C or C++. It is also usable as an extension language for applications that need a programmable interface. Finally, Python is portable: it runs on many Unix variants, on the Mac, and on Windows 2000 and later.

To find out more, start with *tutorial-index*. The [Beginner's Guide to Python](#) links to other introductory tutorials and resources for learning Python.

### 1.1.2 What is the Python Software Foundation?

The Python Software Foundation is an independent non-profit organization that holds the copyright on Python versions 2.1 and newer. The PSF's mission is to advance open source technology related to the Python programming language and to publicize the use of Python. The PSF's home page is at <http://www.python.org/psf/>.

Donations to the PSF are tax-exempt in the US. If you use Python and find it helpful, please contribute via [the PSF donation page](#).

### 1.1.3 Are there copyright restrictions on the use of Python?

You can do anything you want with the source, as long as you leave the copyrights in and display those copyrights in any documentation about Python that you produce. If you honor the copyright rules, it's OK to use Python for commercial use, to sell copies of Python in source or binary form (modified or unmodified), or to sell products that incorporate Python in some form. We would still like to know about all commercial use of Python, of course.

See [the PSF license page](#) to find further explanations and a link to the full text of the license.

The Python logo is trademarked, and in certain cases permission is required to use it. Consult [the Trademark Usage Policy](#) for more information.

### 1.1.4 Why was Python created in the first place?

Here's a *very* brief summary of what started it all, written by Guido van Rossum:

I had extensive experience with implementing an interpreted language in the ABC group at CWI, and from working with this group I had learned a lot about language design. This is the origin of many Python features, including the use of indentation for statement grouping and the inclusion of very-high-level data types (although the details are all different in Python).

I had a number of gripes about the ABC language, but also liked many of its features. It was impossible to extend the ABC language (or its implementation) to remedy my complaints – in fact its lack of extensibility was one of its biggest problems. I had some experience with using Modula-2+ and talked with the designers of Modula-3 and read the Modula-3 report. Modula-3 is the origin of the syntax and semantics used for exceptions, and some other Python features.

I was working in the Amoeba distributed operating system group at CWI. We needed a better way to do system administration than by writing either C programs or Bourne shell scripts, since Amoeba had its own system call interface which wasn't easily accessible from the Bourne shell. My experience with error handling in Amoeba made me acutely aware of the importance of exceptions as a programming language feature.

It occurred to me that a scripting language with a syntax like ABC but with access to the Amoeba system calls would fill the need. I realized that it would be foolish to write an Amoeba-specific language, so I decided that I needed a language that was generally extensible.

During the 1989 Christmas holidays, I had a lot of time on my hand, so I decided to give it a try. During the next year, while still mostly working on it in my own time, Python was used in the Amoeba project with increasing success, and the feedback from colleagues made me add many early improvements.

In February 1991, after just over a year of development, I decided to post to USENET. The rest is in the `Misc/HISTORY` file.

### 1.1.5 What is Python good for?

Python is a high-level general-purpose programming language that can be applied to many different classes of problems.

The language comes with a large standard library that covers areas such as string processing (regular expressions, Unicode, calculating differences between files), Internet protocols (HTTP, FTP, SMTP, XML-RPC, POP, IMAP, CGI programming), software engineering (unit testing, logging, profiling, parsing Python code), and operating system interfaces (system calls, filesystems, TCP/IP sockets). Look at the table of contents for *library-index* to get an idea of what's available. A wide variety of third-party extensions are also available. Consult the [Python Package Index](#) to find packages of interest to you.

### 1.1.6 How does the Python version numbering scheme work?

Python versions are numbered A.B.C or A.B. A is the major version number – it is only incremented for really major changes in the language. B is the minor version number, incremented for less earth-shattering changes. C is the micro-level – it is incremented for each bugfix release. See [PEP 6](#) for more information about bugfix releases.

Not all releases are bugfix releases. In the run-up to a new major release, a series of development releases are made, denoted as alpha, beta, or release candidate. Alphas are early releases in which interfaces aren't yet finalized; it's not unexpected to see an interface change between two alpha releases. Betas are more stable, preserving existing interfaces but possibly adding new modules, and release candidates are frozen, making no changes except as needed to fix critical bugs.

Alpha, beta and release candidate versions have an additional suffix. The suffix for an alpha version is “aN” for some small number N, the suffix for a beta version is “bN” for some small number N, and the suffix for a release candidate version is “cN” for some small number N. In other words, all versions labeled 2.0aN precede the versions labeled 2.0bN, which precede versions labeled 2.0cN, and *those* precede 2.0.

You may also find version numbers with a “+” suffix, e.g. “2.2+”. These are unreleased versions, built directly from the Subversion trunk. In practice, after a final minor release is made, the Subversion trunk is incremented to the next minor version, which becomes the “a0” version, e.g. “2.4a0”.

See also the documentation for `sys.version`, `sys.hexversion`, and `sys.version_info`.

### 1.1.7 How do I obtain a copy of the Python source?

The latest Python source distribution is always available from python.org, at <http://www.python.org/download/>. The latest development sources can be obtained via anonymous Mercurial access at <http://hg.python.org/cpython>.

The source distribution is a gzipped tar file containing the complete C source, Sphinx-formatted documentation, Python library modules, example programs, and several useful pieces of freely distributable software. The source will compile and run out of the box on most UNIX platforms.

Consult the [Developer FAQ](#) for more information on getting the source code and compiling it.

### 1.1.8 How do I get documentation on Python?

The standard documentation for the current stable version of Python is available at <http://docs.python.org/>. PDF, plain text, and downloadable HTML versions are also available at <http://docs.python.org/download.html>.

The documentation is written in reStructuredText and processed by the [Sphinx documentation tool](#). The reStructuredText source for the documentation is part of the Python source distribution.

### 1.1.9 I've never programmed before. Is there a Python tutorial?

There are numerous tutorials and books available. The standard documentation includes *tutorial-index*.

Consult the [Beginner's Guide](#) to find information for beginning Python programmers, including lists of tutorials.

### 1.1.10 Is there a newsgroup or mailing list devoted to Python?

There is a newsgroup, `comp.lang.python`, and a mailing list, `python-list`. The newsgroup and mailing list are gatewayed into each other – if you can read news it's unnecessary to subscribe to the mailing list. `comp.lang.python` is high-traffic, receiving hundreds of postings every day, and Usenet readers are often more able to cope with this volume.

Announcements of new software releases and events can be found in `comp.lang.python.announce`, a low-traffic moderated list that receives about five postings per day. It's available as [the python-announce mailing list](#).

More info about other mailing lists and newsgroups can be found at <http://www.python.org/community/lists/>.

### 1.1.11 How do I get a beta test version of Python?

Alpha and beta releases are available from <http://www.python.org/download/>. All releases are announced on the `comp.lang.python` and `comp.lang.python.announce` newsgroups and on the Python home page at <http://www.python.org/>; an RSS feed of news is available.

You can also access the development version of Python through Subversion. See <http://docs.python.org/devguide/faq> for details.

### 1.1.12 How do I submit bug reports and patches for Python?

To report a bug or submit a patch, please use the Roundup installation at <http://bugs.python.org/>.

You must have a Roundup account to report bugs; this makes it possible for us to contact you if we have follow-up questions. It will also enable Roundup to send you updates as we act on your bug. If you had previously used SourceForge to report bugs to Python, you can obtain your Roundup password through Roundup's [password reset procedure](#).

For more information on how Python is developed, consult [the Python Developer's Guide](#).

### 1.1.13 Are there any published articles about Python that I can reference?

It's probably best to cite your favorite book about Python.

The very first article about Python was written in 1991 and is now quite outdated.

Guido van Rossum and Jelke de Boer, "Interactively Testing Remote Servers Using the Python Programming Language", CWI Quarterly, Volume 4, Issue 4 (December 1991), Amsterdam, pp 283-303.

### 1.1.14 Are there any books on Python?

Yes, there are many, and more are being published. See the `python.org` wiki at <http://wiki.python.org/moin/PythonBooks> for a list.

You can also search online bookstores for "Python" and filter out the Monty Python references; or perhaps search for "Python" and "language".

### 1.1.15 Where in the world is `www.python.org` located?

It's currently in Amsterdam, graciously hosted by [XS4ALL](#). Thanks to Thomas Wouters for his work in arranging `python.org`'s hosting.

### 1.1.16 Why is it called Python?

When he began implementing Python, Guido van Rossum was also reading the published scripts from “[Monty Python’s Flying Circus](#)”, a BBC comedy series from the 1970s. Van Rossum thought he needed a name that was short, unique, and slightly mysterious, so he decided to call the language Python.

### 1.1.17 Do I have to like “Monty Python’s Flying Circus”?

No, but it helps. :)

## 1.2 Python in the real world

### 1.2.1 How stable is Python?

Very stable. New, stable releases have been coming out roughly every 6 to 18 months since 1991, and this seems likely to continue. Currently there are usually around 18 months between major releases.

The developers issue “bugfix” releases of older versions, so the stability of existing releases gradually improves. Bugfix releases, indicated by a third component of the version number (e.g. 2.5.3, 2.6.2), are managed for stability; only fixes for known problems are included in a bugfix release, and it’s guaranteed that interfaces will remain the same throughout a series of bugfix releases.

The latest stable releases can always be found on the [Python download page](#). There are two recommended production-ready versions at this point in time, because at the moment there are two branches of stable releases: 2.x and 3.x. Python 3.x may be less useful than 2.x, since currently there is more third party software available for Python 2 than for Python 3. Python 2 code will generally not run unchanged in Python 3.

### 1.2.2 How many people are using Python?

There are probably tens of thousands of users, though it’s difficult to obtain an exact count.

Python is available for free download, so there are no sales figures, and it’s available from many different sites and packaged with many Linux distributions, so download statistics don’t tell the whole story either.

The `comp.lang.python` newsgroup is very active, but not all Python users post to the group or even read it.

### 1.2.3 Have any significant projects been done in Python?

See <http://python.org/about/success> for a list of projects that use Python. Consulting the proceedings for [past Python conferences](#) will reveal contributions from many different companies and organizations.

High-profile Python projects include [the Mailman mailing list manager](#) and [the Zope application server](#). Several Linux distributions, most notably [Red Hat](#), have written part or all of their installer and system administration software in Python. Companies that use Python internally include Google, Yahoo, and Lucasfilm Ltd.

### 1.2.4 What new developments are expected for Python in the future?

See <http://www.python.org/dev/peps/> for the Python Enhancement Proposals (PEPs). PEPs are design documents describing a suggested new feature for Python, providing a concise technical specification and a rationale. Look for a PEP titled “Python X.Y Release Schedule”, where X.Y is a version that hasn’t been publicly released yet.

New development is discussed on [the python-dev mailing list](#).

### 1.2.5 Is it reasonable to propose incompatible changes to Python?

In general, no. There are already millions of lines of Python code around the world, so any change in the language that invalidates more than a very small fraction of existing programs has to be frowned upon. Even if you can provide a conversion program, there's still the problem of updating all documentation; many books have been written about Python, and we don't want to invalidate them all at a single stroke.

Providing a gradual upgrade path is necessary if a feature has to be changed.

**PEP 5** describes the procedure followed for introducing backward-incompatible changes while minimizing disruption for users.

### 1.2.6 Is Python Y2K (Year 2000) Compliant?

As of August, 2003 no major problems have been reported and Y2K compliance seems to be a non-issue.

Python does very few date calculations and for those it does perform relies on the C library functions. Python generally represents times either as seconds since 1970 or as a (year, month, day, ...) tuple where the year is expressed with four digits, which makes Y2K bugs unlikely. So as long as your C library is okay, Python should be okay. Of course, it's possible that a particular application written in Python makes assumptions about 2-digit years.

Because Python is available free of charge, there are no absolute guarantees. If there *are* unforeseen problems, liability is the user's problem rather than the developers', and there is nobody you can sue for damages. The Python copyright notice contains the following disclaimer:

4. PSF is making Python 2.3 available to Licensee on an "AS IS" basis. PSF MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF EXAMPLE, BUT NOT LIMITATION, PSF MAKES NO AND DISCLAIMS ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF PYTHON 2.3 WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.

5. PSF SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF PYTHON 2.3 FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A RESULT OF MODIFYING, DISTRIBUTING, OR OTHERWISE USING PYTHON 2.3, OR ANY DERIVATIVE THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.

The good news is that *if* you encounter a problem, you have full source available to track it down and fix it. This is one advantage of an open source programming environment.

### 1.2.7 Is Python a good language for beginning programmers?

Yes.

It is still common to start students with a procedural and statically typed language such as Pascal, C, or a subset of C++ or Java. Students may be better served by learning Python as their first language. Python has a very simple and consistent syntax and a large standard library and, most importantly, using Python in a beginning programming course lets students concentrate on important programming skills such as problem decomposition and data type design. With Python, students can be quickly introduced to basic concepts such as loops and procedures. They can probably even work with user-defined objects in their very first course.

For a student who has never programmed before, using a statically typed language seems unnatural. It presents additional complexity that the student must master and slows the pace of the course. The students are trying to learn to think like a computer, decompose problems, design consistent interfaces, and encapsulate data. While learning to use a statically typed language is important in the long term, it is not necessarily the best topic to address in the students' first programming course.

Many other aspects of Python make it a good first language. Like Java, Python has a large standard library so that students can be assigned programming projects very early in the course that *do* something. Assignments aren't restricted to the standard four-function calculator and check balancing programs. By using the standard library, students can gain the satisfaction of working on realistic applications as they learn the fundamentals of

programming. Using the standard library also teaches students about code reuse. Third-party modules such as PyGame are also helpful in extending the students' reach.

Python's interactive interpreter enables students to test language features while they're programming. They can keep a window with the interpreter running while they enter their program's source in another window. If they can't remember the methods for a list, they can do something like this:

```
>>> L = []
>>> dir(L)
['append', 'count', 'extend', 'index', 'insert', 'pop', 'remove',
'reverse', 'sort']
>>> help(L.append)
Help on built-in function append:

append(...)
    L.append(object) -- append object to end
>>> L.append(1)
>>> L
[1]
```

With the interpreter, documentation is never far from the student as he's programming.

There are also good IDEs for Python. IDLE is a cross-platform IDE for Python that is written in Python using Tkinter. PythonWin is a Windows-specific IDE. Emacs users will be happy to know that there is a very good Python mode for Emacs. All of these programming environments provide syntax highlighting, auto-indenting, and access to the interactive interpreter while coding. Consult <http://www.python.org/editors/> for a full list of Python editing environments.

If you want to discuss Python's use in education, you may be interested in joining [the edu-sig mailing list](#).



# PROGRAMMING FAQ

## Contents

- Programming FAQ
  - General Questions
    - \* Is there a source code level debugger with breakpoints, single-stepping, etc.?
    - \* Is there a tool to help find bugs or perform static analysis?
    - \* How can I create a stand-alone binary from a Python script?
    - \* Are there coding standards or a style guide for Python programs?
  - Core Language
    - \* Why am I getting an UnboundLocalError when the variable has a value?
    - \* What are the rules for local and global variables in Python?
    - \* How do I share global variables across modules?
    - \* What are the “best practices” for using import in a module?
    - \* How can I pass optional or keyword parameters from one function to another?
    - \* How do I write a function with output parameters (call by reference)?
    - \* How do you make a higher order function in Python?
    - \* How do I copy an object in Python?
    - \* How can I find the methods or attributes of an object?
    - \* How can my code discover the name of an object?
    - \* What’s up with the comma operator’s precedence?
    - \* Is there an equivalent of C’s “?:” ternary operator?
    - \* Is it possible to write obfuscated one-liners in Python?
  - Numbers and strings
    - \* How do I specify hexadecimal and octal integers?
    - \* Why does -22 // 10 return -3?
    - \* How do I convert a string to a number?
    - \* How do I convert a number to a string?
    - \* How do I modify a string in place?
    - \* How do I use strings to call functions/methods?
    - \* Is there an equivalent to Perl’s chomp() for removing trailing newlines from strings?
    - \* Is there a scanf() or sscanf() equivalent?
    - \* What does ‘UnicodeDecodeError’ or ‘UnicodeEncodeError’ error mean?
  - Performance
    - \* My program is too slow. How do I speed it up?
    - \* What is the most efficient way to concatenate many strings together?
  - Sequences (Tuples/Lists)
    - \* How do I convert between tuples and lists?
    - \* What’s a negative index?
    - \* How do I iterate over a sequence in reverse order?
    - \* How do you remove duplicates from a list?
    - \* How do you make an array in Python?
    - \* How do I create a multidimensional list?
    - \* How do I apply a method to a sequence of objects?
  - Dictionaries
    - \* How can I get a dictionary to display its keys in a consistent order?
    - \* I want to do a complicated sort: can you do a Schwartzian Transform in Python?
    - \* How can I sort one list by values from another list?
  - Objects
    - \* What is a class?
    - \* What is a method?
    - \* What is self?
    - \* How do I check if an object is an instance of a given class or of a subclass of it?
    - \* What is delegation?
    - \* How do I call a method defined in a base class from a derived class that overrides it?
    - \* How can I organize my code to make it easier to change the base class?
    - \* How do I create static class data and static class methods?
    - \* How can I overload constructors (or methods) in Python?
    - \* I try to use \_\_spam and I get an error about \_SomeClassName\_\_spam.
    - \* My class defines \_\_del\_\_ but it is not called when I delete the object.
    - \* How do I get a list of all instances of a given class?

- \* How do I create a .pyc file?
- \* How do I find the current module name?
- \* How can I have modules that mutually import each other?
- \* import (‘x y z’) returns <module ‘x’>; how do I get z?

## 2.1 General Questions

### 2.1.1 Is there a source code level debugger with breakpoints, single-stepping, etc.?

Yes.

The `pdb` module is a simple but adequate console-mode debugger for Python. It is part of the standard Python library, and is documented in the Library Reference Manual. You can also write your own debugger by using the code for `pdb` as an example.

The IDLE interactive development environment, which is part of the standard Python distribution (normally available as `Tools/scripts/idle`), includes a graphical debugger. There is documentation for the IDLE debugger at <http://www.python.org/idle/doc/idle2.html#Debugger>.

PythonWin is a Python IDE that includes a GUI debugger based on `pdb`. The Pythonwin debugger colors breakpoints and has quite a few cool features such as debugging non-Pythonwin programs. Pythonwin is available as part of the [Python for Windows Extensions](#) project and as a part of the ActivePython distribution (see <http://www.activestate.com/Products/ActivePython/index.html>).

**Boa Constructor** is an IDE and GUI builder that uses `wxWidgets`. It offers visual frame creation and manipulation, an object inspector, many views on the source like object browsers, inheritance hierarchies, doc string generated html documentation, an advanced debugger, integrated help, and Zope support.

**Eric** is an IDE built on `PyQt` and the `Scintilla` editing component.

`Pydb` is a version of the standard Python debugger `pdb`, modified for use with `DDD` (Data Display Debugger), a popular graphical debugger front end. `Pydb` can be found at <http://bashdb.sourceforge.net/pydb/> and `DDD` can be found at <http://www.gnu.org/software/ddd>.

There are a number of commercial Python IDEs that include graphical debuggers. They include:

- Wing IDE (<http://wingware.com/>)
- Komodo IDE (<http://www.activestate.com/Products/Komodo>)

### 2.1.2 Is there a tool to help find bugs or perform static analysis?

Yes.

`PyChecker` is a static analysis tool that finds bugs in Python source code and warns about code complexity and style. You can get `PyChecker` from <http://pychecker.sf.net>.

`Pylint` is another tool that checks if a module satisfies a coding standard, and also makes it possible to write plugins to add a custom feature. In addition to the bug checking that `PyChecker` performs, `Pylint` offers some additional features such as checking line length, whether variable names are well-formed according to your coding standard, whether declared interfaces are fully implemented, and more. [http://www.logilab.org/card/pylint\\_manual](http://www.logilab.org/card/pylint_manual) provides a full list of `Pylint`'s features.

### 2.1.3 How can I create a stand-alone binary from a Python script?

You don't need the ability to compile Python to C code if all you want is a stand-alone program that users can download and run without having to install the Python distribution first. There are a number of tools that determine the set of modules required by a program and bind these modules together with a Python binary to produce a single executable.

One is to use the `freeze` tool, which is included in the Python source tree as `Tools/freeze`. It converts Python byte code to C arrays; a C compiler you can embed all your modules into a new program, which is then linked with the standard Python modules.

It works by scanning your source recursively for import statements (in both forms) and looking for the modules in the standard Python path as well as in the source directory (for built-in modules). It then turns the bytecode for

modules written in Python into C code (array initializers that can be turned into code objects using the marshal module) and creates a custom-made config file that only contains those built-in modules which are actually used in the program. It then compiles the generated C code and links it with the rest of the Python interpreter to form a self-contained binary which acts exactly like your script.

Obviously, freeze requires a C compiler. There are several other utilities which don't. One is Thomas Heller's py2exe (Windows only) at

<http://www.py2exe.org/>

Another is Christian Tismer's **SQFREEZE** which appends the byte code to a specially-prepared Python interpreter that can find the byte code in the executable.

Other tools include Fredrik Lundh's **Squeeze** and Anthony Tuininga's **cx\_Freeze**.

### 2.1.4 Are there coding standards or a style guide for Python programs?

Yes. The coding style required for standard library modules is documented as

**PEP 8**.

## 2.2 Core Language

### 2.2.1 Why am I getting an UnboundLocalError when the variable has a value?

It can be a surprise to get the UnboundLocalError in previously working code when it is modified by adding an assignment statement somewhere in the body of a function.

This code:

```
>>> x = 10
>>> def bar():
...     print(x)
>>> bar()
10
```

works, but this code:

```
>>> x = 10
>>> def foo():
...     print(x)
...     x += 1
```

results in an UnboundLocalError:

```
>>> foo()
Traceback (most recent call last):
...
UnboundLocalError: local variable 'x' referenced before assignment
```

This is because when you make an assignment to a variable in a scope, that variable becomes local to that scope and shadows any similarly named variable in the outer scope. Since the last statement in foo assigns a new value to x, the compiler recognizes it as a local variable. Consequently when the earlier print(x) attempts to print the uninitialized local variable and an error results.

In the example above you can access the outer scope variable by declaring it global:

```
>>> x = 10
>>> def foobar():
...     global x
...     print(x)
...     x += 1
```

```
>>> foobar()
10
```

This explicit declaration is required in order to remind you that (unlike the superficially analogous situation with class and instance variables) you are actually modifying the value of the variable in the outer scope:

```
>>> print(x)
11
```

You can do a similar thing in a nested scope using the `nonlocal` keyword:

```
>>> def foo():
...     x = 10
...     def bar():
...         nonlocal x
...         print(x)
...         x += 1
...     bar()
...     print(x)
>>> foo()
10
11
```

## 2.2.2 What are the rules for local and global variables in Python?

In Python, variables that are only referenced inside a function are implicitly global. If a variable is assigned a new value anywhere within the function's body, it's assumed to be a local. If a variable is ever assigned a new value inside the function, the variable is implicitly local, and you need to explicitly declare it as 'global'.

Though a bit surprising at first, a moment's consideration explains this. On one hand, requiring `global` for assigned variables provides a bar against unintended side-effects. On the other hand, if `global` was required for all global references, you'd be using `global` all the time. You'd have to declare as `global` every reference to a built-in function or to a component of an imported module. This clutter would defeat the usefulness of the `global` declaration for identifying side-effects.

## 2.2.3 How do I share global variables across modules?

The canonical way to share information across modules within a single program is to create a special module (often called `config` or `cfg`). Just import the `config` module in all modules of your application; the module then becomes available as a global name. Because there is only one instance of each module, any changes made to the module object get reflected everywhere. For example:

`config.py`:

```
x = 0    # Default value of the 'x' configuration setting
```

`mod.py`:

```
import config
config.x = 1
```

`main.py`:

```
import config
import mod
print(config.x)
```

Note that using a module is also the basis for implementing the Singleton design pattern, for the same reason.

## 2.2.4 What are the “best practices” for using import in a module?

In general, don't use `from modulename import *`. Doing so clutters the importer's namespace. Some people avoid this idiom even with the few modules that were designed to be imported in this manner. Modules designed in this manner include `tkinter`, and `threading`.

Import modules at the top of a file. Doing so makes it clear what other modules your code requires and avoids questions of whether the module name is in scope. Using one import per line makes it easy to add and delete module imports, but using multiple imports per line uses less screen space.

It's good practice if you import modules in the following order:

1. standard library modules – e.g. `sys`, `os`, `getopt`, `re`
2. third-party library modules (anything installed in Python's site-packages directory) – e.g. `mx.DateTime`, `ZODB`, `PIL.Image`, etc.
3. locally-developed modules

Never use relative package imports. If you're writing code that's in the `package.sub.m1` module and want to import `package.sub.m2`, do not just write `from . import m2`, even though it's legal. Write `from package.sub import m2` instead. See [PEP 328](#) for details.

It is sometimes necessary to move imports to a function or class to avoid problems with circular imports. Gordon McMillan says:

Circular imports are fine where both modules use the “import <module>” form of import. They fail when the 2nd module wants to grab a name out of the first (“from module import name”) and the import is at the top level. That's because names in the 1st are not yet available, because the first module is busy importing the 2nd.

In this case, if the second module is only used in one function, then the import can easily be moved into that function. By the time the import is called, the first module will have finished initializing, and the second module can do its import.

It may also be necessary to move imports out of the top level of code if some of the modules are platform-specific. In that case, it may not even be possible to import all of the modules at the top of the file. In this case, importing the correct modules in the corresponding platform-specific code is a good option.

Only move imports into a local scope, such as inside a function definition, if it's necessary to solve a problem such as avoiding a circular import or are trying to reduce the initialization time of a module. This technique is especially helpful if many of the imports are unnecessary depending on how the program executes. You may also want to move imports into a function if the modules are only ever used in that function. Note that loading a module the first time may be expensive because of the one time initialization of the module, but loading a module multiple times is virtually free, costing only a couple of dictionary lookups. Even if the module name has gone out of scope, the module is probably available in `sys.modules`.

If only instances of a specific class use a module, then it is reasonable to import the module in the class's `__init__` method and then assign the module to an instance variable so that the module is always available (via that instance variable) during the life of the object. Note that to delay an import until the class is instantiated, the import must be inside a method. Putting the import inside the class but outside of any method still causes the import to occur when the module is initialized.

## 2.2.5 How can I pass optional or keyword parameters from one function to another?

Collect the arguments using the `*` and `**` specifiers in the function's parameter list; this gives you the positional arguments as a tuple and the keyword arguments as a dictionary. You can then pass these arguments when calling another function by using `*` and `**`:

```
def f(x, *args, **kwargs):  
    ...  
    kwargs['width'] = '14.3c'
```

```
...
g(x, *args, **kwargs)
```

## 2.2.6 How do I write a function with output parameters (call by reference)?

Remember that arguments are passed by assignment in Python. Since assignment just creates references to objects, there's no alias between an argument name in the caller and callee, and so no call-by-reference per se. You can achieve the desired effect in a number of ways.

1. By returning a tuple of the results:

```
def func2(a, b):
    a = 'new-value'           # a and b are local names
    b = b + 1                 # assigned to new objects
    return a, b              # return new values

x, y = 'old-value', 99
x, y = func2(x, y)
print(x, y)                  # output: new-value 100
```

This is almost always the clearest solution.

2. By using global variables. This isn't thread-safe, and is not recommended.
3. By passing a mutable (changeable in-place) object:

```
def func1(a):
    a[0] = 'new-value'       # 'a' references a mutable list
    a[1] = a[1] + 1          # changes a shared object

args = ['old-value', 99]
func1(args)
print(args[0], args[1])     # output: new-value 100
```

4. By passing in a dictionary that gets mutated:

```
def func3(args):
    args['a'] = 'new-value'   # args is a mutable dictionary
    args['b'] = args['b'] + 1 # change it in-place

args = {'a': 'old-value', 'b': 99}
func3(args)
print(args['a'], args['b'])
```

5. Or bundle up values in a class instance:

```
class callByRef:
    def __init__(self, **args):
        for (key, value) in args.items():
            setattr(self, key, value)

def func4(args):
    args.a = 'new-value'      # args is a mutable callByRef
    args.b = args.b + 1       # change object in-place

args = callByRef(a='old-value', b=99)
func4(args)
print(args.a, args.b)
```

There's almost never a good reason to get this complicated.

Your best choice is to return a tuple containing the multiple results.

### 2.2.7 How do you make a higher order function in Python?

You have two choices: you can use nested scopes or you can use callable objects. For example, suppose you wanted to define `linear(a,b)` which returns a function `f(x)` that computes the value `a*x+b`. Using nested scopes:

```
def linear(a, b):
    def result(x):
        return a * x + b
    return result
```

Or using a callable object:

```
class linear:

    def __init__(self, a, b):
        self.a, self.b = a, b

    def __call__(self, x):
        return self.a * x + self.b
```

In both cases,

```
taxes = linear(0.3, 2)
```

gives a callable object where `taxes(10e6) == 0.3 * 10e6 + 2`.

The callable object approach has the disadvantage that it is a bit slower and results in slightly longer code. However, note that a collection of callables can share their signature via inheritance:

```
class exponential(linear):
    # __init__ inherited
    def __call__(self, x):
        return self.a * (x ** self.b)
```

Object can encapsulate state for several methods:

```
class counter:

    value = 0

    def set(self, x):
        self.value = x

    def up(self):
        self.value = self.value + 1

    def down(self):
        self.value = self.value - 1
```

```
count = counter()
inc, dec, reset = count.up, count.down, count.set
```

Here `inc()`, `dec()` and `reset()` act like functions which share the same counting variable.

### 2.2.8 How do I copy an object in Python?

In general, try `copy.copy()` or `copy.deepcopy()` for the general case. Not all objects can be copied, but most can.

Some objects can be copied more easily. Dictionaries have a `copy()` method:

```
newdict = olddict.copy()
```

Sequences can be copied by slicing:

```
new_l = l[:]
```

## 2.2.9 How can I find the methods or attributes of an object?

For an instance `x` of a user-defined class, `dir(x)` returns an alphabetized list of the names containing the instance attributes and methods and attributes defined by its class.

## 2.2.10 How can my code discover the name of an object?

Generally speaking, it can't, because objects don't really have names. Essentially, assignment always binds a name to a value; The same is true of `def` and `class` statements, but in that case the value is a callable. Consider the following code:

```
class A:
    pass

B = A

a = B()
b = a
print(b)
<__main__.A object at 0x16D07CC>
print(a)
<__main__.A object at 0x16D07CC>
```

Arguably the class has a name: even though it is bound to two names and invoked through the name `B` the created instance is still reported as an instance of class `A`. However, it is impossible to say whether the instance's name is `a` or `b`, since both names are bound to the same value.

Generally speaking it should not be necessary for your code to “know the names” of particular values. Unless you are deliberately writing introspective programs, this is usually an indication that a change of approach might be beneficial.

In `comp.lang.python`, Fredrik Lundh once gave an excellent analogy in answer to this question:

The same way as you get the name of that cat you found on your porch: the cat (object) itself cannot tell you its name, and it doesn't really care – so the only way to find out what it's called is to ask all your neighbours (namespaces) if it's their cat (object)...

....and don't be surprised if you'll find that it's known by many names, or no name at all!

## 2.2.11 What's up with the comma operator's precedence?

Comma is not an operator in Python. Consider this session:

```
>>> "a" in "b", "a"
(False, 'a')
```

Since the comma is not an operator, but a separator between expressions the above is evaluated as if you had entered:

```
>>> ("a" in "b"), "a"
```

not:

```
>>> "a" in ("b", "a")
```

The same is true of the various assignment operators (`=`, `+=` etc). They are not truly operators but syntactic delimiters in assignment statements.

## 2.2.12 Is there an equivalent of C's "?:" ternary operator?

Yes, there is. The syntax is as follows:

```
[on_true] if [expression] else [on_false]
```

```
x, y = 50, 25
small = x if x < y else y
```

Before this syntax was introduced in Python 2.5, a common idiom was to use logical operators:

```
[expression] and [on_true] or [on_false]
```

However, this idiom is unsafe, as it can give wrong results when *on\_true* has a false boolean value. Therefore, it is always better to use the ... `if ... else ...` form.

## 2.2.13 Is it possible to write obfuscated one-liners in Python?

Yes. Usually this is done by nesting `lambda` within `lambda`. See the following three examples, due to Ulf Bartelt:

```
from functools import reduce

# Primes < 1000
print(list(filter(None, map(lambda y: y * reduce(lambda x, y: x * y != 0,
map(lambda x, y: y % x, range(2, int(pow(y, 0.5) + 1))), 1), range(2, 1000)))))

# First 10 Fibonacci numbers
print(list(map(lambda x, f: lambda x, f: (f(x - 1, f) + f(x - 2, f)) if x > 1 else 1:
f(x, f), range(10))))

# Mandelbrot set
print((lambda Ru, Ro, Iu, Io, IM, Sx, Sy: reduce(lambda x, y: x + y, map(lambda y,
Iu=Iu, Io=Io, Ru=Ru, Ro=Ro, Sy=Sy, L=lambda yc, Iu=Iu, Io=Io, Ru=Ru, Ro=Ro, i=IM,
Sx=Sx, Sy=Sy: reduce(lambda x, y: x + y, map(lambda x, xc=Ru, yc=yc, Ru=Ru, Ro=Ro,
i=i, Sx=Sx, F=lambda xc, yc, x, y, k, f: lambda xc, yc, x, y, k, f: (k <= 0) or (x * x + y * y
>= 4.0) or 1 + f(xc, yc, x * x - y * y + xc, 2.0 * x * y + yc, k - 1, f): f(xc, yc, x, y, k, f): chr(
64 + F(Ru + x * (Ro - Ru) / Sx, yc, 0, 0, i)), range(Sx))) : L(Iu + y * (Io - Iu) / Sy), range(Sy
))))(-2.1, 0.7, -1.2, 1.2, 30, 80, 24))
#      \___ ___/ \___ ___/ | | | lines on screen
#      V      V      | | columns on screen
#      /      /      | | maximum of "iterations"
#      /      /      | | range on y axis
#      /      /      | | range on x axis
```

Don't try this at home, kids!

## 2.3 Numbers and strings

### 2.3.1 How do I specify hexadecimal and octal integers?

To specify an octal digit, precede the octal value with a zero, and then a lower or uppercase "o". For example, to set the variable "a" to the octal value "10" (8 in decimal), type:

```
>>> a = 0o10
>>> a
8
```

Hexadecimal is just as easy. Simply precede the hexadecimal number with a zero, and then a lower or uppercase “x”. Hexadecimal digits can be specified in lower or uppercase. For example, in the Python interpreter:

```
>>> a = 0xa5
>>> a
165
>>> b = 0xB2
>>> b
178
```

### 2.3.2 Why does `-22 // 10` return `-3`?

It’s primarily driven by the desire that `i % j` have the same sign as `j`. If you want that, and also want:

```
i == (i // j) * j + (i % j)
```

then integer division has to return the floor. C also requires that identity to hold, and then compilers that truncate `i // j` need to make `i % j` have the same sign as `i`.

There are few real use cases for `i % j` when `j` is negative. When `j` is positive, there are many, and in virtually all of them it’s more useful for `i % j` to be  $\geq 0$ . If the clock says 10 now, what did it say 200 hours ago? `-190 % 12 == 2` is useful; `-190 % 12 == -10` is a bug waiting to bite.

### 2.3.3 How do I convert a string to a number?

For integers, use the built-in `int()` type constructor, e.g. `int('144') == 144`. Similarly, `float()` converts to floating-point, e.g. `float('144') == 144.0`.

By default, these interpret the number as decimal, so that `int('0144') == 144` and `int('0x144')` raises `ValueError`. `int(string, base)` takes the base to convert from as a second optional argument, so `int('0x144', 16) == 324`. If the base is specified as 0, the number is interpreted using Python’s rules: a leading ‘0’ indicates octal, and ‘0x’ indicates a hex number.

Do not use the built-in function `eval()` if all you need is to convert strings to numbers. `eval()` will be significantly slower and it presents a security risk: someone could pass you a Python expression that might have unwanted side effects. For example, someone could pass `__import__('os').system("rm -rf $HOME")` which would erase your home directory.

`eval()` also has the effect of interpreting numbers as Python expressions, so that e.g. `eval('09')` gives a syntax error because Python does not allow leading ‘0’ in a decimal number (except ‘0’).

### 2.3.4 How do I convert a number to a string?

To convert, e.g., the number 144 to the string ‘144’, use the built-in type constructor `str()`. If you want a hexadecimal or octal representation, use the built-in functions `hex()` or `oct()`. For fancy formatting, see the *string-formatting* section, e.g. `"{:04d}".format(144)` yields ‘0144’ and `"{: .3f}".format(1/3)` yields ‘0.333’.

### 2.3.5 How do I modify a string in place?

You can’t, because strings are immutable. In most situations, you should simply construct a new string from the various parts you want to assemble it from. However, if you need an object with the ability to modify in-place unicode data, try using a `io.StringIO` object or the `array` module:

```
>>> s = "Hello, world"
>>> sio = io.StringIO(s)
>>> sio.getvalue()
'Hello, world'
>>> sio.seek(7)
```

```
7
>>> sio.write("there!")
6
>>> sio.getvalue()
'Hello, there!'

>>> import array
>>> a = array.array('u', s)
>>> print(a)
array('u', 'Hello, world')
>>> a[0] = 'y'
>>> print(a)
array('u', 'yello world')
>>> a.tounicode()
'yello, world'
```

## 2.3.6 How do I use strings to call functions/methods?

There are various techniques.

- The best is to use a dictionary that maps strings to functions. The primary advantage of this technique is that the strings do not need to match the names of the functions. This is also the primary technique used to emulate a case construct:

```
def a():
    pass
```

```
def b():
    pass
```

```
dispatch = {'go': a, 'stop': b}  # Note lack of parens for funcs
```

```
dispatch[get_input()]()  # Note trailing parens to call function
```

- Use the built-in function `getattr()`:

```
import foo
getattr(foo, 'bar')()
```

Note that `getattr()` works on any object, including classes, class instances, modules, and so on.

This is used in several places in the standard library, like this:

```
class Foo:
    def do_foo(self):
        ...

    def do_bar(self):
        ...
```

```
f = getattr(foo_instance, 'do_' + opname)
f()
```

- Use `locals()` or `eval()` to resolve the function name:

```
def myFunc():
    print("hello")
```

```
fname = "myFunc"
```

```
f = locals()[fname]
f()
```

```
f = eval(fname)
f()
```

Note: Using `eval()` is slow and dangerous. If you don't have absolute control over the contents of the string, someone could pass a string that resulted in an arbitrary function being executed.

### 2.3.7 Is there an equivalent to Perl's `chomp()` for removing trailing newlines from strings?

You can use `S.rstrip("\r\n")` to remove all occurrences of any line terminator from the end of the string `S` without removing other trailing whitespace. If the string `S` represents more than one line, with several empty lines at the end, the line terminators for all the blank lines will be removed:

```
>>> lines = ("line 1 \r\n"
...         "\r\n"
...         "\r\n")
>>> lines.rstrip("\n\r")
'line 1 '
```

Since this is typically only desired when reading text one line at a time, using `S.rstrip()` this way works well.

### 2.3.8 Is there a `scanf()` or `sscanf()` equivalent?

Not as such.

For simple input parsing, the easiest approach is usually to split the line into whitespace-delimited words using the `split()` method of string objects and then convert decimal strings to numeric values using `int()` or `float()`. `split()` supports an optional “sep” parameter which is useful if the line uses something other than whitespace as a separator.

For more complicated input parsing, regular expressions are more powerful than C's `sscanf()` and better suited for the task.

### 2.3.9 What does ‘UnicodeDecodeError’ or ‘UnicodeEncodeError’ error mean?

See the *unicode-howto*.

## 2.4 Performance

### 2.4.1 My program is too slow. How do I speed it up?

That's a tough one, in general. First, here are a list of things to remember before diving further:

- Performance characteristics vary across Python implementations. This FAQ focusses on *CPython*.
- Behaviour can vary across operating systems, especially when talking about I/O or multi-threading.
- You should always find the hot spots in your program *before* attempting to optimize any code (see the `profile` module).
- Writing benchmark scripts will allow you to iterate quickly when searching for improvements (see the `timeit` module).
- It is highly recommended to have good code coverage (through unit testing or any other technique) before potentially introducing regressions hidden in sophisticated optimizations.

That being said, there are many tricks to speed up Python code. Here are some general principles which go a long way towards reaching acceptable performance levels:

- Making your algorithms faster (or changing to faster ones) can yield much larger benefits than trying to sprinkle micro-optimization tricks all over your code.
- Use the right data structures. Study documentation for the *builtin-types* and the `collections` module.
- When the standard library provides a primitive for doing something, it is likely (although not guaranteed) to be faster than any alternative you may come up with. This is doubly true for primitives written in C, such as builtins and some extension types. For example, be sure to use either the `list.sort()` built-in method or the related `sorted()` function to do sorting (and see the [sorting mini-HOWTO](#) for examples of moderately advanced usage).
- Abstractions tend to create indirections and force the interpreter to work more. If the levels of indirection outweigh the amount of useful work done, your program will be slower. You should avoid excessive abstraction, especially under the form of tiny functions or methods (which are also often detrimental to readability).

If you have reached the limit of what pure Python can allow, there are tools to take you further away. For example, [Cython](#) can compile a slightly modified version of Python code into a C extension, and can be used on many different platforms. Cython can take advantage of compilation (and optional type annotations) to make your code significantly faster than when interpreted. If you are confident in your C programming skills, you can also *write a C extension module* yourself.

#### See Also:

The wiki page devoted to [performance tips](#).

## 2.4.2 What is the most efficient way to concatenate many strings together?

`str` and `bytes` objects are immutable, therefore concatenating many strings together is inefficient as each concatenation creates a new object. In the general case, the total runtime cost is quadratic in the total string length.

To accumulate many `str` objects, the recommended idiom is to place them into a list and call `str.join()` at the end:

```
chunks = []
for s in my_strings:
    chunks.append(s)
result = ''.join(chunks)
```

(another reasonably efficient idiom is to use `io.StringIO`)

To accumulate many `bytes` objects, the recommended idiom is to extend a `bytearray` object using in-place concatenation (the `+=` operator):

```
result = bytearray()
for b in my_bytes_objects:
    result += b
```

## 2.5 Sequences (Tuples/Lists)

### 2.5.1 How do I convert between tuples and lists?

The type constructor `tuple(seq)` converts any sequence (actually, any iterable) into a tuple with the same items in the same order.

For example, `tuple([1, 2, 3])` yields `(1, 2, 3)` and `tuple('abc')` yields `('a', 'b', 'c')`. If the argument is a tuple, it does not make a copy but returns the same object, so it is cheap to call `tuple()` when you aren't sure that an object is already a tuple.

The type constructor `list(seq)` converts any sequence or iterable into a list with the same items in the same order. For example, `list((1, 2, 3))` yields `[1, 2, 3]` and `list('abc')` yields `['a', 'b', 'c']`. If the argument is a list, it makes a copy just like `seq[:]` would.

## 2.5.2 What's a negative index?

Python sequences are indexed with positive numbers and negative numbers. For positive numbers 0 is the first index 1 is the second index and so forth. For negative indices -1 is the last index and -2 is the penultimate (next to last) index and so forth. Think of `seq[-n]` as the same as `seq[len(seq)-n]`.

Using negative indices can be very convenient. For example `S[:-1]` is all of the string except for its last character, which is useful for removing the trailing newline from a string.

## 2.5.3 How do I iterate over a sequence in reverse order?

Use the `reversed()` built-in function, which is new in Python 2.4:

```
for x in reversed(sequence):
    ... # do something with x...
```

This won't touch your original sequence, but build a new copy with reversed order to iterate over.

With Python 2.3, you can use an extended slice syntax:

```
for x in sequence[::-1]:
    ... # do something with x...
```

## 2.5.4 How do you remove duplicates from a list?

See the Python Cookbook for a long discussion of many ways to do this:

<http://aspn.activestate.com/ASPN/Cookbook/Python/Recipe/52560>

If you don't mind reordering the list, sort it and then scan from the end of the list, deleting duplicates as you go:

```
if mylist:
    mylist.sort()
    last = mylist[-1]
    for i in range(len(mylist)-2, -1, -1):
        if last == mylist[i]:
            del mylist[i]
        else:
            last = mylist[i]
```

If all elements of the list may be used as set keys (i.e. they are all *hashable*) this is often faster

```
mylist = list(set(mylist))
```

This converts the list into a set, thereby removing duplicates, and then back into a list.

## 2.5.5 How do you make an array in Python?

Use a list:

```
["this", 1, "is", "an", "array"]
```

Lists are equivalent to C or Pascal arrays in their time complexity; the primary difference is that a Python list can contain objects of many different types.

The `array` module also provides methods for creating arrays of fixed types with compact representations, but they are slower to index than lists. Also note that the Numeric extensions and others define array-like structures with various characteristics as well.

To get Lisp-style linked lists, you can emulate cons cells using tuples:

```
lisp_list = ("like", ("this", ("example", None) ) )
```

If mutability is desired, you could use lists instead of tuples. Here the analogue of lisp car is `lisp_list[0]` and the analogue of cdr is `lisp_list[1]`. Only do this if you're sure you really need to, because it's usually a lot slower than using Python lists.

## 2.5.6 How do I create a multidimensional list?

You probably tried to make a multidimensional array like this:

```
A = [[None] * 2] * 3
```

This looks correct if you print it:

```
>>> A
[[None, None], [None, None], [None, None]]
```

But when you assign a value, it shows up in multiple places:

```
>>> A[0][0] = 5
>>> A
[[5, None], [5, None], [5, None]]
```

The reason is that replicating a list with `*` doesn't create copies, it only creates references to the existing objects. The `*3` creates a list containing 3 references to the same list of length two. Changes to one row will show in all rows, which is almost certainly not what you want.

The suggested approach is to create a list of the desired length first and then fill in each element with a newly created list:

```
A = [None] * 3
for i in range(3):
    A[i] = [None] * 2
```

This generates a list containing 3 different lists of length two. You can also use a list comprehension:

```
w, h = 2, 3
A = [[None] * w for i in range(h)]
```

Or, you can use an extension that provides a matrix datatype; [Numeric Python](#) is the best known.

## 2.5.7 How do I apply a method to a sequence of objects?

Use a list comprehension:

```
result = [obj.method() for obj in mylist]
```

## 2.6 Dictionaries

### 2.6.1 How can I get a dictionary to display its keys in a consistent order?

You can't. Dictionaries store their keys in an unpredictable order, so the display order of a dictionary's elements will be similarly unpredictable.

This can be frustrating if you want to save a printable version to a file, make some changes and then compare it with some other printed dictionary. In this case, use the `pprint` module to pretty-print the dictionary; the items will be presented in order sorted by the key.

A more complicated solution is to subclass `dict` to create a `SortedDict` class that prints itself in a predictable order. Here's one simpleminded implementation of such a class:

```
class SortedDict(dict):
    def __repr__(self):
        keys = sorted(self.keys())
        result = ("{!r}: {!r}".format(k, self[k]) for k in keys)
        return "{{{}}}".format(", ".join(result))

    __str__ = __repr__
```

This will work for many common situations you might encounter, though it's far from a perfect solution. The largest flaw is that if some values in the dictionary are also dictionaries, their values won't be presented in any particular order.

## 2.6.2 I want to do a complicated sort: can you do a Schwartzian Transform in Python?

The technique, attributed to Randal Schwartz of the Perl community, sorts the elements of a list by a metric which maps each element to its "sort value". In Python, just use the `key` argument for the `sort()` method:

```
Isorted = L[:]
Isorted.sort(key=lambda s: int(s[10:15]))
```

The `key` argument is new in Python 2.4, for older versions this kind of sorting is quite simple to do with list comprehensions. To sort a list of strings by their uppercase values:

```
tmp1 = [(x.upper(), x) for x in L] # Schwartzian transform
tmp1.sort()
Usorted = [x[1] for x in tmp1]
```

To sort by the integer value of a subfield extending from positions 10-15 in each string:

```
tmp2 = [(int(s[10:15]), s) for s in L] # Schwartzian transform
tmp2.sort()
Isorted = [x[1] for x in tmp2]
```

For versions prior to 3.0, `Isorted` may also be computed by

```
def intfield(s):
    return int(s[10:15])

def Icmp(s1, s2):
    return cmp(intfield(s1), intfield(s2))
```

```
Isorted = L[:]
Isorted.sort(Icmp)
```

but since this method calls `intfield()` many times for each element of `L`, it is slower than the Schwartzian Transform.

## 2.6.3 How can I sort one list by values from another list?

Merge them into an iterator of tuples, sort the resulting list, and then pick out the element you want.

```
>>> list1 = ["what", "I'm", "sorting", "by"]
>>> list2 = ["something", "else", "to", "sort"]
>>> pairs = zip(list1, list2)
>>> pairs = sorted(pairs)
>>> pairs
[('I'm', 'else'), ('by', 'sort'), ('sorting', 'to'), ('what', 'something')]
>>> result = [x[1] for x in pairs]
>>> result
['else', 'sort', 'to', 'something']
```

An alternative for the last step is:

```
>>> result = []
>>> for p in pairs: result.append(p[1])
```

If you find this more legible, you might prefer to use this instead of the final list comprehension. However, it is almost twice as slow for long lists. Why? First, the `append()` operation has to reallocate memory, and while it uses some tricks to avoid doing that each time, it still has to do it occasionally, and that costs quite a bit. Second, the expression “`result.append`” requires an extra attribute lookup, and third, there’s a speed reduction from having to make all those function calls.

## 2.7 Objects

### 2.7.1 What is a class?

A class is the particular object type created by executing a class statement. Class objects are used as templates to create instance objects, which embody both the data (attributes) and code (methods) specific to a datatype.

A class can be based on one or more other classes, called its base class(es). It then inherits the attributes and methods of its base classes. This allows an object model to be successively refined by inheritance. You might have a generic `Mailbox` class that provides basic accessor methods for a mailbox, and subclasses such as `MboxMailbox`, `MaildirMailbox`, `OutlookMailbox` that handle various specific mailbox formats.

### 2.7.2 What is a method?

A method is a function on some object `x` that you normally call as `x.name(arguments...)`. Methods are defined as functions inside the class definition:

```
class C:
    def meth(self, arg):
        return arg * 2 + self.attribute
```

### 2.7.3 What is self?

`Self` is merely a conventional name for the first argument of a method. A method defined as `meth(self, a, b, c)` should be called as `x.meth(a, b, c)` for some instance `x` of the class in which the definition occurs; the called method will think it is called as `meth(x, a, b, c)`.

See also *Why must ‘self’ be used explicitly in method definitions and calls?*.

### 2.7.4 How do I check if an object is an instance of a given class or of a subclass of it?

Use the built-in function `isinstance(obj, cls)`. You can check if an object is an instance of any of a number of classes by providing a tuple instead of a single class, e.g. `isinstance(obj, (class1, class2, ...))`, and can also check whether an object is one of Python’s built-in types, e.g. `isinstance(obj, str)` or `isinstance(obj, (int, float, complex))`.

Note that most programs do not use `isinstance()` on user-defined classes very often. If you are developing the classes yourself, a more proper object-oriented style is to define methods on the classes that encapsulate a particular behaviour, instead of checking the object’s class and doing a different thing based on what class it is. For example, if you have a function that does something:

```
def search(obj):
    if isinstance(obj, Mailbox):
        # ... code to search a mailbox
    elif isinstance(obj, Document):
```

```

    # ... code to search a document
elif ...

```

A better approach is to define a `search()` method on all the classes and just call it:

```

class Mailbox:
    def search(self):
        # ... code to search a mailbox

class Document:
    def search(self):
        # ... code to search a document

obj.search()

```

### 2.7.5 What is delegation?

Delegation is an object oriented technique (also called a design pattern). Let's say you have an object `x` and want to change the behaviour of just one of its methods. You can create a new class that provides a new implementation of the method you're interested in changing and delegates all other methods to the corresponding method of `x`.

Python programmers can easily implement delegation. For example, the following class implements a class that behaves like a file but converts all written data to uppercase:

```

class UpperOut:

    def __init__(self, outfile):
        self._outfile = outfile

    def write(self, s):
        self._outfile.write(s.upper())

    def __getattr__(self, name):
        return getattr(self._outfile, name)

```

Here the `UpperOut` class redefines the `write()` method to convert the argument string to uppercase before calling the underlying `self._outfile.write()` method. All other methods are delegated to the underlying `self._outfile` object. The delegation is accomplished via the `__getattr__` method; consult *the language reference* for more information about controlling attribute access.

Note that for more general cases delegation can get trickier. When attributes must be set as well as retrieved, the class must define a `__setattr__()` method too, and it must do so carefully. The basic implementation of `__setattr__()` is roughly equivalent to the following:

```

class X:
    ...
    def __setattr__(self, name, value):
        self.__dict__[name] = value
    ...

```

Most `__setattr__()` implementations must modify `self.__dict__` to store local state for `self` without causing an infinite recursion.

### 2.7.6 How do I call a method defined in a base class from a derived class that overrides it?

Use the built-in `super()` function:

```

class Derived(Base):
    def meth(self):
        super(Derived, self).meth()

```

For version prior to 3.0, you may be using classic classes: For a class definition such as `class Derived(Base):` ... you can call method `meth()` defined in `Base` (or one of `Base`'s base classes) as `Base.meth(self, arguments...)`. Here, `Base.meth` is an unbound method, so you need to provide the `self` argument.

## 2.7.7 How can I organize my code to make it easier to change the base class?

You could define an alias for the base class, assign the real base class to it before your class definition, and use the alias throughout your class. Then all you have to change is the value assigned to the alias. Incidentally, this trick is also handy if you want to decide dynamically (e.g. depending on availability of resources) which base class to use. Example:

```
BaseAlias = <real base class>
```

```
class Derived(BaseAlias):
    def meth(self):
        BaseAlias.meth(self)
    ...
```

## 2.7.8 How do I create static class data and static class methods?

Both static data and static methods (in the sense of C++ or Java) are supported in Python.

For static data, simply define a class attribute. To assign a new value to the attribute, you have to explicitly use the class name in the assignment:

```
class C:
    count = 0    # number of times C.__init__ called

    def __init__(self):
        C.count = C.count + 1

    def getcount(self):
        return C.count    # or return self.count
```

`c.count` also refers to `C.count` for any `c` such that `isinstance(c, C)` holds, unless overridden by `c` itself or by some class on the base-class search path from `c.__class__` back to `C`.

Caution: within a method of `C`, an assignment like `self.count = 42` creates a new and unrelated instance named "count" in `self`'s own dict. Rebinding of a class-static data name must always specify the class whether inside a method or not:

```
C.count = 314
```

Static methods are possible:

```
class C:
    @staticmethod
    def static(arg1, arg2, arg3):
        # No 'self' parameter!
    ...
```

However, a far more straightforward way to get the effect of a static method is via a simple module-level function:

```
def getcount():
    return C.count
```

If your code is structured so as to define one class (or tightly related class hierarchy) per module, this supplies the desired encapsulation.

### 2.7.9 How can I overload constructors (or methods) in Python?

This answer actually applies to all methods, but the question usually comes up first in the context of constructors.

In C++ you'd write

```
class C {
    C() { cout << "No arguments\n"; }
    C(int i) { cout << "Argument is " << i << "\n"; }
}
```

In Python you have to write a single constructor that catches all cases using default arguments. For example:

```
class C:
    def __init__(self, i=None):
        if i is None:
            print("No arguments")
        else:
            print("Argument is", i)
```

This is not entirely equivalent, but close enough in practice.

You could also try a variable-length argument list, e.g.

```
def __init__(self, *args):
    ...
```

The same approach works for all method definitions.

### 2.7.10 I try to use `__spam` and I get an error about `_SomeClassName__spam`.

Variable names with double leading underscores are “mangled” to provide a simple but effective way to define class private variables. Any identifier of the form `__spam` (at least two leading underscores, at most one trailing underscore) is textually replaced with `_classname__spam`, where `classname` is the current class name with any leading underscores stripped.

This doesn't guarantee privacy: an outside user can still deliberately access the “`_classname__spam`” attribute, and private values are visible in the object's `__dict__`. Many Python programmers never bother to use private variable names at all.

### 2.7.11 My class defines `__del__` but it is not called when I delete the object.

There are several possible reasons for this.

The `del` statement does not necessarily call `__del__()` – it simply decrements the object's reference count, and if this reaches zero `__del__()` is called.

If your data structures contain circular links (e.g. a tree where each child has a parent reference and each parent has a list of children) the reference counts will never go back to zero. Once in a while Python runs an algorithm to detect such cycles, but the garbage collector might run some time after the last reference to your data structure vanishes, so your `__del__()` method may be called at an inconvenient and random time. This is inconvenient if you're trying to reproduce a problem. Worse, the order in which object's `__del__()` methods are executed is arbitrary. You can run `gc.collect()` to force a collection, but there *are* pathological cases where objects will never be collected.

Despite the cycle collector, it's still a good idea to define an explicit `close()` method on objects to be called whenever you're done with them. The `close()` method can then remove attributes that refer to subobjects. Don't call `__del__()` directly – `__del__()` should call `close()` and `close()` should make sure that it can be called more than once for the same object.

Another way to avoid cyclical references is to use the `weakref` module, which allows you to point to objects without incrementing their reference count. Tree data structures, for instance, should use weak references for their parent and sibling references (if they need them!).

Finally, if your `__del__()` method raises an exception, a warning message is printed to `sys.stderr`.

### 2.7.12 How do I get a list of all instances of a given class?

Python does not keep track of all instances of a class (or of a built-in type). You can program the class's constructor to keep track of all instances by keeping a list of weak references to each instance.

## 2.8 Modules

### 2.8.1 How do I create a .pyc file?

When a module is imported for the first time (or when the source is more recent than the current compiled file) a `.pyc` file containing the compiled code should be created in the same directory as the `.py` file.

One reason that a `.pyc` file may not be created is permissions problems with the directory. This can happen, for example, if you develop as one user but run as another, such as if you are testing with a web server. Creation of a `.pyc` file is automatic if you're importing a module and Python has the ability (permissions, free space, etc...) to write the compiled module back to the directory.

Running Python on a top level script is not considered an import and no `.pyc` will be created. For example, if you have a top-level module `abc.py` that imports another module `xyz.py`, when you run `abc`, `xyz.pyc` will be created since `xyz` is imported, but no `abc.pyc` file will be created since `abc.py` isn't being imported.

If you need to create `abc.pyc` – that is, to create a `.pyc` file for a module that is not imported – you can, using the `py_compile` and `compileall` modules.

The `py_compile` module can manually compile any module. One way is to use the `compile()` function in that module interactively:

```
>>> import py_compile
>>> py_compile.compile('abc.py')
```

This will write the `.pyc` to the same location as `abc.py` (or you can override that with the optional parameter `cfile`).

You can also automatically compile all files in a directory or directories using the `compileall` module. You can do it from the shell prompt by running `compileall.py` and providing the path of a directory containing Python files to compile:

```
python -m compileall .
```

### 2.8.2 How do I find the current module name?

A module can find out its own module name by looking at the predefined global variable `__name__`. If this has the value `'__main__'`, the program is running as a script. Many modules that are usually used by importing them also provide a command-line interface or a self-test, and only execute this code after checking `__name__`:

```
def main():
    print('Running test...')
    ...

if __name__ == '__main__':
    main()
```

### 2.8.3 How can I have modules that mutually import each other?

Suppose you have the following modules:

`foo.py`:

```

from bar import bar_var
foo_var = 1

bar.py:
from foo import foo_var
bar_var = 2

```

The problem is that the interpreter will perform the following steps:

- main imports foo
- Empty globals for foo are created
- foo is compiled and starts executing
- foo imports bar
- Empty globals for bar are created
- bar is compiled and starts executing
- bar imports foo (which is a no-op since there already is a module named foo)
- bar.foo\_var = foo.foo\_var

The last step fails, because Python isn't done with interpreting `foo` yet and the global symbol dictionary for `foo` is still empty.

The same thing happens when you use `import foo`, and then try to access `foo.foo_var` in global code.

There are (at least) three possible workarounds for this problem.

Guido van Rossum recommends avoiding all uses of `from <module> import ...`, and placing all code inside functions. Initializations of global variables and class variables should use constants or built-in functions only. This means everything from an imported module is referenced as `<module>.<name>`.

Jim Roskind suggests performing steps in the following order in each module:

- exports (globals, functions, and classes that don't need imported base classes)
- import statements
- active code (including globals that are initialized from imported values).

van Rossum doesn't like this approach much because the imports appear in a strange place, but it does work.

Matthias Urlichs recommends restructuring your code so that the recursive import is not necessary in the first place.

These solutions are not mutually exclusive.

## 2.8.4 `__import__('x.y.z')` returns `<module 'x'>`; how do I get `z`?

Try:

```
__import__('x.y.z').y.z
```

For more realistic situations, you may have to do something like

```

m = __import__(s)
for i in s.split(".")[1:]:
    m = getattr(m, i)

```

See `importlib` for a convenience function called `import_module()`.

### 2.8.5 When I edit an imported module and reimport it, the changes don't show up. Why does this happen?

For reasons of efficiency as well as consistency, Python only reads the module file on the first time a module is imported. If it didn't, in a program consisting of many modules where each one imports the same basic module, the basic module would be parsed and re-parsed many times. To force rereading of a changed module, do this:

```
import imp
import modname
imp.reload(modname)
```

Warning: this technique is not 100% fool-proof. In particular, modules containing statements like

```
from modname import some_objects
```

will continue to work with the old version of the imported objects. If the module contains class definitions, existing class instances will *not* be updated to use the new class definition. This can result in the following paradoxical behaviour:

```
>>> import imp
>>> import cls
>>> c = cls.C()                # Create an instance of C
>>> imp.reload(cls)
<module 'cls' from 'cls.py'>
>>> isinstance(c, cls.C)      # isinstance is false?!?
False
```

The nature of the problem is made clear if you print out the “identity” of the class objects:

```
>>> hex(id(c.__class__))
'0x7352a0'
>>> hex(id(cls.C))
'0x4198d0'
```

## DESIGN AND HISTORY FAQ

### 3.1 Why does Python use indentation for grouping of statements?

Guido van Rossum believes that using indentation for grouping is extremely elegant and contributes a lot to the clarity of the average Python program. Most people learn to love this feature after a while.

Since there are no begin/end brackets there cannot be a disagreement between grouping perceived by the parser and the human reader. Occasionally C programmers will encounter a fragment of code like this:

```
if (x <= y)
    x++;
    y--;
z++;
```

Only the `x++` statement is executed if the condition is true, but the indentation leads you to believe otherwise. Even experienced C programmers will sometimes stare at it a long time wondering why `y` is being decremented even for `x > y`.

Because there are no begin/end brackets, Python is much less prone to coding-style conflicts. In C there are many different ways to place the braces. If you're used to reading and writing code that uses one style, you will feel at least slightly uneasy when reading (or being required to write) another style.

Many coding styles place begin/end brackets on a line by themselves. This makes programs considerably longer and wastes valuable screen space, making it harder to get a good overview of a program. Ideally, a function should fit on one screen (say, 20-30 lines). 20 lines of Python can do a lot more work than 20 lines of C. This is not solely due to the lack of begin/end brackets – the lack of declarations and the high-level data types are also responsible – but the indentation-based syntax certainly helps.

### 3.2 Why am I getting strange results with simple arithmetic operations?

See the next question.

### 3.3 Why are floating-point calculations so inaccurate?

Users are often surprised by results like this:

```
>>> 1.2 - 1.0
0.19999999999999996
```

and think it is a bug in Python. It's not. This has little to do with Python, and much more to do with how the underlying platform handles floating-point numbers.

The `float` type in CPython uses a C `double` for storage. A `float` object's value is stored in binary floating-point with a fixed precision (typically 53 bits) and Python uses C operations, which in turn rely on the hardware implementation in the processor, to perform floating-point operations. This means that as far as floating-point operations are concerned, Python behaves like many popular languages including C and Java.

Many numbers that can be written easily in decimal notation cannot be expressed exactly in binary floating-point. For example, after:

```
>>> x = 1.2
```

the value stored for `x` is a (very good) approximation to the decimal value `1.2`, but is not exactly equal to it. On a typical machine, the actual stored value is:

```
1.001100110011001100110011001100110011001100110011001100110011 (binary)
```

which is exactly:

```
1.1999999999999999555910790149937383830547332763671875 (decimal)
```

The typical precision of 53 bits provides Python floats with 15-16 decimal digits of accuracy.

For a fuller explanation, please see the *floating point arithmetic* chapter in the Python tutorial.

## 3.4 Why are Python strings immutable?

There are several advantages.

One is performance: knowing that a string is immutable means we can allocate space for it at creation time, and the storage requirements are fixed and unchanging. This is also one of the reasons for the distinction between tuples and lists.

Another advantage is that strings in Python are considered as “elemental” as numbers. No amount of activity will change the value `8` to anything else, and in Python, no amount of activity will change the string “eight” to anything else.

## 3.5 Why must ‘self’ be used explicitly in method definitions and calls?

The idea was borrowed from Modula-3. It turns out to be very useful, for a variety of reasons.

First, it's more obvious that you are using a method or instance attribute instead of a local variable. Reading `self.x` or `self.meth()` makes it absolutely clear that an instance variable or method is used even if you don't know the class definition by heart. In C++, you can sort of tell by the lack of a local variable declaration (assuming globals are rare or easily recognizable) – but in Python, there are no local variable declarations, so you'd have to look up the class definition to be sure. Some C++ and Java coding standards call for instance attributes to have an `m_` prefix, so this explicitness is still useful in those languages, too.

Second, it means that no special syntax is necessary if you want to explicitly reference or call the method from a particular class. In C++, if you want to use a method from a base class which is overridden in a derived class, you have to use the `::` operator – in Python you can write `baseclass.methodname(self, <argument list>)`. This is particularly useful for `__init__()` methods, and in general in cases where a derived class method wants to extend the base class method of the same name and thus has to call the base class method somehow.

Finally, for instance variables it solves a syntactic problem with assignment: since local variables in Python are (by definition!) those variables to which a value is assigned in a function body (and that aren't explicitly declared global), there has to be some way to tell the interpreter that an assignment was meant to assign to an instance variable instead of to a local variable, and it should preferably be syntactic (for efficiency reasons). C++ does this through declarations, but Python doesn't have declarations and it would be a pity having to introduce them just for this purpose. Using the explicit `self.var` solves this nicely. Similarly, for using instance variables, having to write `self.var` means that references to unqualified names inside a method don't have to search the instance's

directories. To put it another way, local variables and instance variables live in two different namespaces, and you need to tell Python which namespace to use.

## 3.6 Why can't I use an assignment in an expression?

Many people used to C or Perl complain that they want to use this C idiom:

```
while (line = readline(f)) {
    // do something with line
}
```

where in Python you're forced to write this:

```
while True:
    line = f.readline()
    if not line:
        break
    ... # do something with line
```

The reason for not allowing assignment in Python expressions is a common, hard-to-find bug in those other languages, caused by this construct:

```
if (x = 0) {
    // error handling
}
else {
    // code that only works for nonzero x
}
```

The error is a simple typo: `x = 0`, which assigns 0 to the variable `x`, was written while the comparison `x == 0` is certainly what was intended.

Many alternatives have been proposed. Most are hacks that save some typing but use arbitrary or cryptic syntax or keywords, and fail the simple criterion for language change proposals: it should intuitively suggest the proper meaning to a human reader who has not yet been introduced to the construct.

An interesting phenomenon is that most experienced Python programmers recognize the `while True` idiom and don't seem to be missing the assignment in expression construct much; it's only newcomers who express a strong desire to add this to the language.

There's an alternative way of spelling this that seems attractive but is generally less robust than the "while True" solution:

```
line = f.readline()
while line:
    ... # do something with line...
    line = f.readline()
```

The problem with this is that if you change your mind about exactly how you get the next line (e.g. you want to change it into `sys.stdin.readline()`) you have to remember to change two places in your program – the second occurrence is hidden at the bottom of the loop.

The best approach is to use iterators, making it possible to loop through objects using the `for` statement. For example, *file objects* support the iterator protocol, so you can write simply:

```
for line in f:
    ... # do something with line...
```

### 3.7 Why does Python use methods for some functionality (e.g. `list.index()`) but functions for other (e.g. `len(list)`)?

The major reason is history. Functions were used for those operations that were generic for a group of types and which were intended to work even for objects that didn't have methods at all (e.g. tuples). It is also convenient to have a function that can readily be applied to an amorphous collection of objects when you use the functional features of Python (`map()`, `apply()` et al).

In fact, implementing `len()`, `max()`, `min()` as a built-in function is actually less code than implementing them as methods for each type. One can quibble about individual cases but it's a part of Python, and it's too late to make such fundamental changes now. The functions have to remain to avoid massive code breakage.

---

**Note:** For string operations, Python has moved from external functions (the `string` module) to methods. However, `len()` is still a function.

---

### 3.8 Why is `join()` a string method instead of a list or tuple method?

Strings became much more like other standard types starting in Python 1.6, when methods were added which give the same functionality that has always been available using the functions of the `string` module. Most of these new methods have been widely accepted, but the one which appears to make some programmers feel uncomfortable is:

```
"", ".join(['1', '2', '4', '8', '16'])
```

which gives the result:

```
"1, 2, 4, 8, 16"
```

There are two common arguments against this usage.

The first runs along the lines of: "It looks really ugly using a method of a string literal (string constant)", to which the answer is that it might, but a string literal is just a fixed value. If the methods are to be allowed on names bound to strings there is no logical reason to make them unavailable on literals.

The second objection is typically cast as: "I am really telling a sequence to join its members together with a string constant". Sadly, you aren't. For some reason there seems to be much less difficulty with having `split()` as a string method, since in that case it is easy to see that

```
"1, 2, 4, 8, 16".split(", ")
```

is an instruction to a string literal to return the substrings delimited by the given separator (or, by default, arbitrary runs of white space).

`join()` is a string method because in using it you are telling the separator string to iterate over a sequence of strings and insert itself between adjacent elements. This method can be used with any argument which obeys the rules for sequence objects, including any new classes you might define yourself. Similar methods exist for bytes and bytearray objects.

### 3.9 How fast are exceptions?

A try/except block is extremely efficient if no exceptions are raised. Actually catching an exception is expensive. In versions of Python prior to 2.0 it was common to use this idiom:

```
try:
    value = mydict[key]
except KeyError:
    mydict[key] = getvalue(key)
    value = mydict[key]
```

This only made sense when you expected the dict to have the key almost all the time. If that wasn't the case, you coded it like this:

```
if key in mydict:
    value = mydict[key]
else:
    value = mydict[key] = getvalue(key)
```

For this specific case, you could also use `value = dict.setdefault(key, getvalue(key))`, but only if the `getvalue()` call is cheap enough because it is evaluated in all cases.

## 3.10 Why isn't there a switch or case statement in Python?

You can do this easily enough with a sequence of `if... elif... elif... else`. There have been some proposals for switch statement syntax, but there is no consensus (yet) on whether and how to do range tests. See [PEP 275](#) for complete details and the current status.

For cases where you need to choose from a very large number of possibilities, you can create a dictionary mapping case values to functions to call. For example:

```
def function_1(...):
    ...

functions = {'a': function_1,
            'b': function_2,
            'c': self.method_1, ...}

func = functions[value]
func()
```

For calling methods on objects, you can simplify yet further by using the `getattr()` built-in to retrieve methods with a particular name:

```
def visit_a(self, ...):
    ...

...

def dispatch(self, value):
    method_name = 'visit_' + str(value)
    method = getattr(self, method_name)
    method()
```

It's suggested that you use a prefix for the method names, such as `visit_` in this example. Without such a prefix, if values are coming from an untrusted source, an attacker would be able to call any method on your object.

## 3.11 Can't you emulate threads in the interpreter instead of relying on an OS-specific thread implementation?

Answer 1: Unfortunately, the interpreter pushes at least one C stack frame for each Python stack frame. Also, extensions can call back into Python at almost random moments. Therefore, a complete threads implementation requires thread support for C.

Answer 2: Fortunately, there is [Stackless Python](#), which has a completely redesigned interpreter loop that avoids the C stack. It's still experimental but looks very promising. Although it is binary compatible with standard Python, it's still unclear whether Stackless will make it into the core – maybe it's just too revolutionary.

## 3.12 Why can't lambda forms contain statements?

Python lambda forms cannot contain statements because Python's syntactic framework can't handle statements nested inside expressions. However, in Python, this is not a serious problem. Unlike lambda forms in other languages, where they add functionality, Python lambdas are only a shorthand notation if you're too lazy to define a function.

Functions are already first class objects in Python, and can be declared in a local scope. Therefore the only advantage of using a lambda form instead of a locally-defined function is that you don't need to invent a name for the function – but that's just a local variable to which the function object (which is exactly the same type of object that a lambda form yields) is assigned!

## 3.13 Can Python be compiled to machine code, C or some other language?

Practical answer:

[Cython](#) and [Pyrex](#) compile a modified version of Python with optional annotations into C extensions. [Weave](#) makes it easy to intermingle Python and C code in various ways to increase performance. [Nuitka](#) is an up-and-coming compiler of Python into C++ code, aiming to support the full Python language.

Theoretical answer:

Not trivially. Python's high level data types, dynamic typing of objects and run-time invocation of the interpreter (using `eval()` or `exec()`) together mean that a naïvely “compiled” Python program would probably consist mostly of calls into the Python run-time system, even for seemingly simple operations like `x+1`.

Several projects described in the Python newsgroup or at past [Python conferences](#) have shown that this approach is feasible, although the speedups reached so far are only modest (e.g. 2x). Jython uses the same strategy for compiling to Java bytecode. (Jim Hugunin has demonstrated that in combination with whole-program analysis, speedups of 1000x are feasible for small demo programs. See the proceedings from the [1997 Python conference](#) for more information.)

## 3.14 How does Python manage memory?

The details of Python memory management depend on the implementation. The standard implementation of Python, [CPython](#), uses reference counting to detect inaccessible objects, and another mechanism to collect reference cycles, periodically executing a cycle detection algorithm which looks for inaccessible cycles and deletes the objects involved. The `gc` module provides functions to perform a garbage collection, obtain debugging statistics, and tune the collector's parameters.

Other implementations (such as [Jython](#) or [PyPy](#)), however, can rely on a different mechanism such as a full-blown garbage collector. This difference can cause some subtle porting problems if your Python code depends on the behavior of the reference counting implementation.

In some Python implementations, the following code (which is fine in CPython) will probably run out of file descriptors:

```
for file in very_long_list_of_files:
    f = open(file)
    c = f.read(1)
```

Indeed, using CPython's reference counting and destructor scheme, each new assignment to `f` closes the previous file. With a traditional GC, however, those file objects will only get collected (and closed) at varying and possibly long intervals.

If you want to write code that will work with any Python implementation, you should explicitly close the file or use the `with` statement; this will work regardless of memory management scheme:

```
for file in very_long_list_of_files:
    with open(file) as f:
        c = f.read(1)
```

### 3.15 Why doesn't CPython use a more traditional garbage collection scheme?

For one thing, this is not a C standard feature and hence it's not portable. (Yes, we know about the Boehm GC library. It has bits of assembler code for *most* common platforms, not for all of them, and although it is mostly transparent, it isn't completely transparent; patches are required to get Python to work with it.)

Traditional GC also becomes a problem when Python is embedded into other applications. While in a standalone Python it's fine to replace the standard `malloc()` and `free()` with versions provided by the GC library, an application embedding Python may want to have its *own* substitute for `malloc()` and `free()`, and may not want Python's. Right now, CPython works with anything that implements `malloc()` and `free()` properly.

### 3.16 Why isn't all memory freed when CPython exits?

Objects referenced from the global namespaces of Python modules are not always deallocated when Python exits. This may happen if there are circular references. There are also certain bits of memory that are allocated by the C library that are impossible to free (e.g. a tool like Purify will complain about these). Python is, however, aggressive about cleaning up memory on exit and does try to destroy every single object.

If you want to force Python to delete certain things on deallocation use the `atexit` module to run a function that will force those deletions.

### 3.17 Why are there separate tuple and list data types?

Lists and tuples, while similar in many respects, are generally used in fundamentally different ways. Tuples can be thought of as being similar to Pascal records or C structs; they're small collections of related data which may be of different types which are operated on as a group. For example, a Cartesian coordinate is appropriately represented as a tuple of two or three numbers.

Lists, on the other hand, are more like arrays in other languages. They tend to hold a varying number of objects all of which have the same type and which are operated on one-by-one. For example, `os.listdir('.')` returns a list of strings representing the files in the current directory. Functions which operate on this output would generally not break if you added another file or two to the directory.

Tuples are immutable, meaning that once a tuple has been created, you can't replace any of its elements with a new value. Lists are mutable, meaning that you can always change a list's elements. Only immutable elements can be used as dictionary keys, and hence only tuples and not lists can be used as keys.

### 3.18 How are lists implemented?

Python's lists are really variable-length arrays, not Lisp-style linked lists. The implementation uses a contiguous array of references to other objects, and keeps a pointer to this array and the array's length in a list head structure.

This makes indexing a list `a[i]` an operation whose cost is independent of the size of the list or the value of the index.

When items are appended or inserted, the array of references is resized. Some cleverness is applied to improve the performance of appending items repeatedly; when the array must be grown, some extra space is allocated so the next few times don't require an actual resize.

## 3.19 How are dictionaries implemented?

Python's dictionaries are implemented as resizable hash tables. Compared to B-trees, this gives better performance for lookup (the most common operation by far) under most circumstances, and the implementation is simpler.

Dictionaries work by computing a hash code for each key stored in the dictionary using the `hash()` built-in function. The hash code varies widely depending on the key and a per-process seed; for example, "Python" could hash to -539294296 while "python", a string that differs by a single bit, could hash to 1142331976. The hash code is then used to calculate a location in an internal array where the value will be stored. Assuming that you're storing keys that all have different hash values, this means that dictionaries take constant time –  $O(1)$ , in computer science notation – to retrieve a key. It also means that no sorted order of the keys is maintained, and traversing the array as the `.keys()` and `.items()` do will output the dictionary's content in some arbitrary jumbled order that can change with every invocation of a program.

## 3.20 Why must dictionary keys be immutable?

The hash table implementation of dictionaries uses a hash value calculated from the key value to find the key. If the key were a mutable object, its value could change, and thus its hash could also change. But since whoever changes the key object can't tell that it was being used as a dictionary key, it can't move the entry around in the dictionary. Then, when you try to look up the same object in the dictionary it won't be found because its hash value is different. If you tried to look up the old value it wouldn't be found either, because the value of the object found in that hash bin would be different.

If you want a dictionary indexed with a list, simply convert the list to a tuple first; the function `tuple(L)` creates a tuple with the same entries as the list `L`. Tuples are immutable and can therefore be used as dictionary keys.

Some unacceptable solutions that have been proposed:

- Hash lists by their address (object ID). This doesn't work because if you construct a new list with the same value it won't be found; e.g.:

```
mydict = {[1, 2]: '12'}
print(mydict[[1, 2]])
```

would raise a `KeyError` exception because the id of the `[1, 2]` used in the second line differs from that in the first line. In other words, dictionary keys should be compared using `==`, not using `is`.

- Make a copy when using a list as a key. This doesn't work because the list, being a mutable object, could contain a reference to itself, and then the copying code would run into an infinite loop.
- Allow lists as keys but tell the user not to modify them. This would allow a class of hard-to-track bugs in programs when you forgot or modified a list by accident. It also invalidates an important invariant of dictionaries: every value in `d.keys()` is usable as a key of the dictionary.
- Mark lists as read-only once they are used as a dictionary key. The problem is that it's not just the top-level object that could change its value; you could use a tuple containing a list as a key. Entering anything as a key into a dictionary would require marking all objects reachable from there as read-only – and again, self-referential objects could cause an infinite loop.

There is a trick to get around this if you need to, but use it at your own risk: You can wrap a mutable structure inside a class instance which has both a `__eq__()` and a `__hash__()` method. You must then make sure that the hash value for all such wrapper objects that reside in a dictionary (or other hash based structure), remain fixed while the object is in the dictionary (or other structure).

```
class ListWrapper:
    def __init__(self, the_list):
```

```

self.the_list = the_list
def __eq__(self, other):
    return self.the_list == other.the_list
def __hash__(self):
    l = self.the_list
    result = 98767 - len(l)*555
    for i, el in enumerate(l):
        try:
            result = result + (hash(el) % 9999999) * 1001 + i
        except Exception:
            result = (result % 7777777) + i * 333
    return result

```

Note that the hash computation is complicated by the possibility that some members of the list may be unhashable and also by the possibility of arithmetic overflow.

Furthermore it must always be the case that if `o1 == o2` (ie `o1.__eq__(o2)` is True) then `hash(o1) == hash(o2)` (ie, `o1.__hash__() == o2.__hash__()`), regardless of whether the object is in a dictionary or not. If you fail to meet these restrictions dictionaries and other hash based structures will misbehave.

In the case of `ListWrapper`, whenever the wrapper object is in a dictionary the wrapped list must not change to avoid anomalies. Don't do this unless you are prepared to think hard about the requirements and the consequences of not meeting them correctly. Consider yourself warned.

## 3.21 Why doesn't `list.sort()` return the sorted list?

In situations where performance matters, making a copy of the list just to sort it would be wasteful. Therefore, `list.sort()` sorts the list in place. In order to remind you of that fact, it does not return the sorted list. This way, you won't be fooled into accidentally overwriting a list when you need a sorted copy but also need to keep the unsorted version around.

If you want to return a new list, use the built-in `sorted()` function instead. This function creates a new list from a provided iterable, sorts it and returns it. For example, here's how to iterate over the keys of a dictionary in sorted order:

```

for key in sorted(mydict):
    ... # do whatever with mydict[key]...

```

## 3.22 How do you specify and enforce an interface spec in Python?

An interface specification for a module as provided by languages such as C++ and Java describes the prototypes for the methods and functions of the module. Many feel that compile-time enforcement of interface specifications helps in the construction of large programs.

Python 2.6 adds an `abc` module that lets you define Abstract Base Classes (ABCs). You can then use `isinstance()` and `issubclass()` to check whether an instance or a class implements a particular ABC. The `collections.abc` module defines a set of useful ABCs such as `Iterable`, `Container`, and `MutableMapping`.

For Python, many of the advantages of interface specifications can be obtained by an appropriate test discipline for components. There is also a tool, `PyChecker`, which can be used to find problems due to subclassing.

A good test suite for a module can both provide a regression test and serve as a module interface specification and a set of examples. Many Python modules can be run as a script to provide a simple "self test." Even modules which use complex external interfaces can often be tested in isolation using trivial "stub" emulations of the external interface. The `doctest` and `unittest` modules or third-party test frameworks can be used to construct exhaustive test suites that exercise every line of code in a module.

An appropriate testing discipline can help build large complex applications in Python as well as having interface specifications would. In fact, it can be better because an interface specification cannot test certain properties of a program. For example, the `append()` method is expected to add new elements to the end of some internal list; an interface specification cannot test that your `append()` implementation will actually do this correctly, but it's trivial to check this property in a test suite.

Writing test suites is very helpful, and you might want to design your code with an eye to making it easily tested. One increasingly popular technique, test-directed development, calls for writing parts of the test suite first, before you write any of the actual code. Of course Python allows you to be sloppy and not write test cases at all.

## 3.23 Why are default values shared between objects?

This type of bug commonly bites neophyte programmers. Consider this function:

```
def foo(mydict={}): # Danger: shared reference to one dict for all calls
    ... compute something ...
    mydict[key] = value
    return mydict
```

The first time you call this function, `mydict` contains a single item. The second time, `mydict` contains two items because when `foo()` begins executing, `mydict` starts out with an item already in it.

It is often expected that a function call creates new objects for default values. This is not what happens. Default values are created exactly once, when the function is defined. If that object is changed, like the dictionary in this example, subsequent calls to the function will refer to this changed object.

By definition, immutable objects such as numbers, strings, tuples, and `None`, are safe from change. Changes to mutable objects such as dictionaries, lists, and class instances can lead to confusion.

Because of this feature, it is good programming practice to not use mutable objects as default values. Instead, use `None` as the default value and inside the function, check if the parameter is `None` and create a new list/dictionary/whatever if it is. For example, don't write:

```
def foo(mydict={}):
    ...
```

but:

```
def foo(mydict=None):
    if mydict is None:
        mydict = {} # create a new dict for local namespace
```

This feature can be useful. When you have a function that's time-consuming to compute, a common technique is to cache the parameters and the resulting value of each call to the function, and return the cached value if the same value is requested again. This is called "memoizing", and can be implemented like this:

```
# Callers will never provide a third parameter for this function.
def expensive (arg1, arg2, _cache={}):
    if (arg1, arg2) in _cache:
        return _cache[(arg1, arg2)]

    # Calculate the value
    result = ... expensive computation ...
    _cache[(arg1, arg2)] = result # Store result in the cache
    return result
```

You could use a global variable containing a dictionary instead of the default value; it's a matter of taste.

### 3.24 Why is there no goto?

You can use exceptions to provide a “structured goto” that even works across function calls. Many feel that exceptions can conveniently emulate all reasonable uses of the “go” or “goto” constructs of C, Fortran, and other languages. For example:

```
class label: pass # declare a label

try:
    ...
    if (condition): raise label() # goto label
    ...
except label: # where to goto
    pass
...
```

This doesn’t allow you to jump into the middle of a loop, but that’s usually considered an abuse of goto anyway. Use sparingly.

### 3.25 Why can’t raw strings (r-strings) end with a backslash?

More precisely, they can’t end with an odd number of backslashes: the unpaired backslash at the end escapes the closing quote character, leaving an unterminated string.

Raw strings were designed to ease creating input for processors (chiefly regular expression engines) that want to do their own backslash escape processing. Such processors consider an unmatched trailing backslash to be an error anyway, so raw strings disallow that. In return, they allow you to pass on the string quote character by escaping it with a backslash. These rules work well when r-strings are used for their intended purpose.

If you’re trying to build Windows pathnames, note that all Windows system calls accept forward slashes too:

```
f = open("/mydir/file.txt") # works fine!
```

If you’re trying to build a pathname for a DOS command, try e.g. one of

```
dir = r"\this\is\my\dos\dir" "\\\"
dir = r"\this\is\my\dos\dir\" "[:-1]
dir = "\\this\\is\\my\\dos\\dir\\\"
```

### 3.26 Why doesn’t Python have a “with” statement for attribute assignments?

Python has a ‘with’ statement that wraps the execution of a block, calling code on the entrance and exit from the block. Some language have a construct that looks like this:

```
with obj:
    a = 1 # equivalent to obj.a = 1
    total = total + 1 # obj.total = obj.total + 1
```

In Python, such a construct would be ambiguous.

Other languages, such as Object Pascal, Delphi, and C++, use static types, so it’s possible to know, in an unambiguous way, what member is being assigned to. This is the main point of static typing – the compiler *always* knows the scope of every variable at compile time.

Python uses dynamic types. It is impossible to know in advance which attribute will be referenced at runtime. Member attributes may be added or removed from objects on the fly. This makes it impossible to know, from a simple reading, what attribute is being referenced: a local one, a global one, or a member attribute?

For instance, take the following incomplete snippet:

```
def foo(a):  
    with a:  
        print(x)
```

The snippet assumes that “a” must have a member attribute called “x”. However, there is nothing in Python that tells the interpreter this. What should happen if “a” is, let us say, an integer? If there is a global variable named “x”, will it be used inside the with block? As you see, the dynamic nature of Python makes such choices much harder.

The primary benefit of “with” and similar language features (reduction of code volume) can, however, easily be achieved in Python by assignment. Instead of:

```
function(args).mydict[index][index].a = 21  
function(args).mydict[index][index].b = 42  
function(args).mydict[index][index].c = 63
```

write this:

```
ref = function(args).mydict[index][index]  
ref.a = 21  
ref.b = 42  
ref.c = 63
```

This also has the side-effect of increasing execution speed because name bindings are resolved at run-time in Python, and the second version only needs to perform the resolution once.

## 3.27 Why are colons required for the if/while/def/class statements?

The colon is required primarily to enhance readability (one of the results of the experimental ABC language). Consider this:

```
if a == b  
    print(a)
```

versus

```
if a == b:  
    print(a)
```

Notice how the second one is slightly easier to read. Notice further how a colon sets off the example in this FAQ answer; it’s a standard usage in English.

Another minor reason is that the colon makes it easier for editors with syntax highlighting; they can look for colons to decide when indentation needs to be increased instead of having to do a more elaborate parsing of the program text.

## 3.28 Why does Python allow commas at the end of lists and tuples?

Python lets you add a trailing comma at the end of lists, tuples, and dictionaries:

```
[1, 2, 3,]  
( 'a', 'b', 'c', )  
d = {  
    "A": [1, 5],  
    "B": [6, 7], # last trailing comma is optional but good style  
}
```

There are several reasons to allow this.

When you have a literal value for a list, tuple, or dictionary spread across multiple lines, it's easier to add more elements because you don't have to remember to add a comma to the previous line. The lines can also be sorted in your editor without creating a syntax error.

Accidentally omitting the comma can lead to errors that are hard to diagnose. For example:

```
x = [  
    "fee",  
    "fie"  
    "foo",  
    "fum"  
]
```

This list looks like it has four elements, but it actually contains three: “fee”, “fiefoo” and “fum”. Always adding the comma avoids this source of error.

Allowing the trailing comma may also make programmatic code generation easier.



# LIBRARY AND EXTENSION FAQ

## Contents

- Library and Extension FAQ
  - General Library Questions
    - \* How do I find a module or application to perform task X?
    - \* Where is the math.py (socket.py, regex.py, etc.) source file?
    - \* How do I make a Python script executable on Unix?
    - \* Is there a curses/termcap package for Python?
    - \* Is there an equivalent to C's onexit() in Python?
    - \* Why don't my signal handlers work?
  - Common tasks
    - \* How do I test a Python program or component?
    - \* How do I create documentation from doc strings?
    - \* How do I get a single keypress at a time?
  - Threads
    - \* How do I program using threads?
    - \* None of my threads seem to run: why?
    - \* How do I parcel out work among a bunch of worker threads?
    - \* What kinds of global value mutation are thread-safe?
    - \* Can't we get rid of the Global Interpreter Lock?
  - Input and Output
    - \* How do I delete a file? (And other file questions...)
    - \* How do I copy a file?
    - \* How do I read (or write) binary data?
    - \* I can't seem to use os.read() on a pipe created with os.popen(); why?
    - \* How do I access the serial (RS232) port?
    - \* Why doesn't closing sys.stdout (stdin, stderr) really close it?
  - Network/Internet Programming
    - \* What WWW tools are there for Python?
    - \* How can I mimic CGI form submission (METHOD=POST)?
    - \* What module should I use to help with generating HTML?
    - \* How do I send mail from a Python script?
    - \* How do I avoid blocking in the connect() method of a socket?
  - Databases
    - \* Are there any interfaces to database packages in Python?
    - \* How do you implement persistent objects in Python?
  - Mathematics and Numerics
    - \* How do I generate random numbers in Python?

## 4.1 General Library Questions

### 4.1.1 How do I find a module or application to perform task X?

Check *the Library Reference* to see if there's a relevant standard library module. (Eventually you'll learn what's in the standard library and will be able to skip this step.)

For third-party packages, search the [Python Package Index](#) or try [Google](#) or another Web search engine. Searching for "Python" plus a keyword or two for your topic of interest will usually find something helpful.

### 4.1.2 Where is the `math.py` (`socket.py`, `regex.py`, etc.) source file?

If you can't find a source file for a module it may be a built-in or dynamically loaded module implemented in C, C++ or other compiled language. In this case you may not have the source file or it may be something like `mathmodule.c`, somewhere in a C source directory (not on the Python Path).

There are (at least) three kinds of modules in Python:

1. modules written in Python (`.py`);
2. modules written in C and dynamically loaded (`.dll`, `.pyd`, `.so`, `.sl`, etc);
3. modules written in C and linked with the interpreter; to get a list of these, type:

```
import sys
print(sys.builtin_module_names)
```

### 4.1.3 How do I make a Python script executable on Unix?

You need to do two things: the script file's mode must be executable and the first line must begin with `#!` followed by the path of the Python interpreter.

The first is done by executing `chmod +x scriptfile` or perhaps `chmod 755 scriptfile`.

The second can be done in a number of ways. The most straightforward way is to write

```
#!/usr/local/bin/python
```

as the very first line of your file, using the pathname for where the Python interpreter is installed on your platform.

If you would like the script to be independent of where the Python interpreter lives, you can use the `env` program. Almost all Unix variants support the following, assuming the Python interpreter is in a directory on the user's

`PATH`:

```
#!/usr/bin/env python
```

*Don't* do this for CGI scripts. The `PATH` variable for CGI scripts is often very minimal, so you need to use the actual absolute pathname of the interpreter.

Occasionally, a user's environment is so full that the `/usr/bin/env` program fails; or there's no `env` program at all. In that case, you can try the following hack (due to Alex Rezinsky):

```
#!/bin/sh
"""
exec python $0 ${1+"$@"}
"""
```

The minor disadvantage is that this defines the script's `__doc__` string. However, you can fix that by adding

```
__doc__ = """...Whatever..."""
```

#### 4.1.4 Is there a `curses/termcap` package for Python?

For Unix variants: The standard Python source distribution comes with a `curses` module in the [Modules](#) subdirectory, though it's not compiled by default. (Note that this is not available in the Windows distribution – there is no `curses` module for Windows.)

The `curses` module supports basic `curses` features as well as many additional functions from `ncurses` and `SVSVCurses` such as colour, alternative character set support, pads, and mouse support. This means the module isn't compatible with operating systems that only have BSD `curses`, but there don't seem to be any currently maintained OSes that fall into this category.

For Windows: use [the `consolelib` module](#).

#### 4.1.5 Is there an equivalent to C's `onexit()` in Python?

The `atexit` module provides a register function that is similar to C's `onexit()`.

#### 4.1.6 Why don't my signal handlers work?

The most common problem is that the signal handler is declared with the wrong argument list. It is called as

```
handler(signum, frame)
```

so it should be declared with two arguments:

```
def handler(signum, frame):  
    ...
```

### 4.2 Common tasks

#### 4.2.1 How do I test a Python program or component?

Python comes with two testing frameworks. The `doctest` module finds examples in the docstrings for a module and runs them, comparing the output with the expected output given in the docstring.

The `unittest` module is a fancier testing framework modelled on Java and Smalltalk testing frameworks.

To make testing easier, you should use good modular design in your program. Your program should have almost all functionality encapsulated in either functions or class methods – and this sometimes has the surprising and delightful effect of making the program run faster (because local variable accesses are faster than global accesses). Furthermore the program should avoid depending on mutating global variables, since this makes testing much more difficult to do.

The “global main logic” of your program may be as simple as

```
if __name__ == "__main__":  
    main_logic()
```

at the bottom of the main module of your program.

Once your program is organized as a tractable collection of functions and class behaviours you should write test functions that exercise the behaviours. A test suite that automates a sequence of tests can be associated with each module. This sounds like a lot of work, but since Python is so terse and flexible it's surprisingly easy. You can make coding much more pleasant and fun by writing your test functions in parallel with the “production code”, since this makes it easy to find bugs and even design flaws earlier.

“Support modules” that are not intended to be the main module of a program may include a self-test of the module.

```
if __name__ == "__main__":  
    self_test()
```

Even programs that interact with complex external interfaces may be tested when the external interfaces are unavailable by using “fake” interfaces implemented in Python.

## 4.2.2 How do I create documentation from doc strings?

The `pydoc` module can create HTML from the doc strings in your Python source code. An alternative for creating API documentation purely from docstrings is `epydoc`. `Sphinx` can also include docstring content.

## 4.2.3 How do I get a single keypress at a time?

For Unix variants there are several solutions. It’s straightforward to do this using `curses`, but `curses` is a fairly large module to learn.

# 4.3 Threads

## 4.3.1 How do I program using threads?

Be sure to use the `threading` module and not the `_thread` module. The `threading` module builds convenient abstractions on top of the low-level primitives provided by the `_thread` module.

Aahz has a set of slides from his threading tutorial that are helpful; see <http://www.pythoncraft.com/OSCON2001/>.

## 4.3.2 None of my threads seem to run: why?

As soon as the main thread exits, all threads are killed. Your main thread is running too quickly, giving the threads no time to do any work.

A simple fix is to add a sleep to the end of the program that’s long enough for all the threads to finish:

```
import threading, time

def thread_task(name, n):
    for i in range(n): print(name, i)

for i in range(10):
    T = threading.Thread(target=thread_task, args=(str(i), i))
    T.start()

time.sleep(10)  # <-----!


```

But now (on many platforms) the threads don’t run in parallel, but appear to run sequentially, one at a time! The reason is that the OS thread scheduler doesn’t start a new thread until the previous thread is blocked.

A simple fix is to add a tiny sleep to the start of the run function:

```
def thread_task(name, n):
    time.sleep(0.001)  # <-----!
    for i in range(n): print(name, i)

for i in range(10):
    T = threading.Thread(target=thread_task, args=(str(i), i))
    T.start()

time.sleep(10)


```

Instead of trying to guess a good delay value for `time.sleep()`, it's better to use some kind of semaphore mechanism. One idea is to use the `queue` module to create a queue object, let each thread append a token to the queue when it finishes, and let the main thread read as many tokens from the queue as there are threads.

### 4.3.3 How do I parcel out work among a bunch of worker threads?

The easiest way is to use the new `concurrent.futures` module, especially the `ThreadPoolExecutor` class.

Or, if you want fine control over the dispatching algorithm, you can write your own logic manually. Use the `queue` module to create a queue containing a list of jobs. The `Queue` class maintains a list of objects and has a `.put(obj)` method that adds items to the queue and a `.get()` method to return them. The class will take care of the locking necessary to ensure that each job is handed out exactly once.

Here's a trivial example:

```
import threading, queue, time

# The worker thread gets jobs off the queue.  When the queue is empty, it
# assumes there will be no more work and exits.
# (Realistically workers will run until terminated.)
def worker():
    print('Running worker')
    time.sleep(0.1)
    while True:
        try:
            arg = q.get(block=False)
        except queue.Empty:
            print('Worker', threading.currentThread(), end=' ')
            print('queue empty')
            break
        else:
            print('Worker', threading.currentThread(), end=' ')
            print('running with argument', arg)
            time.sleep(0.5)

# Create queue
q = queue.Queue()

# Start a pool of 5 workers
for i in range(5):
    t = threading.Thread(target=worker, name='worker %i' % (i+1))
    t.start()

# Begin adding work to the queue
for i in range(50):
    q.put(i)

# Give threads time to run
print('Main thread sleeping')
time.sleep(5)
```

When run, this will produce the following output:

```
Running worker
Running worker
Running worker
Running worker
Running worker
Main thread sleeping
```

```
Worker <Thread(worker 1, started 130283832797456)> running with argument 0
Worker <Thread(worker 2, started 130283824404752)> running with argument 1
Worker <Thread(worker 3, started 130283816012048)> running with argument 2
Worker <Thread(worker 4, started 130283807619344)> running with argument 3
Worker <Thread(worker 5, started 130283799226640)> running with argument 4
Worker <Thread(worker 1, started 130283832797456)> running with argument 5
...
```

Consult the module’s documentation for more details; the `Queue` class provides a featureful interface.

#### 4.3.4 What kinds of global value mutation are thread-safe?

A *global interpreter lock* (GIL) is used internally to ensure that only one thread runs in the Python VM at a time. In general, Python offers to switch among threads only between bytecode instructions; how frequently it switches can be set via `sys.setswitchinterval()`. Each bytecode instruction and therefore all the C implementation code reached from each instruction is therefore atomic from the point of view of a Python program.

In theory, this means an exact accounting requires an exact understanding of the PVM bytecode implementation. In practice, it means that operations on shared variables of built-in data types (ints, lists, dicts, etc) that “look atomic” really are.

For example, the following operations are all atomic (L, L1, L2 are lists, D, D1, D2 are dicts, x, y are objects, i, j are ints):

```
L.append(x)
L1.extend(L2)
x = L[i]
x = L.pop()
L1[i:j] = L2
L.sort()
x = y
x.field = y
D[x] = y
D1.update(D2)
D.keys()
```

These aren’t:

```
i = i+1
L.append(L[-1])
L[i] = L[j]
D[x] = D[x] + 1
```

Operations that replace other objects may invoke those other objects’ `__del__()` method when their reference count reaches zero, and that can affect things. This is especially true for the mass updates to dictionaries and lists. When in doubt, use a mutex!

#### 4.3.5 Can’t we get rid of the Global Interpreter Lock?

The *global interpreter lock* (GIL) is often seen as a hindrance to Python’s deployment on high-end multiprocessor server machines, because a multi-threaded Python program effectively only uses one CPU, due to the insistence that (almost) all Python code can only run while the GIL is held.

Back in the days of Python 1.5, Greg Stein actually implemented a comprehensive patch set (the “free threading” patches) that removed the GIL and replaced it with fine-grained locking. Adam Olsen recently did a similar experiment in his [python-safethread](#) project. Unfortunately, both experiments exhibited a sharp drop in single-thread performance (at least 30% slower), due to the amount of fine-grained locking necessary to compensate for the removal of the GIL.

This doesn’t mean that you can’t make good use of Python on multi-CPU machines! You just have to be creative with dividing the work up between multiple *processes* rather than multiple *threads*. The

`ProcessPoolExecutor` class in the new `concurrent.futures` module provides an easy way of doing so; the `multiprocessing` module provides a lower-level API in case you want more control over dispatching of tasks.

Judicious use of C extensions will also help; if you use a C extension to perform a time-consuming task, the extension can release the GIL while the thread of execution is in the C code and allow other threads to get some work done. Some standard library modules such as `zlib` and `hashlib` already do this.

It has been suggested that the GIL should be a per-interpreter-state lock rather than truly global; interpreters then wouldn't be able to share objects. Unfortunately, this isn't likely to happen either. It would be a tremendous amount of work, because many object implementations currently have global state. For example, small integers and short strings are cached; these caches would have to be moved to the interpreter state. Other object types have their own free list; these free lists would have to be moved to the interpreter state. And so on.

And I doubt that it can even be done in finite time, because the same problem exists for 3rd party extensions. It is likely that 3rd party extensions are being written at a faster rate than you can convert them to store all their global state in the interpreter state.

And finally, once you have multiple interpreters not sharing any state, what have you gained over running each interpreter in a separate process?

## 4.4 Input and Output

### 4.4.1 How do I delete a file? (And other file questions...)

Use `os.remove(filename)` or `os.unlink(filename)`; for documentation, see the `os` module. The two functions are identical; `unlink()` is simply the name of the Unix system call for this function.

To remove a directory, use `os.rmdir()`; use `os.mkdir()` to create one. `os.makedirs(path)` will create any intermediate directories in `path` that don't exist. `os.removedirs(path)` will remove intermediate directories as long as they're empty; if you want to delete an entire directory tree and its contents, use `shutil.rmtree()`.

To rename a file, use `os.rename(old_path, new_path)`.

To truncate a file, open it using `f = open(filename, "rb+")`, and use `f.truncate(offset)`; offset defaults to the current seek position. There's also `os.ftruncate(fd, offset)` for files opened with `os.open()`, where `fd` is the file descriptor (a small integer).

The `shutil` module also contains a number of functions to work on files including `copyfile()`, `copytree()`, and `rmtree()`.

### 4.4.2 How do I copy a file?

The `shutil` module contains a `copyfile()` function. Note that on MacOS 9 it doesn't copy the resource fork and Finder info.

### 4.4.3 How do I read (or write) binary data?

To read or write complex binary data formats, it's best to use the `struct` module. It allows you to take a string containing binary data (usually numbers) and convert it to Python objects; and vice versa.

For example, the following code reads two 2-byte integers and one 4-byte integer in big-endian format from a file:

```
import struct

with open(filename, "rb") as f:
    s = f.read(8)
    x, y, z = struct.unpack(">hhl", s)
```

The ‘>’ in the format string forces big-endian data; the letter ‘h’ reads one “short integer” (2 bytes), and ‘l’ reads one “long integer” (4 bytes) from the string.

For data that is more regular (e.g. a homogeneous list of ints or floats), you can also use the `array` module.

---

**Note:** To read and write binary data, it is mandatory to open the file in binary mode (here, passing “rb” to `open()`). If you use “r” instead (the default), the file will be open in text mode and `f.read()` will return `str` objects rather than `bytes` objects.

---

### 4.4.4 I can’t seem to use `os.read()` on a pipe created with `os.popen()`; why?

`os.read()` is a low-level function which takes a file descriptor, a small integer representing the opened file. `os.popen()` creates a high-level file object, the same type returned by the built-in `open()` function. Thus, to read *n* bytes from a pipe *p* created with `os.popen()`, you need to use `p.read(n)`.

### 4.4.5 How do I access the serial (RS232) port?

For Win32, POSIX (Linux, BSD, etc.), Jython:

<http://pyserial.sourceforge.net>

For Unix, see a Usenet post by Mitch Chapman:

<http://groups.google.com/groups?selm=34A04430.CF9@ohioee.com>

### 4.4.6 Why doesn’t closing `sys.stdout` (`stdin`, `stderr`) really close it?

Python *file objects* are a high-level layer of abstraction on low-level C file descriptors.

For most file objects you create in Python via the built-in `open()` function, `f.close()` marks the Python file object as being closed from Python’s point of view, and also arranges to close the underlying C file descriptor. This also happens automatically in `f`’s destructor, when `f` becomes garbage.

But `stdin`, `stdout` and `stderr` are treated specially by Python, because of the special status also given to them by C. Running `sys.stdout.close()` marks the Python-level file object as being closed, but does *not* close the associated C file descriptor.

To close the underlying C file descriptor for one of these three, you should first be sure that’s what you really want to do (e.g., you may confuse extension modules trying to do I/O). If it is, use `os.close()`:

```
os.close(stdin.fileno())
os.close(stdout.fileno())
os.close(stderr.fileno())
```

Or you can use the numeric constants 0, 1 and 2, respectively.

## 4.5 Network/Internet Programming

### 4.5.1 What WWW tools are there for Python?

See the chapters titled *internet* and *netdata* in the Library Reference Manual. Python has many modules that will help you build server-side and client-side web systems.

A summary of available frameworks is maintained by Paul Boddie at <http://wiki.python.org/moin/WebProgramming>.

Cameron Laird maintains a useful set of pages about Python web technologies at [http://phaseit.net/claird/comp.lang.python/web\\_python](http://phaseit.net/claird/comp.lang.python/web_python).

### 4.5.2 How can I mimic CGI form submission (METHOD=POST)?

I would like to retrieve web pages that are the result of POSTing a form. Is there existing code that would let me do this easily?

Yes. Here's a simple example that uses `urllib.request`:

```
#!/usr/local/bin/python

import urllib.request

### build the query string
qs = "First=Josephine&MI=Q&Last=Public"

### connect and send the server a path
req = urllib.request.urlopen('http://www.some-server.out-there'
                              '/cgi-bin/some-cgi-script', data=qs)
msg, hdrs = req.read(), req.info()
```

Note that in general for percent-encoded POST operations, query strings must be quoted using `urllib.parse.urlencode()`. For example, to send `name=Guy Steele, Jr.:`

```
>>> import urllib.parse
>>> urllib.parse.urlencode({'name': 'Guy Steele, Jr.'})
'name=Guy+Steele%2C+Jr.'
```

**See Also:**

*urllib-howto* for extensive examples.

### 4.5.3 What module should I use to help with generating HTML?

You can find a collection of useful links on the [Web Programming wiki page](#).

### 4.5.4 How do I send mail from a Python script?

Use the standard library module `smtplib`.

Here's a very simple interactive mail sender that uses it. This method will work on any host that supports an SMTP listener.

```
import sys, smtplib

fromaddr = input("From: ")
toaddrs = input("To: ").split(',')
print("Enter message, end with ^D:")
msg = ''
while True:
    line = sys.stdin.readline()
    if not line:
        break
    msg += line

# The actual mail send
server = smtplib.SMTP('localhost')
server.sendmail(fromaddr, toaddrs, msg)
server.quit()
```

A Unix-only alternative uses `sendmail`. The location of the `sendmail` program varies between systems; sometimes it is `/usr/lib/sendmail`, sometimes `/usr/sbin/sendmail`. The `sendmail` manual page will help you out. Here's some sample code:

```
SENDMAIL = "/usr/sbin/sendmail" # sendmail location
import os
p = os.popen("%s -t -i" % SENDMAIL, "w")
p.write("To: receiver@example.com\n")
p.write("Subject: test\n")
p.write("\n") # blank line separating headers from body
p.write("Some text\n")
p.write("some more text\n")
sts = p.close()
if sts != 0:
    print("Sendmail exit status", sts)
```

## 4.5.5 How do I avoid blocking in the connect() method of a socket?

The `select` module is commonly used to help with asynchronous I/O on sockets.

To prevent the TCP connect from blocking, you can set the socket to non-blocking mode. Then when you do the `connect()`, you will either connect immediately (unlikely) or get an exception that contains the error number as `.errno.errno.EINPROGRESS` indicates that the connection is in progress, but hasn't finished yet. Different OSes will return different values, so you're going to have to check what's returned on your system.

You can use the `connect_ex()` method to avoid creating an exception. It will just return the `errno` value. To poll, you can call `connect_ex()` again later – 0 or `errno.EISCONN` indicate that you're connected – or you can pass this socket to `select` to check if it's writable.

---

**Note:** The `asyncore` module presents a framework-like approach to the problem of writing non-blocking networking code. The third-party [Twisted](#) library is a popular and feature-rich alternative.

---

## 4.6 Databases

### 4.6.1 Are there any interfaces to database packages in Python?

Yes.

Interfaces to disk-based hashes such as DBM and GDBM are also included with standard Python. There is also the `sqlite3` module, which provides a lightweight disk-based relational database.

Support for most relational databases is available. See the [DatabaseProgramming wiki page](#) for details.

### 4.6.2 How do you implement persistent objects in Python?

The `pickle` library module solves this in a very general way (though you still can't store things like open files, sockets or windows), and the `shelve` library module uses `pickle` and `(g)dbm` to create persistent mappings containing arbitrary Python objects.

## 4.7 Mathematics and Numerics

### 4.7.1 How do I generate random numbers in Python?

The standard module `random` implements a random number generator. Usage is simple:

```
import random
random.random()
```

This returns a random floating point number in the range [0, 1).

There are also many other specialized generators in this module, such as:

- `randrange(a, b)` chooses an integer in the range [a, b).
- `uniform(a, b)` chooses a floating point number in the range [a, b).
- `normalvariate(mean, sdev)` samples the normal (Gaussian) distribution.

Some higher-level functions operate on sequences directly, such as:

- `choice(S)` chooses random element from a given sequence
- `shuffle(L)` shuffles a list in-place, i.e. permutes it randomly

There's also a `Random` class you can instantiate to create independent multiple random number generators.



## EXTENDING/EMBEDDING FAQ

### Contents

- Extending/Embedding FAQ
  - Can I create my own functions in C?
  - Can I create my own functions in C++?
  - Writing C is hard; are there any alternatives?
  - How can I execute arbitrary Python statements from C?
  - How can I evaluate an arbitrary Python expression from C?
  - How do I extract C values from a Python object?
  - How do I use `Py_BuildValue()` to create a tuple of arbitrary length?
  - How do I call an object's method from C?
  - How do I catch the output from `PyErr_Print()` (or anything that prints to `stdout/stderr`)?
  - How do I access a module written in Python from C?
  - How do I interface to C++ objects from Python?
  - I added a module using the Setup file and the make fails; why?
  - How do I debug an extension?
  - I want to compile a Python module on my Linux system, but some files are missing. Why?
  - What does “`SystemError: _PyImport_FixupExtension: module yourmodule not loaded`” mean?
  - How do I tell “incomplete input” from “invalid input”?
  - How do I find undefined g++ symbols `__builtin_new` or `__pure_virtual`?
  - Can I create an object class with some methods implemented in C and others in Python (e.g. through inheritance)?

### 5.1 Can I create my own functions in C?

Yes, you can create built-in modules containing functions, variables, exceptions and even new types in C. This is explained in the document *extending-index*.

Most intermediate or advanced Python books will also cover this topic.

### 5.2 Can I create my own functions in C++?

Yes, using the C compatibility features found in C++. Place `extern "C" { ... }` around the Python include files and put `extern "C"` before each function that is going to be called by the Python interpreter. Global or static C++ objects with constructors are probably not a good idea.

## 5.3 Writing C is hard; are there any alternatives?

There are a number of alternatives to writing your own C extensions, depending on what you're trying to do.

[Cython](#) and its relative [Pyrex](#) are compilers that accept a slightly modified form of Python and generate the corresponding C code. Cython and Pyrex make it possible to write an extension without having to learn Python's C API.

If you need to interface to some C or C++ library for which no Python extension currently exists, you can try wrapping the library's data types and functions with a tool such as [SWIG](#). [SIP](#), [CXX Boost](#), or [Weave](#) are also alternatives for wrapping C++ libraries.

## 5.4 How can I execute arbitrary Python statements from C?

The highest-level function to do this is `PyRun_SimpleString()` which takes a single string argument to be executed in the context of the module `__main__` and returns 0 for success and -1 when an exception occurred (including `SyntaxError`). If you want more control, use `PyRun_String()`; see the source for `PyRun_SimpleString()` in `Python/pythonrun.c`.

## 5.5 How can I evaluate an arbitrary Python expression from C?

Call the function `PyRun_String()` from the previous question with the start symbol `Py_eval_input`; it parses an expression, evaluates it and returns its value.

## 5.6 How do I extract C values from a Python object?

That depends on the object's type. If it's a tuple, `PyTuple_Size()` returns its length and `PyTuple_GetItem()` returns the item at a specified index. Lists have similar functions, `PyList_Size()` and `PyList_GetItem()`.

For strings, `PyString_Size()` returns its length and `PyString_AsString()` a pointer to its value. Note that Python strings may contain null bytes so C's `strlen()` should not be used.

To test the type of an object, first make sure it isn't `NULL`, and then use `PyString_Check()`, `PyTuple_Check()`, `PyList_Check()`, etc.

There is also a high-level API to Python objects which is provided by the so-called 'abstract' interface – read `Include/abstract.h` for further details. It allows interfacing with any kind of Python sequence using calls like `PySequence_Length()`, `PySequence_GetItem()`, etc.) as well as many other useful protocols.

## 5.7 How do I use `Py_BuildValue()` to create a tuple of arbitrary length?

You can't. Use `PyTuple_Pack()` instead.

## 5.8 How do I call an object's method from C?

The `PyObject_CallMethod()` function can be used to call an arbitrary method of an object. The parameters are the object, the name of the method to call, a format string like that used with `Py_BuildValue()`, and the argument values:

```
PyObject *
PyObject_CallMethod(PyObject *object, char *method_name,
                   char *arg_format, ...);
```

This works for any object that has methods – whether built-in or user-defined. You are responsible for eventually `Py_DECREF()` ‘ing the return value.

To call, e.g., a file object’s “seek” method with arguments 10, 0 (assuming the file object pointer is “f”):

```
res = PyObject_CallMethod(f, "seek", "(ii)", 10, 0);
if (res == NULL) {
    ... an exception occurred ...
}
else {
    Py_DECREF(res);
}
```

Note that since `PyObject_CallObject()` *always* wants a tuple for the argument list, to call a function without arguments, pass “()” for the format, and to call a function with one argument, surround the argument in parentheses, e.g. “(i)”.

## 5.9 How do I catch the output from `PyErr_Print()` (or anything that prints to `stdout/stderr`)?

In Python code, define an object that supports the `write()` method. Assign this object to `sys.stdout` and `sys.stderr`. Call `print_error`, or just allow the standard traceback mechanism to work. Then, the output will go wherever your `write()` method sends it.

The easiest way to do this is to use the `io.StringIO` class:

```
>>> import io, sys
>>> sys.stdout = io.StringIO()
>>> print('foo')
>>> print('hello world!')
>>> sys.stderr.write(sys.stdout.getvalue())
foo
hello world!
```

A custom object to do the same would look like this:

```
>>> import io, sys
>>> class StdoutCatcher(io.TextIOBase):
...     def __init__(self):
...         self.data = []
...     def write(self, stuff):
...         self.data.append(stuff)
...
>>> import sys
>>> sys.stdout = StdoutCatcher()
>>> print('foo')
>>> print('hello world!')
>>> sys.stderr.write(''.join(sys.stdout.data))
foo
hello world!
```

## 5.10 How do I access a module written in Python from C?

You can get a pointer to the module object as follows:

```
module = PyImport_ImportModule("<modulename>");
```

If the module hasn't been imported yet (i.e. it is not yet present in `sys.modules`), this initializes the module; otherwise it simply returns the value of `sys.modules["<modulename>"]`. Note that it doesn't enter the module into any namespace – it only ensures it has been initialized and is stored in `sys.modules`.

You can then access the module's attributes (i.e. any name defined in the module) as follows:

```
attr = PyObject_GetAttrString(module, "<attrname>");
```

Calling `PyObject_SetAttrString()` to assign to variables in the module also works.

## 5.11 How do I interface to C++ objects from Python?

Depending on your requirements, there are many approaches. To do this manually, begin by reading *the “Extending and Embedding” document*. Realize that for the Python run-time system, there isn't a whole lot of difference between C and C++ – so the strategy of building a new Python type around a C structure (pointer) type will also work for C++ objects.

For C++ libraries, see *Writing C is hard; are there any alternatives?*.

## 5.12 I added a module using the Setup file and the make fails; why?

Setup must end in a newline, if there is no newline there, the build process fails. (Fixing this requires some ugly shell script hackery, and this bug is so minor that it doesn't seem worth the effort.)

## 5.13 How do I debug an extension?

When using GDB with dynamically loaded extensions, you can't set a breakpoint in your extension until your extension is loaded.

In your `.gdbinit` file (or interactively), add the command:

```
br _PyImport_LoadDynamicModule
```

Then, when you run GDB:

```
$ gdb /local/bin/python
gdb) run myscript.py
gdb) continue # repeat until your extension is loaded
gdb) finish   # so that your extension is loaded
gdb) br myfunction.c:50
gdb) continue
```

## 5.14 I want to compile a Python module on my Linux system, but some files are missing. Why?

Most packaged versions of Python don't include the `/usr/lib/python2.x/config/` directory, which contains various files required for compiling Python extensions.

For Red Hat, install the python-devel RPM to get the necessary files.

For Debian, run `apt-get install python-dev`.

## 5.15 What does “SystemError: \_PyImport\_FixupExtension: module yourmodule not loaded” mean?

This means that you have created an extension module named “yourmodule”, but your module init function does not initialize with that name.

Every module init function will have a line similar to:

```
module = Py_InitModule("yourmodule", yourmodule_functions);
```

If the string passed to this function is not the same name as your extension module, the `SystemError` exception will be raised.

## 5.16 How do I tell “incomplete input” from “invalid input”?

Sometimes you want to emulate the Python interactive interpreter’s behavior, where it gives you a continuation prompt when the input is incomplete (e.g. you typed the start of an “if” statement or you didn’t close your parentheses or triple string quotes), but it gives you a syntax error message immediately when the input is invalid.

In Python you can use the `codeop` module, which approximates the parser’s behavior sufficiently. IDLE uses this, for example.

The easiest way to do it in C is to call `PyRun_InteractiveLoop()` (perhaps in a separate thread) and let the Python interpreter handle the input for you. You can also set the `PyOS_ReadlineFunctionPointer()` to point at your custom input function. See `Modules/readline.c` and `Parser/myreadline.c` for more hints.

However sometimes you have to run the embedded Python interpreter in the same thread as your rest application and you can’t allow the `PyRun_InteractiveLoop()` to stop while waiting for user input. The one solution then is to call `PyParser_ParseString()` and test for `e.error` equal to `E_EOF`, which means the input is incomplete). Here’s a sample code fragment, untested, inspired by code from Alex Farber:

```
#include <Python.h>
#include <node.h>
#include <errcode.h>
#include <grammar.h>
#include <parsetok.h>
#include <compile.h>

int testcomplete(char *code)
/* code should end in \n */
/* return -1 for error, 0 for incomplete, 1 for complete */
{
    node *n;
    perrdetail e;

    n = PyParser_ParseString(code, &PyParser_Grammar,
                             Py_file_input, &e);

    if (n == NULL) {
        if (e.error == E_EOF)
            return 0;
        return -1;
    }

    PyNode_Free(n);
    return 1;
}
```

Another solution is trying to compile the received string with `Py_CompileString()`. If it compiles without errors, try to execute the returned code object by calling `PyEval_EvalCode()`. Otherwise save the input for later. If the compilation fails, find out if it's an error or just more input is required - by extracting the message string from the exception tuple and comparing it to the string "unexpected EOF while parsing". Here is a complete example using the GNU readline library (you may want to ignore **SIGINT** while calling `readline()`):

```
#include <stdio.h>
#include <readline.h>

#include <Python.h>
#include <object.h>
#include <compile.h>
#include <eval.h>

int main (int argc, char* argv[])
{
    int i, j, done = 0;                /* lengths of line, code */
    char ps1[] = ">>> ";
    char ps2[] = "... ";
    char *prompt = ps1;
    char *msg, *line, *code = NULL;
    PyObject *src, *glb, *loc;
    PyObject *exc, *val, *trb, *obj, *dum;

    Py_Initialize ();
    loc = PyDict_New ();
    glb = PyDict_New ();
    PyDict_SetItemString (glb, "__builtins__", PyEval_GetBuiltins ());

    while (!done)
    {
        line = readline (prompt);

        if (NULL == line)              /* CTRL-D pressed */
        {
            done = 1;
        }
        else
        {
            i = strlen (line);

            if (i > 0)
                add_history (line);    /* save non-empty lines */

            if (NULL == code)          /* nothing in code yet */
                j = 0;
            else
                j = strlen (code);

            code = realloc (code, i + j + 2);
            if (NULL == code)          /* out of memory */
                exit (1);

            if (0 == j)                /* code was empty, so */
                code[0] = '\0';        /* keep strncat happy */

            strncat (code, line, i);   /* append line to code */
            code[i + j] = '\n';        /* append '\n' to code */
            code[i + j + 1] = '\0';
        }
    }
}
```

```

src = Py_CompileString (code, "<stdin>", Py_single_input);

if (NULL != src)                                /* compiled just fine - */
{
    if (ps1 == prompt ||                          /* ">>> " or */
        '\n' == code[i + j - 1])                 /* "... " and double '\n' */
    {                                              /* so execute it */
        dum = PyEval_EvalCode (src, glb, loc);
        Py_XDECREF (dum);
        Py_XDECREF (src);
        free (code);
        code = NULL;
        if (PyErr_Occurred ())
            PyErr_Print ();
        prompt = ps1;
    }
}
else if (PyErr_ExceptionMatches (PyExc_SyntaxError)) /* syntax error or E_EOF? */
{
    PyErr_Fetch (&exc, &val, &trb);             /* clears exception! */

    if (PyArg_ParseTuple (val, "sO", &msg, &obj) &&
        !strcmp (msg, "unexpected EOF while parsing")) /* E_EOF */
    {
        Py_XDECREF (exc);
        Py_XDECREF (val);
        Py_XDECREF (trb);
        prompt = ps2;
    }
    else                                          /* some other syntax error */
    {
        PyErr_Restore (exc, val, trb);
        PyErr_Print ();
        free (code);
        code = NULL;
        prompt = ps1;
    }
}
else                                          /* some non-syntax error */
{
    PyErr_Print ();
    free (code);
    code = NULL;
    prompt = ps1;
}

free (line);
}
}

Py_XDECREF (glb);
Py_XDECREF (loc);
Py_Finalize();
exit(0);
}

```

## 5.17 How do I find undefined g++ symbols `__builtin_new` or `__pure_virtual`?

To dynamically load g++ extension modules, you must recompile Python, relink it using g++ (change `LINKCC` in the Python Modules Makefile), and link your extension module using g++ (e.g., `g++ -shared -o mymodule.so mymodule.o`).

## 5.18 Can I create an object class with some methods implemented in C and others in Python (e.g. through inheritance)?

In Python 2.2, you can inherit from built-in classes such as `int`, `list`, `dict`, etc.

The Boost Python Library (BPL, <http://www.boost.org/libs/python/doc/index.html>) provides a way of doing this from C++ (i.e. you can inherit from an extension class written in C++ using the BPL).

# PYTHON ON WINDOWS FAQ

## Contents

- Python on Windows FAQ
  - How do I run a Python program under Windows?
  - How do I make Python scripts executable?
  - Why does Python sometimes take so long to start?
  - Where is Freeze for Windows?
  - Is a \*.pyd file the same as a DLL?
  - How can I embed Python into a Windows application?
  - How do I use Python for CGI?
  - How do I keep editors from inserting tabs into my Python source?
  - How do I check for a keypress without blocking?
  - How do I emulate os.kill() in Windows?
  - Why does os.path.isdir() fail on NT shared directories?
  - cgi.py (or other CGI programming) doesn't work sometimes on NT or win95!
  - Why doesn't os.popen() work in PythonWin on NT?
  - Why doesn't os.popen()/win32pipe.popen() work on Win9x?
  - PyRun\_SimpleFile() crashes on Windows but not on Unix; why?
  - Importing \_tkinter fails on Windows 95/98: why?
  - How do I extract the downloaded documentation on Windows?
  - Missing cw3215mt.dll (or missing cw3215.dll)
  - Warning about CTL3D32 version from installer

## 6.1 How do I run a Python program under Windows?

This is not necessarily a straightforward question. If you are already familiar with running programs from the Windows command line then everything will seem obvious; otherwise, you might need a little more guidance. There are also differences between Windows 95, 98, NT, ME, 2000 and XP which can add to the confusion.



### Python Development on XP

This series of screencasts aims to get you up and running with Python on Windows XP. The knowledge is distilled into 1.5 hours and will get you up and running with the right Python distribution, coding in your choice of IDE, and debugging and writing solid code with unit-tests.

Unless you use some sort of integrated development environment, you will end up *typing* Windows commands into what is variously referred to as a “DOS window” or “Command prompt window”. Usually you can create such a window from your Start menu; under Windows 2000 the menu selection is *Start → Programs → Accessories → Command Prompt*. You should be able to recognize when you have started such a window because you will see a Windows “command prompt”, which usually looks like this:

```
C:\>
```

The letter may be different, and there might be other things after it, so you might just as easily see something like:

```
D:\Steve\Projects\Python>
```

depending on how your computer has been set up and what else you have recently done with it. Once you have started such a window, you are well on the way to running Python programs.

You need to realize that your Python scripts have to be processed by another program called the Python interpreter. The interpreter reads your script, compiles it into bytecodes, and then executes the bytecodes to run your program. So, how do you arrange for the interpreter to handle your Python?

First, you need to make sure that your command window recognises the word “python” as an instruction to start the interpreter. If you have opened a command window, you should try entering the command `python` and hitting return. You should then see something like:

```
Python 2.2 (#28, Dec 21 2001, 12:21:22) [MSC 32 bit (Intel)] on win32
Type "help", "copyright", "credits" or "license" for more information.
>>>
```

You have started the interpreter in “interactive mode”. That means you can enter Python statements or expressions interactively and have them executed or evaluated while you wait. This is one of Python’s strongest features. Check it by entering a few expressions of your choice and seeing the results:

```
>>> print("Hello")
Hello
>>> "Hello" * 3
HelloHelloHello
```

Many people use the interactive mode as a convenient yet highly programmable calculator. When you want to end your interactive Python session, hold the Ctrl key down while you enter a Z, then hit the “Enter” key to get back to your Windows command prompt.

You may also find that you have a Start-menu entry such as *Start → Programs → Python 2.2 → Python (command line)* that results in you seeing the `>>>` prompt in a new window. If so, the window will disappear after you enter the Ctrl-Z character; Windows is running a single “python” command in the window, and closes it when you terminate the interpreter.

If the `python` command, instead of displaying the interpreter prompt `>>>`, gives you a message like:

```
'python' is not recognized as an internal or external command,
operable program or batch file.
```



### Adding Python to DOS Path

Python is not added to the DOS path by default. This screencast will walk you through the steps to add the correct entry to the *System Path*, allowing Python to be executed from the command-line by all users.

or:

Bad command **or** filename

then you need to make sure that your computer knows where to find the Python interpreter. To do this you will have to modify a setting called PATH, which is a list of directories where Windows will look for programs.

You should arrange for Python's installation directory to be added to the PATH of every command window as it starts. If you installed Python fairly recently then the command

```
dir C:\py*
```

will probably tell you where it is installed; the usual location is something like C:\Python23. Otherwise you will be reduced to a search of your whole disk ... use *Tools* → *Find* or hit the *Search* button and look for "python.exe". Supposing you discover that Python is installed in the C:\Python23 directory (the default at the time of writing), you should make sure that entering the command

```
c:\Python23\python
```

starts up the interpreter as above (and don't forget you'll need a "CTRL-Z" and an "Enter" to get out of it). Once you have verified the directory, you need to add it to the start-up routines your computer goes through. For older versions of Windows the easiest way to do this is to edit the C:\AUTOEXEC.BAT file. You would want to add a line like the following to AUTOEXEC.BAT:

```
PATH C:\Python23;%PATH%
```

For Windows NT, 2000 and (I assume) XP, you will need to add a string such as

```
;C:\Python23
```

to the current setting for the PATH environment variable, which you will find in the properties window of "My Computer" under the "Advanced" tab. Note that if you have sufficient privilege you might get a choice of installing the settings either for the Current User or for System. The latter is preferred if you want everybody to be able to run Python on the machine.

If you aren't confident doing any of these manipulations yourself, ask for help! At this stage you may want to reboot your system to make absolutely sure the new setting has taken effect. You probably won't need to reboot for Windows NT, XP or 2000. You can also avoid it in earlier versions by editing the file C:\WINDOWS\COMMAND\CMDINIT.BAT instead of AUTOEXEC.BAT.

You should now be able to start a new command window, enter `python` at the C:\> (or whatever) prompt, and see the >>> prompt that indicates the Python interpreter is reading interactive commands.

Let's suppose you have a program called `pytest.py` in directory C:\Steve\Projects\Python. A session to run that program might look like this:

```
C:\> cd \Steve\Projects\Python
C:\Steve\Projects\Python> python pytest.py
```

Because you added a file name to the command to start the interpreter, when it starts up it reads the Python script in the named file, compiles it, executes it, and terminates, so you see another C:\> prompt. You might also have entered

```
C:\> python \Steve\Projects\Python\pytest.py
```

if you hadn't wanted to change your current directory.

Under NT, 2000 and XP you may well find that the installation process has also arranged that the command `pytest.py` (or, if the file isn't in the current directory, `C:\Steve\Projects\Python\pytest.py`) will automatically recognize the ".py" extension and run the Python interpreter on the named file. Using this feature is fine, but *some* versions of Windows have bugs which mean that this form isn't exactly equivalent to using the interpreter explicitly, so be careful.

The important things to remember are:

1. Start Python from the Start Menu, or make sure the PATH is set correctly so Windows can find the Python interpreter.

```
python
```

should give you a '>>>' prompt from the Python interpreter. Don't forget the CTRL-Z and ENTER to terminate the interpreter (and, if you started the window from the Start Menu, make the window disappear).

2. Once this works, you run programs with commands:

```
python {program-file}
```

3. When you know the commands to use you can build Windows shortcuts to run the Python interpreter on any of your scripts, naming particular working directories, and adding them to your menus. Take a look at

```
python --help
```

if your needs are complex.

4. Interactive mode (where you see the >>> prompt) is best used for checking that individual statements and expressions do what you think they will, and for developing code by experiment.

## 6.2 How do I make Python scripts executable?

On Windows 2000, the standard Python installer already associates the .py extension with a file type (Python.File) and gives that file type an open command that runs the interpreter (`D:\Program Files\Python\python.exe "%1" %*`). This is enough to make scripts executable from the command prompt as 'foo.py'. If you'd rather be able to execute the script by simple typing 'foo' with no extension you need to add .py to the PATHEXT environment variable.

On Windows NT, the steps taken by the installer as described above allow you to run a script with 'foo.py', but a longtime bug in the NT command processor prevents you from redirecting the input or output of any script executed in this way. This is often important.

The incantation for making a Python script executable under WinNT is to give the file an extension of .cmd and add the following as the first line:

```
@setlocal enableextensions & python -x %~f0 %* & goto :EOF
```

## 6.3 Why does Python sometimes take so long to start?

Usually Python starts very quickly on Windows, but occasionally there are bug reports that Python suddenly begins to take a long time to start up. This is made even more puzzling because Python will work fine on other Windows systems which appear to be configured identically.

The problem may be caused by a misconfiguration of virus checking software on the problem machine. Some virus scanners have been known to introduce startup overhead of two orders of magnitude when the scanner is configured to monitor all reads from the filesystem. Try checking the configuration of virus scanning software on your systems to ensure that they are indeed configured identically. McAfee, when configured to scan all file system read activity, is a particular offender.

## 6.4 Where is Freeze for Windows?

“Freeze” is a program that allows you to ship a Python program as a single stand-alone executable file. It is *not* a compiler; your programs don’t run any faster, but they are more easily distributable, at least to platforms with the same OS and CPU. Read the README file of the freeze program for more disclaimers.

You can use freeze on Windows, but you must download the source tree (see <http://www.python.org/download/source>). The freeze program is in the `Tools\freeze` subdirectory of the source tree.

You need the Microsoft VC++ compiler, and you probably need to build Python. The required project files are in the PCbuild directory.

## 6.5 Is a \*.pyd file the same as a DLL?

Yes, .pyd files are dll’s, but there are a few differences. If you have a DLL named `foo.pyd`, then it must have a function `initfoo()`. You can then write Python “import foo”, and Python will search for `foo.pyd` (as well as `foo.py`, `foo.pyc`) and if it finds it, will attempt to call `initfoo()` to initialize it. You do not link your .exe with `foo.lib`, as that would cause Windows to require the DLL to be present.

Note that the search path for `foo.pyd` is `PYTHONPATH`, not the same as the path that Windows uses to search for `foo.dll`. Also, `foo.pyd` need not be present to run your program, whereas if you linked your program with a dll, the dll is required. Of course, `foo.pyd` is required if you want to say `import foo`. In a DLL, linkage is declared in the source code with `__declspec(dllexport)`. In a .pyd, linkage is defined in a list of available functions.

## 6.6 How can I embed Python into a Windows application?

Embedding the Python interpreter in a Windows app can be summarized as follows:

1. Do `_not_` build Python into your .exe file directly. On Windows, Python must be a DLL to handle importing modules that are themselves DLL’s. (This is the first key undocumented fact.) Instead, link to `pythonNN.dll`; it is typically installed in `C:\Windows\System`. *NN* is the Python version, a number such as “23” for Python 2.3.

You can link to Python in two different ways. Load-time linking means linking against `pythonNN.lib`, while run-time linking means linking against `pythonNN.dll`. (General note: `pythonNN.lib` is the so-called “import lib” corresponding to `pythonNN.dll`. It merely defines symbols for the linker.)

Run-time linking greatly simplifies link options; everything happens at run time. Your code must load `pythonNN.dll` using the Windows `LoadLibraryEx()` routine. The code must also use access routines and data in `pythonNN.dll` (that is, Python’s C API’s) using pointers obtained by the Windows `GetProcAddress()` routine. Macros can make using these pointers transparent to any C code that calls routines in Python’s C API.

Borland note: convert `pythonNN.lib` to OMF format using `Coff2Omf.exe` first.

2. If you use SWIG, it is easy to create a Python “extension module” that will make the app’s data and methods available to Python. SWIG will handle just about all the grungy details for you. The result is C code that you link *into* your .exe file (!) You do `_not_` have to create a DLL file, and this also simplifies linking.
3. SWIG will create an init function (a C function) whose name depends on the name of the extension module. For example, if the name of the module is `leo`, the init function will be called `initleo()`. If you use SWIG shadow classes, as you should, the init function will be called `initleoC()`. This initializes a mostly hidden helper class used by the shadow class.

The reason you can link the C code in step 2 into your .exe file is that calling the initialization function is equivalent to importing the module into Python! (This is the second key undocumented fact.)

4. In short, you can use the following code to initialize the Python interpreter with your extension module.

```
#include "python.h"
...
Py_Initialize(); // Initialize Python.
initmyAppc(); // Initialize (import) the helper class.
PyRun_SimpleString("import myApp") ; // Import the shadow class.
```

5. There are two problems with Python's C API which will become apparent if you use a compiler other than MSVC, the compiler used to build pythonNN.dll.

Problem 1: The so-called "Very High Level" functions that take FILE \* arguments will not work in a multi-compiler environment because each compiler's notion of a struct FILE will be different. From an implementation standpoint these are very `_low_level` functions.

Problem 2: SWIG generates the following code when generating wrappers to void functions:

```
Py_INCREF(Py_None);
_resultobj = Py_None;
return _resultobj;
```

Alas, `Py_None` is a macro that expands to a reference to a complex data structure called `_Py_NoneStruct` inside `pythonNN.dll`. Again, this code will fail in a multi-compiler environment. Replace such code by:

```
return Py_BuildValue("");
```

It may be possible to use SWIG's `%typemap` command to make the change automatically, though I have not been able to get this to work (I'm a complete SWIG newbie).

6. Using a Python shell script to put up a Python interpreter window from inside your Windows app is not a good idea; the resulting window will be independent of your app's windowing system. Rather, you (or the `wxPythonWindow` class) should create a "native" interpreter window. It is easy to connect that window to the Python interpreter. You can redirect Python's i/o to `_any_` object that supports read and write, so all you need is a Python object (defined in your extension module) that contains `read()` and `write()` methods.

## 6.7 How do I use Python for CGI?

On the Microsoft IIS server or on the Win95 MS Personal Web Server you set up Python in the same way that you would set up any other scripting engine.

Run `regedt32` and go to:

```
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\W3SVC\Parameters\ScriptMap
```

and enter the following line (making any specific changes that your system may need):

```
.py :REG_SZ: c:\<path to python>\python.exe -u %s %s
```

This line will allow you to call your script with a simple reference like: `http://yourserver/scripts/yourscript.py` provided "scripts" is an "executable" directory for your server (which it usually is by default). The `-u` flag specifies unbuffered and binary mode for stdin - needed when working with binary data.

In addition, it is recommended that using ".py" may not be a good idea for the file extensions when used in this context (you might want to reserve \*.py for support modules and use \*.cgi or \*.cgp for "main program" scripts).

In order to set up Internet Information Services 5 to use Python for CGI processing, please see the following links:

[http://www.e-coli.net/pyiis\\_server.html](http://www.e-coli.net/pyiis_server.html) (for Win2k Server) <http://www.e-coli.net/pyiis.html> (for Win2k pro)

Configuring Apache is much simpler. In the Apache configuration file `httpd.conf`, add the following line at the end of the file:

```
ScriptInterpreterSource Registry
```

Then, give your Python CGI-scripts the extension `.py` and put them in the `cgi-bin` directory.

## 6.8 How do I keep editors from inserting tabs into my Python source?

The FAQ does not recommend using tabs, and the Python style guide, [PEP 8](#), recommends 4 spaces for distributed Python code; this is also the Emacs python-mode default.

Under any editor, mixing tabs and spaces is a bad idea. MSVC is no different in this respect, and is easily configured to use spaces: Take *Tools* → *Options* → *Tabs*, and for file type “Default” set “Tab size” and “Indent size” to 4, and select the “Insert spaces” radio button.

If you suspect mixed tabs and spaces are causing problems in leading whitespace, run Python with the `-t` switch or run `Tools/Scripts/tabnanny.py` to check a directory tree in batch mode.

## 6.9 How do I check for a keypress without blocking?

Use the `msvcrt` module. This is a standard Windows-specific extension module. It defines a function `kbhit()` which checks whether a keyboard hit is present, and `getch()` which gets one character without echoing it.

## 6.10 How do I emulate `os.kill()` in Windows?

Prior to Python 2.7 and 3.2, to terminate a process, you can use `ctypes`:

```
import ctypes

def kill(pid):
    """kill function for Win32"""
    kernel32 = ctypes.windll.kernel32
    handle = kernel32.OpenProcess(1, 0, pid)
    return (0 != kernel32.TerminateProcess(handle, 0))
```

In 2.7 and 3.2, `os.kill()` is implemented similar to the above function, with the additional feature of being able to send CTRL+C and CTRL+BREAK to console subprocesses which are designed to handle those signals. See `os.kill()` for further details.

## 6.11 Why does `os.path.isdir()` fail on NT shared directories?

The solution appears to be always append the “\” on the end of shared drives.

```
>>> import os
>>> os.path.isdir( '\\\\rorschach\\public')
0
>>> os.path.isdir( '\\\\rorschach\\public\\')
1
```

It helps to think of share points as being like drive letters. Example:

```
k: is not a directory
k:\ is a directory
k:\media is a directory
k:\media\ is not a directory
```

The same rules apply if you substitute “k:” with “\conkyfoo”:

```
\\conky\foo is not a directory
\\conky\foo\ is a directory
\\conky\foo\media is a directory
\\conky\foo\media\ is not a directory
```

## 6.12 cgi.py (or other CGI programming) doesn't work sometimes on NT or win95!

Be sure you have the latest python.exe, that you are using python.exe rather than a GUI version of Python and that you have configured the server to execute

```
"...\python.exe -u ..."
```

for the CGI execution. The `-u` (unbuffered) option on NT and Win95 prevents the interpreter from altering new-lines in the standard input and output. Without it post/multipart requests will seem to have the wrong length and binary (e.g. GIF) responses may get garbled (resulting in broken images, PDF files, and other binary downloads failing).

## 6.13 Why doesn't os.popen() work in PythonWin on NT?

The reason that `os.popen()` doesn't work from within PythonWin is due to a bug in Microsoft's C Runtime Library (CRT). The CRT assumes you have a Win32 console attached to the process.

You should use the `win32pipe` module's `popen()` instead which doesn't depend on having an attached Win32 console.

Example:

```
import win32pipe
f = win32pipe.popen('dir /c c:\\')
print(f.readlines())
f.close()
```

## 6.14 Why doesn't os.popen()/win32pipe.popen() work on Win9x?

There is a bug in Win9x that prevents `os.popen/win32pipe.popen*` from working. The good news is there is a way to work around this problem. The Microsoft Knowledge Base article that you need to lookup is: Q150956. You will find links to the knowledge base at: <http://support.microsoft.com/>.

## 6.15 PyRun\_SimpleFile() crashes on Windows but not on Unix; why?

This is very sensitive to the compiler vendor, version and (perhaps) even options. If the `FILE*` structure in your embedding program isn't the same as is assumed by the Python interpreter it won't work.

The Python 1.5.\* DLLs (`python15.dll`) are all compiled with MS VC++ 5.0 and with `multithreading-DLL` options (`/MD`).

If you can't change compilers or flags, try using `Py_RunSimpleString()`. A trick to get it to run an arbitrary file is to construct a call to `exec()` and `open()` with the name of your file as argument.

Also note that you can not mix-and-match Debug and Release versions. If you wish to use the Debug Multi-threaded DLL, then your module *must* have `_d` appended to the base name.

## 6.16 Importing \_tkinter fails on Windows 95/98: why?

Sometimes, the import of `_tkinter` fails on Windows 95 or 98, complaining with a message like the following:

```
ImportError: DLL load failed: One of the library files needed
to run this application cannot be found.
```

It could be that you haven't installed Tcl/Tk, but if you did install Tcl/Tk, and the Wish application works correctly, the problem may be that its installer didn't manage to edit the autoexec.bat file correctly. It tries to add a statement that changes the PATH environment variable to include the Tcl/Tk 'bin' subdirectory, but sometimes this edit doesn't quite work. Opening it with notepad usually reveals what the problem is.

(One additional hint, noted by David Szafranski: you can't use long filenames here; e.g. use C:\PROGRA~1\Tcl\bin instead of C:\Program Files\Tcl\bin.)

## 6.17 How do I extract the downloaded documentation on Windows?

Sometimes, when you download the documentation package to a Windows machine using a web browser, the file extension of the saved file ends up being .EXE. This is a mistake; the extension should be .TGZ.

Simply rename the downloaded file to have the .TGZ extension, and WinZip will be able to handle it. (If your copy of WinZip doesn't, get a newer one from <http://www.winzip.com>.)

## 6.18 Missing cw3215mt.dll (or missing cw3215.dll)

Sometimes, when using Tkinter on Windows, you get an error that cw3215mt.dll or cw3215.dll is missing.

Cause: you have an old Tcl/Tk DLL built with cygwin in your path (probably C:\Windows). You must use the Tcl/Tk DLLs from the standard Tcl/Tk installation (Python 1.5.2 comes with one).

## 6.19 Warning about CTL3D32 version from installer

The Python installer issues a warning like this:

```
This version uses CTL3D32.DLL which is not the correct version.
This version is used for windows NT applications only.
```

Tim Peters:

This is a Microsoft DLL, and a notorious source of problems. The message means what it says: you have the wrong version of this DLL for your operating system. The Python installation did not cause this – something else you installed previous to this overwrote the DLL that came with your OS (probably older shareware of some sort, but there's no way to tell now). If you search for "CTL3D32" using any search engine (AltaVista, for example), you'll find hundreds and hundreds of web pages complaining about the same problem with all sorts of installation programs. They'll point you to ways to get the correct version reinstalled on your system (since Python doesn't cause this, we can't fix it).

David A Burton has written a little program to fix this. Go to <http://www.burtonsys.com/downloads.html> and click on "ctl3dfix.zip".



# GRAPHIC USER INTERFACE FAQ

## Contents

- Graphic User Interface FAQ
  - General GUI Questions
  - What platform-independent GUI toolkits exist for Python?
    - \* Tkinter
    - \* wxWidgets
    - \* Qt
    - \* Gtk+
    - \* FLTK
    - \* FOX
    - \* OpenGL
  - What platform-specific GUI toolkits exist for Python?
  - Tkinter questions
    - \* How do I freeze Tkinter applications?
    - \* Can I have Tk events handled while waiting for I/O?
    - \* I can't get key bindings to work in Tkinter: why?

## 7.1 General GUI Questions

## 7.2 What platform-independent GUI toolkits exist for Python?

Depending on what platform(s) you are aiming at, there are several. Some of them haven't been ported to Python 3 yet. At least [Tkinter](#) and [Qt](#) are known to be Python 3-compatible.

### 7.2.1 Tkinter

Standard builds of Python include an object-oriented interface to the Tcl/Tk widget set, called *tkinter*. This is probably the easiest to install (since it comes included with most [binary distributions](#) of Python) and use. For more info about Tk, including pointers to the source, see the [Tcl/Tk home page](#). Tcl/Tk is fully portable to the MacOS, Windows, and Unix platforms.

### 7.2.2 wxWidgets

wxWidgets (<http://www.wxwidgets.org>) is a free, portable GUI class library written in C++ that provides a native look and feel on a number of platforms, with Windows, MacOS X, GTK, X11, all listed as current stable targets. Language bindings are available for a number of languages including Python, Perl, Ruby, etc.

wxPython (<http://www.wxpython.org>) is the Python binding for wxwidgets. While it often lags slightly behind the official wxWidgets releases, it also offers a number of features via pure Python extensions that are not available in other language bindings. There is an active wxPython user and developer community.

Both wxWidgets and wxPython are free, open source, software with permissive licences that allow their use in commercial products as well as in freeware or shareware.

### 7.2.3 Qt

There are bindings available for the Qt toolkit (using either [PyQt](#) or [PySide](#)) and for KDE ([PyKDE](#)). PyQt is currently more mature than PySide, but you must buy a PyQt license from [Riverbank Computing](#) if you want to write proprietary applications. PySide is free for all applications.

Qt 4.5 upwards is licensed under the LGPL license; also, commercial licenses are available from [Nokia](#).

### 7.2.4 Gtk+

The GObject introspection bindings for Python allow you to write GTK+ 3 applications. There is also a [Python GTK+ 3 Tutorial](#).

The older PyGtk bindings for the [Gtk+ 2 toolkit](#) have been implemented by James Henstridge; see <http://www.pygtk.org>.

### 7.2.5 FLTK

Python bindings for the [FLTK toolkit](#), a simple yet powerful and mature cross-platform windowing system, are available from the [PyFLTK project](#).

### 7.2.6 FOX

A wrapper for the [FOX toolkit](#) called [FXpy](#) is available. FOX supports both Unix variants and Windows.

### 7.2.7 OpenGL

For OpenGL bindings, see [PyOpenGL](#).

## 7.3 What platform-specific GUI toolkits exist for Python?

The [Mac port](#) by Jack Jansen has a rich and ever-growing set of modules that support the native Mac toolbox calls. The port supports MacOS X's Carbon libraries.

By installing the [PyObjc Objective-C bridge](#), Python programs can use MacOS X's Cocoa libraries. See the documentation that comes with the Mac port.

[Pythonwin](#) by Mark Hammond includes an interface to the Microsoft Foundation Classes and a Python programming environment that's written mostly in Python using the MFC classes.

## 7.4 Tkinter questions

### 7.4.1 How do I freeze Tkinter applications?

Freeze is a tool to create stand-alone applications. When freezing Tkinter applications, the applications will not be truly stand-alone, as the application will still need the Tcl and Tk libraries.

One solution is to ship the application with the Tcl and Tk libraries, and point to them at run-time using the `TCL_LIBRARY` and `TK_LIBRARY` environment variables.

To get truly stand-alone applications, the Tcl scripts that form the library have to be integrated into the application as well. One tool supporting that is SAM (stand-alone modules), which is part of the Tix distribution (<http://tix.sourceforge.net/>).

Build Tix with SAM enabled, perform the appropriate call to `Tclsam_init()`, etc. inside Python's `Modules/tkappinit.c`, and link with `libtclsam` and `libtkjam` (you might include the Tix libraries as well).

## 7.4.2 Can I have Tk events handled while waiting for I/O?

Yes, and you don't even need threads! But you'll have to restructure your I/O code a bit. Tk has the equivalent of Xt's `XtAddInput()` call, which allows you to register a callback function which will be called from the Tk mainloop when I/O is possible on a file descriptor. Here's what you need:

```
from Tkinter import tkinter
tkinter.createfilehandler(file, mask, callback)
```

The file may be a Python file or socket object (actually, anything with a `fileno()` method), or an integer file descriptor. The mask is one of the constants `tkinter.READABLE` or `tkinter.WRITABLE`. The callback is called as follows:

```
callback(file, mask)
```

You must unregister the callback when you're done, using

```
tkinter.deletefilehandler(file)
```

Note: since you don't know *how many bytes* are available for reading, you can't use the Python file object's `read` or `readline` methods, since these will insist on reading a predefined number of bytes. For sockets, the `recv()` or `recvfrom()` methods will work fine; for other files, use `os.read(file.fileno(), maxbytescount)`.

## 7.4.3 I can't get key bindings to work in Tkinter: why?

An often-heard complaint is that event handlers bound to events with the `bind()` method don't get handled even when the appropriate key is pressed.

The most common cause is that the widget to which the binding applies doesn't have "keyboard focus". Check out the Tk documentation for the focus command. Usually a widget is given the keyboard focus by clicking in it (but not for labels; see the `takefocus` option).



# “WHY IS PYTHON INSTALLED ON MY COMPUTER?” FAQ

## 8.1 What is Python?

Python is a programming language. It's used for many different applications. It's used in some high schools and colleges as an introductory programming language because Python is easy to learn, but it's also used by professional software developers at places such as Google, NASA, and Lucasfilm Ltd.

If you wish to learn more about Python, start with the [Beginner's Guide to Python](#).

## 8.2 Why is Python installed on my machine?

If you find Python installed on your system but don't remember installing it, there are several possible ways it could have gotten there.

- Perhaps another user on the computer wanted to learn programming and installed it; you'll have to figure out who's been using the machine and might have installed it.
- A third-party application installed on the machine might have been written in Python and included a Python installation. There are many such applications, from GUI programs to network servers and administrative scripts.
- Some Windows machines also have Python installed. At this writing we're aware of computers from Hewlett-Packard and Compaq that include Python. Apparently some of HP/Compaq's administrative tools are written in Python.
- Many Unix-compatible operating systems, such as Mac OS X and some Linux distributions, have Python installed by default; it's included in the base installation.

## 8.3 Can I delete Python?

That depends on where Python came from.

If someone installed it deliberately, you can remove it without hurting anything. On Windows, use the Add/Remove Programs icon in the Control Panel.

If Python was installed by a third-party application, you can also remove it, but that application will no longer work. You should use that application's uninstaller rather than removing Python directly.

If Python came with your operating system, removing it is not recommended. If you remove it, whatever tools were written in Python will no longer run, and some of them might be important to you. Reinstalling the whole system would then be required to fix things again.



---

# GLOSSARY

**>>>** The default Python prompt of the interactive shell. Often seen for code examples which can be executed interactively in the interpreter.

**. . .** The default Python prompt of the interactive shell when entering code for an indented code block or within a pair of matching left and right delimiters (parentheses, square brackets or curly braces).

**2to3** A tool that tries to convert Python 2.x code to Python 3.x code by handling most of the incompatibilities which can be detected by parsing the source and traversing the parse tree.

2to3 is available in the standard library as `lib2to3`; a standalone entry point is provided as `Tools/scripts/2to3`. See *2to3-reference*.

**abstract base class** Abstract base classes complement *duck-typing* by providing a way to define interfaces when other techniques like `hasattr()` would be clumsy or subtly wrong (for example with *magic methods*). ABCs introduce virtual subclasses, which are classes that don't inherit from a class but are still recognized by `isinstance()` and `issubclass()`; see the `abc` module documentation. Python comes with many built-in ABCs for data structures (in the `collections.abc` module), numbers (in the `numbers` module), streams (in the `io` module), import finders and loaders (in the `importlib.abc` module). You can create your own ABCs with the `abc` module.

**argument** A value passed to a function or method, assigned to a named local variable in the function body. A function or method may have both positional arguments and keyword arguments in its definition. Positional and keyword arguments may be variable-length: `*` accepts or passes (if in the function definition or call) several positional arguments in a list, while `**` does the same for keyword arguments in a dictionary.

Any expression may be used within the argument list, and the evaluated value is passed to the local variable.

**attribute** A value associated with an object which is referenced by name using dotted expressions. For example, if an object *o* has an attribute *a* it would be referenced as *o.a*.

**BDFL** Benevolent Dictator For Life, a.k.a. [Guido van Rossum](#), Python's creator.

**bytecode** Python source code is compiled into bytecode, the internal representation of a Python program in the CPython interpreter. The bytecode is also cached in `.pyc` and `.pyo` files so that executing the same file is faster the second time (recompilation from source to bytecode can be avoided). This “intermediate language” is said to run on a *virtual machine* that executes the machine code corresponding to each bytecode. Do note that bytecodes are not expected to work between different Python virtual machines, nor to be stable between Python releases.

A list of bytecode instructions can be found in the documentation for *the dis module*.

**class** A template for creating user-defined objects. Class definitions normally contain method definitions which operate on instances of the class.

**coercion** The implicit conversion of an instance of one type to another during an operation which involves two arguments of the same type. For example, `int(3.15)` converts the floating point number to the integer 3, but in `3+4.5`, each argument is of a different type (one int, one float), and both must be converted to the same type before they can be added or it will raise a `TypeError`. Without coercion, all arguments of even compatible types would have to be normalized to the same value by the programmer, e.g., `float(3)+4.5` rather than just `3+4.5`.

**complex number** An extension of the familiar real number system in which all numbers are expressed as a sum of a real part and an imaginary part. Imaginary numbers are real multiples of the imaginary unit (the square root of  $-1$ ), often written  $i$  in mathematics or  $j$  in engineering. Python has built-in support for complex numbers, which are written with this latter notation; the imaginary part is written with a  $j$  suffix, e.g.,  $3+1j$ . To get access to complex equivalents of the `math` module, use `cmath`. Use of complex numbers is a fairly advanced mathematical feature. If you're not aware of a need for them, it's almost certain you can safely ignore them.

**context manager** An object which controls the environment seen in a `with` statement by defining `__enter__()` and `__exit__()` methods. See [PEP 343](#).

**CPython** The canonical implementation of the Python programming language, as distributed on [python.org](http://python.org). The term “CPython” is used when necessary to distinguish this implementation from others such as Jython or IronPython.

**decorator** A function returning another function, usually applied as a function transformation using the `@wrapper` syntax. Common examples for decorators are `classmethod()` and `staticmethod()`.

The decorator syntax is merely syntactic sugar, the following two function definitions are semantically equivalent:

```
def f(...):  
    ...  
f = staticmethod(f)  
  
@staticmethod  
def f(...):  
    ...
```

The same concept exists for classes, but is less commonly used there. See the documentation for *function definitions* and *class definitions* for more about decorators.

**descriptor** Any object which defines the methods `__get__()`, `__set__()`, or `__delete__()`. When a class attribute is a descriptor, its special binding behavior is triggered upon attribute lookup. Normally, using `a.b` to get, set or delete an attribute looks up the object named `b` in the class dictionary for `a`, but if `b` is a descriptor, the respective descriptor method gets called. Understanding descriptors is a key to a deep understanding of Python because they are the basis for many features including functions, methods, properties, class methods, static methods, and reference to super classes.

For more information about descriptors' methods, see *descriptors*.

**dictionary** An associative array, where arbitrary keys are mapped to values. The keys can be any object with `__hash__()` and `__eq__()` methods. Called a hash in Perl.

**docstring** A string literal which appears as the first expression in a class, function or module. While ignored when the suite is executed, it is recognized by the compiler and put into the `__doc__` attribute of the enclosing class, function or module. Since it is available via introspection, it is the canonical place for documentation of the object.

**duck-typing** A programming style which does not look at an object's type to determine if it has the right interface; instead, the method or attribute is simply called or used (“If it looks like a duck and quacks like a duck, it must be a duck.”) By emphasizing interfaces rather than specific types, well-designed code improves its flexibility by allowing polymorphic substitution. Duck-typing avoids tests using `type()` or `isinstance()`. (Note, however, that duck-typing can be complemented with *abstract base classes*.) Instead, it typically employs `hasattr()` tests or *EAFP* programming.

**EAFP** Easier to ask for forgiveness than permission. This common Python coding style assumes the existence of valid keys or attributes and catches exceptions if the assumption proves false. This clean and fast style is characterized by the presence of many `try` and `except` statements. The technique contrasts with the *LBYL* style common to many other languages such as C.

**expression** A piece of syntax which can be evaluated to some value. In other words, an expression is an accumulation of expression elements like literals, names, attribute access, operators or function calls which all return a value. In contrast to many other languages, not all language constructs are expressions. There

are also *statements* which cannot be used as expressions, such as `if`. Assignments are also statements, not expressions.

**extension module** A module written in C or C++, using Python's C API to interact with the core and with user code.

**file object** An object exposing a file-oriented API (with methods such as `read()` or `write()`) to an underlying resource. Depending on the way it was created, a file object can mediate access to a real on-disk file or to another type of storage or communication device (for example standard input/output, in-memory buffers, sockets, pipes, etc.). File objects are also called *file-like objects* or *streams*.

There are actually three categories of file objects: raw binary files, buffered binary files and text files. Their interfaces are defined in the `io` module. The canonical way to create a file object is by using the `open()` function.

**file-like object** A synonym for *file object*.

**finder** An object that tries to find the *loader* for a module. It must implement either a method named `find_loader()` or a method named `find_module()`. See [PEP 302](#) and [PEP 420](#) for details and `importlib.abc.Finder` for an *abstract base class*.

**floor division** Mathematical division that rounds down to nearest integer. The floor division operator is `//`. For example, the expression `11 // 4` evaluates to 2 in contrast to the 2.75 returned by float true division. Note that `(-11) // 4` is -3 because that is -2.75 rounded *downward*. See [PEP 238](#).

**function** A series of statements which returns some value to a caller. It can also be passed zero or more arguments which may be used in the execution of the body. See also *argument* and *method*.

**`__future__`** A pseudo-module which programmers can use to enable new language features which are not compatible with the current interpreter.

By importing the `__future__` module and evaluating its variables, you can see when a new feature was first added to the language and when it becomes the default:

```
>>> import __future__
>>> __future__.division
_Feature((2, 2, 0, 'alpha', 2), (3, 0, 0, 'alpha', 0), 8192)
```

**garbage collection** The process of freeing memory when it is not used anymore. Python performs garbage collection via reference counting and a cyclic garbage collector that is able to detect and break reference cycles.

**generator** A function which returns an iterator. It looks like a normal function except that it contains `yield` statements for producing a series of values usable in a for-loop or that can be retrieved one at a time with the `next()` function. Each `yield` temporarily suspends processing, remembering the location execution state (including local variables and pending try-statements). When the generator resumes, it picks-up where it left-off (in contrast to functions which start fresh on every invocation).

**generator expression** An expression that returns an iterator. It looks like a normal expression followed by a `for` expression defining a loop variable, range, and an optional `if` expression. The combined expression generates values for an enclosing function:

```
>>> sum(i*i for i in range(10))           # sum of squares 0, 1, 4, ... 81
285
```

**GIL** See *global interpreter lock*.

**global interpreter lock** The mechanism used by the *CPython* interpreter to assure that only one thread executes Python *bytecode* at a time. This simplifies the CPython implementation by making the object model (including critical built-in types such as `dict`) implicitly safe against concurrent access. Locking the entire interpreter makes it easier for the interpreter to be multi-threaded, at the expense of much of the parallelism afforded by multi-processor machines.

However, some extension modules, either standard or third-party, are designed so as to release the GIL when doing computationally-intensive tasks such as compression or hashing. Also, the GIL is always released when doing I/O.

Past efforts to create a “free-threaded” interpreter (one which locks shared data at a much finer granularity) have not been successful because performance suffered in the common single-processor case. It is believed that overcoming this performance issue would make the implementation much more complicated and therefore costlier to maintain.

**hashable** An object is *hashable* if it has a hash value which never changes during its lifetime (it needs a `__hash__()` method), and can be compared to other objects (it needs an `__eq__()` method). Hashable objects which compare equal must have the same hash value.

Hashability makes an object usable as a dictionary key and a set member, because these data structures use the hash value internally.

All of Python’s immutable built-in objects are hashable, while no mutable containers (such as lists or dictionaries) are. Objects which are instances of user-defined classes are hashable by default; they all compare unequal, and their hash value is their `id()`.

**IDLE** An Integrated Development Environment for Python. IDLE is a basic editor and interpreter environment which ships with the standard distribution of Python.

**immutable** An object with a fixed value. Immutable objects include numbers, strings and tuples. Such an object cannot be altered. A new object has to be created if a different value has to be stored. They play an important role in places where a constant hash value is needed, for example as a key in a dictionary.

**import path** A list of locations (or *path entries*) that are searched by the *path based finder* for modules to import. During import, this list of locations usually comes from `sys.path`, but for subpackages it may also come from the parent package’s `__path__` attribute.

**importing** The process by which Python code in one module is made available to Python code in another module.

**importer** An object that both finds and loads a module; both a *finder* and *loader* object.

**interactive** Python has an interactive interpreter which means you can enter statements and expressions at the interpreter prompt, immediately execute them and see their results. Just launch `python` with no arguments (possibly by selecting it from your computer’s main menu). It is a very powerful way to test out new ideas or inspect modules and packages (remember `help(x)`).

**interpreted** Python is an interpreted language, as opposed to a compiled one, though the distinction can be blurry because of the presence of the bytecode compiler. This means that source files can be run directly without explicitly creating an executable which is then run. Interpreted languages typically have a shorter development/debug cycle than compiled ones, though their programs generally also run more slowly. See also *interactive*.

**iterable** An object capable of returning its members one at a time. Examples of iterables include all sequence types (such as `list`, `str`, and `tuple`) and some non-sequence types like `dict` and `file` and objects of any classes you define with an `__iter__()` or `__getitem__()` method. Iterables can be used in a `for` loop and in many other places where a sequence is needed (`zip()`, `map()`, ...). When an iterable object is passed as an argument to the built-in function `iter()`, it returns an iterator for the object. This iterator is good for one pass over the set of values. When using iterables, it is usually not necessary to call `iter()` or deal with iterator objects yourself. The `for` statement does that automatically for you, creating a temporary unnamed variable to hold the iterator for the duration of the loop. See also *iterator*, *sequence*, and *generator*.

**iterator** An object representing a stream of data. Repeated calls to the iterator’s `__next__()` method (or passing it to the built-in function `next()`) return successive items in the stream. When no more data are available a `StopIteration` exception is raised instead. At this point, the iterator object is exhausted and any further calls to its `__next__()` method just raise `StopIteration` again. Iterators are required to have an `__iter__()` method that returns the iterator object itself so every iterator is also iterable and may be used in most places where other iterables are accepted. One notable exception is code which attempts multiple iteration passes. A container object (such as a `list`) produces a fresh new iterator each time you pass it to the `iter()` function or use it in a `for` loop. Attempting this with an iterator will just return the same exhausted iterator object used in the previous iteration pass, making it appear like an empty container.

More information can be found in *typeiter*.

**key function** A key function or collation function is a callable that returns a value used for sorting or ordering. For example, `locale.strxfrm()` is used to produce a sort key that is aware of locale specific sort conventions.

A number of tools in Python accept key functions to control how elements are ordered or grouped. They include `min()`, `max()`, `sorted()`, `list.sort()`, `heapq.nsmallest()`, `heapq.nlargest()`, and `itertools.groupby()`.

There are several ways to create a key function. For example, the `str.lower()` method can serve as a key function for case insensitive sorts. Alternatively, an ad-hoc key function can be built from a lambda expression such as `lambda r: (r[0], r[2])`. Also, the `operator` module provides three key function constructors: `attrgetter()`, `itemgetter()`, and `methodcaller()`. See the *Sorting HOW TO* for examples of how to create and use key functions.

**keyword argument** Arguments which are preceded with a `variable_name=` in the call. The variable name designates the local name in the function to which the value is assigned. `**` is used to accept or pass a dictionary of keyword arguments. See *argument*.

**lambda** An anonymous inline function consisting of a single *expression* which is evaluated when the function is called. The syntax to create a lambda function is `lambda [arguments]: expression`

**LBYL** Look before you leap. This coding style explicitly tests for pre-conditions before making calls or lookups. This style contrasts with the *EAFP* approach and is characterized by the presence of many `if` statements.

In a multi-threaded environment, the LBYL approach can risk introducing a race condition between “the looking” and “the leaping”. For example, the code, `if key in mapping: return mapping[key]` can fail if another thread removes *key* from *mapping* after the test, but before the lookup. This issue can be solved with locks or by using the *EAFP* approach.

**list** A built-in Python *sequence*. Despite its name it is more akin to an array in other languages than to a linked list since access to elements are  $O(1)$ .

**list comprehension** A compact way to process all or part of the elements in a sequence and return a list with the results. `result = ['{:04x}'.format(x) for x in range(256) if x % 2 == 0]` generates a list of strings containing even hex numbers (0x..) in the range from 0 to 255. The `if` clause is optional. If omitted, all elements in `range(256)` are processed.

**loader** An object that loads a module. It must define a method named `load_module()`. A loader is typically returned by a *finder*. See **PEP 302** for details and `importlib.abc.Loader` for an *abstract base class*.

**mapping** A container object that supports arbitrary key lookups and implements the methods specified in the Mapping or MutableMapping *abstract base classes*. Examples include `dict`, `collections.defaultdict`, `collections.OrderedDict` and `collections.Counter`.

**meta path finder** A finder returned by a search of `sys.meta_path`. Meta path finders are related to, but different from *path entry finders*.

**metaclass** The class of a class. Class definitions create a class name, a class dictionary, and a list of base classes. The metaclass is responsible for taking those three arguments and creating the class. Most object oriented programming languages provide a default implementation. What makes Python special is that it is possible to create custom metaclasses. Most users never need this tool, but when the need arises, metaclasses can provide powerful, elegant solutions. They have been used for logging attribute access, adding thread-safety, tracking object creation, implementing singletons, and many other tasks.

More information can be found in *metaclasses*.

**method** A function which is defined inside a class body. If called as an attribute of an instance of that class, the method will get the instance object as its first *argument* (which is usually called `self`). See *function* and *nested scope*.

**method resolution order** Method Resolution Order is the order in which base classes are searched for a member during lookup. See [The Python 2.3 Method Resolution Order](#).

**module** An object that serves as an organizational unit of Python code. Modules have a namespace containing arbitrary Python objects. Modules are loaded into Python by the process of *importing*.

**MRO** See *method resolution order*.

**mutable** Mutable objects can change their value but keep their `id()`. See also *immutable*.

**named tuple** Any tuple-like class whose indexable elements are also accessible using named attributes (for example, `time.localtime()` returns a tuple-like object where the *year* is accessible either with an index such as `t[0]` or with a named attribute like `t.tm_year`).

A named tuple can be a built-in type such as `time.struct_time`, or it can be created with a regular class definition. A full featured named tuple can also be created with the factory function `collections.namedtuple()`. The latter approach automatically provides extra features such as a self-documenting representation like `Employee(name='jones', title='programmer')`.

**namespace** The place where a variable is stored. Namespaces are implemented as dictionaries. There are the local, global and built-in namespaces as well as nested namespaces in objects (in methods). Namespaces support modularity by preventing naming conflicts. For instance, the functions `builtins.open()` and `os.open()` are distinguished by their namespaces. Namespaces also aid readability and maintainability by making it clear which module implements a function. For instance, writing `random.seed()` or `itertools.islice()` makes it clear that those functions are implemented by the `random` and `itertools` modules, respectively.

**namespace package** A [PEP 420 package](#) which serves only as a container for subpackages. Namespace packages may have no physical representation, and specifically are not like a *regular package* because they have no `__init__.py` file.

**nested scope** The ability to refer to a variable in an enclosing definition. For instance, a function defined inside another function can refer to variables in the outer function. Note that nested scopes by default work only for reference and not for assignment. Local variables both read and write in the innermost scope. Likewise, global variables read and write to the global namespace. The `nonlocal` allows writing to outer scopes.

**new-style class** Old name for the flavor of classes now used for all class objects. In earlier Python versions, only new-style classes could use Python's newer, versatile features like `__slots__`, descriptors, properties, `__getattr__()`, class methods, and static methods.

**object** Any data with state (attributes or value) and defined behavior (methods). Also the ultimate base class of any *new-style class*.

**package** A Python module which can contain submodules or recursively, subpackages. Technically, a package is a Python module with an `__path__` attribute.

**path entry** A single location on the *import path* which the *path based finder* consults to find modules for importing.

**path entry finder** A *finder* returned by a callable on `sys.path_hooks` (i.e. a *path entry hook*) which knows how to locate modules given a *path entry*.

**path entry hook** A callable on the `sys.path_hook` list which returns a *path entry finder* if it knows how to find modules on a specific *path entry*.

**path based finder** One of the default *meta path finders* which searches an *import path* for modules.

**portion** A set of files in a single directory (possibly stored in a zip file) that contribute to a namespace package, as defined in [PEP 420](#).

**positional argument** The arguments assigned to local names inside a function or method, determined by the order in which they were given in the call. `*` is used to either accept multiple positional arguments (when in the definition), or pass several arguments as a list to a function. See *argument*.

**provisional package** A provisional package is one which has been deliberately excluded from the standard library's backwards compatibility guarantees. While major changes to such packages are not expected, as long as they are marked provisional, backwards incompatible changes (up to and including removal of the package) may occur if deemed necessary by core developers. Such changes will not be made gratuitously – they will occur only if serious flaws are uncovered that were missed prior to the inclusion of the package.

This process allows the standard library to continue to evolve over time, without locking in problematic design errors for extended periods of time. See [PEP 411](#) for more details.

**Python 3000** Nickname for the Python 3.x release line (coined long ago when the release of version 3 was something in the distant future.) This is also abbreviated “Py3k”.

**Pythonic** An idea or piece of code which closely follows the most common idioms of the Python language, rather than implementing code using concepts common to other languages. For example, a common idiom in Python is to loop over all elements of an iterable using a `for` statement. Many other languages don't have this type of construct, so people unfamiliar with Python sometimes use a numerical counter instead:

```
for i in range(len(food)) :  
    print(food[i])
```

As opposed to the cleaner, Pythonic method:

```
for piece in food:  
    print(piece)
```

**qualified name** A dotted name showing the “path” from a module’s global scope to a class, function or method defined in that module, as defined in

**PEP 3155**. For top-level functions and classes, the qualified name is the same as the object’s name:

```
>>> class C:  
...     class D:  
...         def meth(self):  
...             pass  
...  
>>> C.__qualname__  
'C'  
>>> C.D.__qualname__  
'C.D'  
>>> C.D.meth.__qualname__  
'C.D.meth'
```

When used to refer to modules, the *fully qualified name* means the entire dotted path to the module, including any parent packages, e.g. `email.mime.text`:

```
>>> import email.mime.text  
>>> email.mime.text.__name__  
'email.mime.text'
```

**reference count** The number of references to an object. When the reference count of an object drops to zero, it is deallocated. Reference counting is generally not visible to Python code, but it is a key element of the *CPython* implementation. The `sys` module defines a `getrefcount()` function that programmers can call to return the reference count for a particular object.

**regular package** A traditional *package*, such as a directory containing an `__init__.py` file.

**\_\_slots\_\_** A declaration inside a class that saves memory by pre-declaring space for instance attributes and eliminating instance dictionaries. Though popular, the technique is somewhat tricky to get right and is best reserved for rare cases where there are large numbers of instances in a memory-critical application.

**sequence** An *iterable* which supports efficient element access using integer indices via the `__getitem__()` special method and defines a `len()` method that returns the length of the sequence. Some built-in sequence types are `list`, `str`, `tuple`, and `bytes`. Note that `dict` also supports `__getitem__()` and `__len__()`, but is considered a mapping rather than a sequence because the lookups use arbitrary *immutable* keys rather than integers.

**slice** An object usually containing a portion of a *sequence*. A slice is created using the subscript notation, `[]` with colons between numbers when several are given, such as in `variable_name[1:3:5]`. The bracket (subscript) notation uses `slice` objects internally.

**special method** A method that is called implicitly by Python to execute a certain operation on a type, such as addition. Such methods have names starting and ending with double underscores. Special methods are documented in *specialnames*.

**statement** A statement is part of a suite (a “block” of code). A statement is either an *expression* or a one of several constructs with a keyword, such as `if`, `while` or `for`.

**struct sequence** A tuple with named elements. Struct sequences expose an interface similar to *named tuple* in that elements can either be accessed either by index or as an attribute. However, they do not have any of the named tuple methods like `_make()` or `_asdict()`. Examples of struct sequences include `sys.float_info` and the return value of `os.stat()`.

**triple-quoted string** A string which is bound by three instances of either a quotation mark (") or an apostrophe ('). While they don't provide any functionality not available with single-quoted strings, they are useful for a number of reasons. They allow you to include unescaped single and double quotes within a string and they can span multiple lines without the use of the continuation character, making them especially useful when writing docstrings.

**type** The type of a Python object determines what kind of object it is; every object has a type. An object's type is accessible as its `__class__` attribute or can be retrieved with `type(obj)`.

**universal newlines** A manner of interpreting text streams in which all of the following are recognized as ending a line: the Unix end-of-line convention `'\n'`, the Windows convention `'\r\n'`, and the old Macintosh convention `'\r'`. See [PEP 278](#) and [PEP 3116](#), as well as `str.splitlines()` for an additional use.

**view** The objects returned from `dict.keys()`, `dict.values()`, and `dict.items()` are called dictionary views. They are lazy sequences that will see changes in the underlying dictionary. To force the dictionary view to become a full list use `list(dictview)`. See *dict-views*.

**virtual machine** A computer defined entirely in software. Python's virtual machine executes the *bytecode* emitted by the bytecode compiler.

**Zen of Python** Listing of Python design principles and philosophies that are helpful in understanding and using the language. The listing can be found by typing `"import this"` at the interactive prompt.

---

# ABOUT THESE DOCUMENTS

These documents are generated from [reStructuredText](#) sources by [Sphinx](#), a document processor specifically written for the Python documentation.

Development of the documentation and its toolchain takes place on the [docs@python.org](mailto:docs@python.org) mailing list. We're always looking for volunteers wanting to help with the docs, so feel free to send a mail there!

Many thanks go to:

- Fred L. Drake, Jr., the creator of the original Python documentation toolset and writer of much of the content;
- the [Docutils](#) project for creating reStructuredText and the Docutils suite;
- Fredrik Lundh for his [Alternative Python Reference](#) project from which Sphinx got many good ideas.

See *reporting-bugs* for information how to report bugs in this documentation, or Python itself.

## B.1 Contributors to the Python Documentation

This section lists people who have contributed in some way to the Python documentation. It is probably not complete – if you feel that you or anyone else should be on this list, please let us know (send email to [docs@python.org](mailto:docs@python.org)), and we'll be glad to correct the problem.

Aahz, Michael Abbott, Steve Alexander, Jim Ahlstrom, Fred Allen, A. Amoroso, Pehr Anderson, Oliver Andrich, Heidi Annexstad, Jesús Cea Avi3n, Manuel Balsera, Daniel Barclay, Chris Barker, Don Bashford, Anthony Baxter, Alexander Belopolsky, Bennett Benson, Jonathan Black, Robin Boerdijk, Michal Bozon, Aaron Brancotti, Georg Brandl, Keith Briggs, Ian Bruntlett, Lee Busby, Arnaud Calmettes, Lorenzo M. Catucci, Carl Cerecke, Mauro Cicognini, Gilles Civario, Mike Clarkson, Steve Clift, Dave Cole, Matthew Cowles, Jeremy Craven, Andrew Dalke, Ben Darnell, L. Peter Deutsch, Robert Donohue, Fred L. Drake, Jr., Jacques Ducasse, Josip Dzolong, Jeff Epler, Michael Ernst, Blame Andy Eskilsson, Carey Evans, Martijn Faassen, Carl Feynman, Dan Finnie, Hern3n Mart3nez Foffani, Michael Foord, Stefan Franke, Jim Fulton, Peter Funk, Ethan Furman, Lele Gaifax, Matthew Gallagher, Gabriel Genellina, Ben Gertzfield, Nadim Ghaznavi, Jonathan Giddy, Matt Giuca, Shelley Gooch, Nathaniel Gray, Grant Griffin, Thomas Guettler, Anders Hammarquist, Mark Hammond, Harald Hanche-Olsen, Manus Hand, Gerhard H3ring, Travis B. Hartwell, Tim Hatch, Janko Hauser, Ben Hayden, Thomas Heller, Bernhard Herzog, Magnus L. Hetland, Konrad Hins, Stefan Hoffmeister, Albert Hofkamp, Gregor Hoffleit, Steve Holden, Thomas Holenstein, Gerrit Holl, Rob Hooft, Brian Hooper, Randall Hopper, Michael Hudson, Eric Huss, Jeremy Hylton, Roger Irwin, Jack Jansen, Philip H. Jensen, Pedro Diaz Jimenez, Kent Johnson, Lucas de Jonge, Andreas Jung, Robert Kern, Jim Kerr, Jan Kim, Kamil Kisiel, Greg Kochanski, Guido Kollerie, Peter A. Koren, Daniel Kozan, Andrew M. Kuchling, Dave Kuhlman, Erno Kuusela, Ross Lagerwall, Thomas Lamb, Detlef Lannert, Piers Lauder, Julia Lawall, Glyph Lefkowitz, Robert Lehmann, Marc-Andr3 Lemburg, Ross Light, Gediminas Liktaras, Ulf A. Lindgren, Everett Lipman, Mirko Liss, Martin von L3wis, Fredrik Lundh, Jeff MacDonald, John Machin, Andrew MacIntyre, Vladimir Marangozov, Vincent Marchetti, Westley Mart3nez, Laura Matson, Daniel May, Rebecca McCreary, Doug Mennella, Paolo Milani, Skip Montanaro, Paul Moore, Ross Moore, Sjoerd Mullender, Dale Nagata, Trent Nelson, Michal Nowikowski, Steffen Daode Nurpmeso, Ng Pheng Siong, Koray Oner, Tomas Oppelstrup, Denis S. Otkidach, Zooko O'Whielacronx, Shriphani Palakodety, William Park, Joonas Paalasmaa, Harri Pasanen, Bo Peng, Tim Peters, Benjamin Peterson, Christopher Petrilli, Justin D.

Pettit, Chris Phoenix, François Pinard, Paul Prescod, Eric S. Raymond, Edward K. Ream, Terry J. Reedy, Sean Reifschneider, Bernhard Reiter, Armin Rigo, Wes Rishel, Armin Ronacher, Jim Roskind, Guido van Rossum, Donald Wallace Rouse II, Mark Russell, Nick Russo, Chris Ryland, Constantina S., Hugh Sasse, Bob Savage, Scott Schram, Neil Schemenauer, Barry Scott, Joakim Sernbrant, Justin Sheehy, Charlie Shepherd, Yue Shuaijie, SilentGhost, Michael Simcich, Ionel Simionescu, Michael Sloan, Gregory P. Smith, Roy Smith, Clay Spence, Nicholas Spies, Tage Stabell-Kulo, Frank Stajano, Anthony Starks, Greg Stein, Peter Stoehr, Mark Summerfield, Reuben Sumner, Kalle Svensson, Jim Tittsler, David Turner, Sandro Tosi, Ville Vainio, Nadeem Vawda, Martijn Vries, Charles G. Waldman, Greg Ward, Barry Warsaw, Corran Webster, Glyn Webster, Bob Weiner, Eddy Welbourne, Jeff Wheeler, Mats Wichmann, Gerry Wiener, Timothy Wild, Paul Winkler, Collin Winter, Blake Winton, Dan Wolfe, Adam Woodbeck, Steven Work, Thomas Wouters, Ka-Ping Yee, Rory Yorke, Moshe Zadka, Milan Zamazal, Cheng Zhang.

It is only with the input and contributions of the Python community that Python has such wonderful documentation – Thank You!

# HISTORY AND LICENSE

## C.1 History of the software

Python was created in the early 1990s by Guido van Rossum at Stichting Mathematisch Centrum (CWI, see <http://www.cwi.nl/>) in the Netherlands as a successor of a language called ABC. Guido remains Python's principal author, although it includes many contributions from others.

In 1995, Guido continued his work on Python at the Corporation for National Research Initiatives (CNRI, see <http://www.cnri.reston.va.us/>) in Reston, Virginia where he released several versions of the software.

In May 2000, Guido and the Python core development team moved to BeOpen.com to form the BeOpen Python-Labs team. In October of the same year, the PythonLabs team moved to Digital Creations (now Zope Corporation; see <http://www.zope.com/>). In 2001, the Python Software Foundation (PSF, see <http://www.python.org/psf/>) was formed, a non-profit organization created specifically to own Python-related Intellectual Property. Zope Corporation is a sponsoring member of the PSF.

All Python releases are Open Source (see <http://www.opensource.org/> for the Open Source Definition). Historically, most, but not all, Python releases have also been GPL-compatible; the table below summarizes the various releases.

| Release        | Derived from | Year      | Owner      | GPL compatible? |
|----------------|--------------|-----------|------------|-----------------|
| 0.9.0 thru 1.2 | n/a          | 1991-1995 | CWI        | yes             |
| 1.3 thru 1.5.2 | 1.2          | 1995-1999 | CNRI       | yes             |
| 1.6            | 1.5.2        | 2000      | CNRI       | no              |
| 2.0            | 1.6          | 2000      | BeOpen.com | no              |
| 1.6.1          | 1.6          | 2001      | CNRI       | no              |
| 2.1            | 2.0+1.6.1    | 2001      | PSF        | no              |
| 2.0.1          | 2.0+1.6.1    | 2001      | PSF        | yes             |
| 2.1.1          | 2.1+2.0.1    | 2001      | PSF        | yes             |
| 2.2            | 2.1.1        | 2001      | PSF        | yes             |
| 2.1.2          | 2.1.1        | 2002      | PSF        | yes             |
| 2.1.3          | 2.1.2        | 2002      | PSF        | yes             |
| 2.2.1          | 2.2          | 2002      | PSF        | yes             |
| 2.2.2          | 2.2.1        | 2002      | PSF        | yes             |
| 2.2.3          | 2.2.2        | 2002-2003 | PSF        | yes             |
| 2.3            | 2.2.2        | 2002-2003 | PSF        | yes             |
| 2.3.1          | 2.3          | 2002-2003 | PSF        | yes             |
| 2.3.2          | 2.3.1        | 2003      | PSF        | yes             |
| 2.3.3          | 2.3.2        | 2003      | PSF        | yes             |
| 2.3.4          | 2.3.3        | 2004      | PSF        | yes             |
| 2.3.5          | 2.3.4        | 2005      | PSF        | yes             |
| 2.4            | 2.3          | 2004      | PSF        | yes             |
| 2.4.1          | 2.4          | 2005      | PSF        | yes             |
| 2.4.2          | 2.4.1        | 2005      | PSF        | yes             |
| 2.4.3          | 2.4.2        | 2006      | PSF        | yes             |

Continued on next page

**Table C.1 – continued from previous page**

|       |       |      |     |     |
|-------|-------|------|-----|-----|
| 2.4.4 | 2.4.3 | 2006 | PSF | yes |
| 2.5   | 2.4   | 2006 | PSF | yes |
| 2.5.1 | 2.5   | 2007 | PSF | yes |
| 2.6   | 2.5   | 2008 | PSF | yes |
| 2.6.1 | 2.6   | 2008 | PSF | yes |
| 2.6.2 | 2.6.1 | 2009 | PSF | yes |
| 2.6.3 | 2.6.2 | 2009 | PSF | yes |
| 2.6.4 | 2.6.3 | 2009 | PSF | yes |
| 3.0   | 2.6   | 2008 | PSF | yes |
| 3.0.1 | 3.0   | 2009 | PSF | yes |
| 3.1   | 3.0.1 | 2009 | PSF | yes |
| 3.1.1 | 3.1   | 2009 | PSF | yes |
| 3.1.2 | 3.1.1 | 2010 | PSF | yes |
| 3.1.3 | 3.1.2 | 2010 | PSF | yes |
| 3.1.4 | 3.1.3 | 2011 | PSF | yes |
| 3.2   | 3.1   | 2011 | PSF | yes |
| 3.2.1 | 3.2   | 2011 | PSF | yes |
| 3.2.2 | 3.2.1 | 2011 | PSF | yes |
| 3.2.3 | 3.2.2 | 2012 | PSF | yes |
| 3.3.0 | 3.2   | 2012 | PSF | yes |

---

**Note:** GPL-compatible doesn't mean that we're distributing Python under the GPL. All Python licenses, unlike the GPL, let you distribute a modified version without making your changes open source. The GPL-compatible licenses make it possible to combine Python with other software that is released under the GPL; the others don't.

---

Thanks to the many outside volunteers who have worked under Guido's direction to make these releases possible.

## C.2 Terms and conditions for accessing or otherwise using Python

### PSF LICENSE AGREEMENT FOR PYTHON 3.3.0

1. This LICENSE AGREEMENT is between the Python Software Foundation ("PSF"), and the Individual or Organization ("Licensee") accessing and otherwise using Python 3.3.0 software in source or binary form and its associated documentation.
2. Subject to the terms and conditions of this License Agreement, PSF hereby grants Licensee a nonexclusive, royalty-free, world-wide license to reproduce, analyze, test, perform and/or display publicly, prepare derivative works, distribute, and otherwise use Python 3.3.0 alone or in any derivative version, provided, however, that PSF's License Agreement and PSF's notice of copyright, i.e., "Copyright © 2001-2012 Python Software Foundation; All Rights Reserved" are retained in Python 3.3.0 alone or in any derivative version prepared by Licensee.
3. In the event Licensee prepares a derivative work that is based on or incorporates Python 3.3.0 or any part thereof, and wants to make the derivative work available to others as provided herein, then Licensee hereby agrees to include in any such work a brief summary of the changes made to Python 3.3.0.
4. PSF is making Python 3.3.0 available to Licensee on an "AS IS" basis. PSF MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF EXAMPLE, BUT NOT LIMITATION, PSF MAKES NO AND DISCLAIMS ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF PYTHON 3.3.0 WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
5. PSF SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF PYTHON 3.3.0 FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A RESULT OF MODIFYING, DISTRIBUTING, OR OTHERWISE USING PYTHON 3.3.0, OR ANY DERIVATIVE THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.

6. This License Agreement will automatically terminate upon a material breach of its terms and conditions.
7. Nothing in this License Agreement shall be deemed to create any relationship of agency, partnership, or joint venture between PSF and Licensee. This License Agreement does not grant permission to use PSF trademarks or trade name in a trademark sense to endorse or promote products or services of Licensee, or any third party.
8. By copying, installing or otherwise using Python 3.3.0, Licensee agrees to be bound by the terms and conditions of this License Agreement.

BEOPEN.COM LICENSE AGREEMENT FOR PYTHON 2.0

BEOPEN PYTHON OPEN SOURCE LICENSE AGREEMENT VERSION 1

1. This LICENSE AGREEMENT is between BeOpen.com ("BeOpen"), having an office at 160 Saratoga Avenue, Santa Clara, CA 95051, and the Individual or Organization ("Licensee") accessing and otherwise using this software in source or binary form and its associated documentation ("the Software").
2. Subject to the terms and conditions of this BeOpen Python License Agreement, BeOpen hereby grants Licensee a non-exclusive, royalty-free, world-wide license to reproduce, analyze, test, perform and/or display publicly, prepare derivative works, distribute, and otherwise use the Software alone or in any derivative version, provided, however, that the BeOpen Python License is retained in the Software, alone or in any derivative version prepared by Licensee.
3. BeOpen is making the Software available to Licensee on an "AS IS" basis. BEOPEN MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF EXAMPLE, BUT NOT LIMITATION, BEOPEN MAKES NO AND DISCLAIMS ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF THE SOFTWARE WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
4. BEOPEN SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF THE SOFTWARE FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A RESULT OF USING, MODIFYING OR DISTRIBUTING THE SOFTWARE, OR ANY DERIVATIVE THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.
5. This License Agreement will automatically terminate upon a material breach of its terms and conditions.
6. This License Agreement shall be governed by and interpreted in all respects by the law of the State of California, excluding conflict of law provisions. Nothing in this License Agreement shall be deemed to create any relationship of agency, partnership, or joint venture between BeOpen and Licensee. This License Agreement does not grant permission to use BeOpen trademarks or trade names in a trademark sense to endorse or promote products or services of Licensee, or any third party. As an exception, the "BeOpen Python" logos available at <http://www.pythonlabs.com/logos.html> may be used according to the permissions granted on that web page.
7. By copying, installing or otherwise using the software, Licensee agrees to be bound by the terms and conditions of this License Agreement.

CNRI LICENSE AGREEMENT FOR PYTHON 1.6.1

1. This LICENSE AGREEMENT is between the Corporation for National Research Initiatives, having an office at 1895 Preston White Drive, Reston, VA 20191 ("CNRI"), and the Individual or Organization ("Licensee") accessing and otherwise using Python 1.6.1 software in source or binary form and its associated documentation.
2. Subject to the terms and conditions of this License Agreement, CNRI hereby grants Licensee a nonexclusive, royalty-free, world-wide license to reproduce, analyze, test, perform and/or display publicly, prepare derivative works, distribute, and otherwise use Python 1.6.1 alone or in any derivative version, provided, however, that CNRI's License Agreement and CNRI's notice of copyright, i.e., "Copyright © 1995-2001 Corporation for National Research Initiatives; All Rights Reserved" are retained in Python 1.6.1 alone or in any derivative version prepared by Licensee. Alternately, in lieu of CNRI's License Agreement, Licensee may substitute the following text (omitting the quotes): "Python 1.6.1 is made available subject to the terms and conditions in CNRI's License Agreement. This Agreement together with Python 1.6.1 may be located on the Internet using the following unique, persistent identifier (known as a handle):

1895.22/1013. This Agreement may also be obtained from a proxy server on the Internet using the following URL: <http://hdl.handle.net/1895.22/1013>.”

3. In the event Licensee prepares a derivative work that is based on or incorporates Python 1.6.1 or any part thereof, and wants to make the derivative work available to others as provided herein, then Licensee hereby agrees to include in any such work a brief summary of the changes made to Python 1.6.1.
4. CNRI is making Python 1.6.1 available to Licensee on an “AS IS” basis. CNRI MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED. BY WAY OF EXAMPLE, BUT NOT LIMITATION, CNRI MAKES NO AND DISCLAIMS ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF PYTHON 1.6.1 WILL NOT INFRINGE ANY THIRD PARTY RIGHTS.
5. CNRI SHALL NOT BE LIABLE TO LICENSEE OR ANY OTHER USERS OF PYTHON 1.6.1 FOR ANY INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSS AS A RESULT OF MODIFYING, DISTRIBUTING, OR OTHERWISE USING PYTHON 1.6.1, OR ANY DERIVATIVE THEREOF, EVEN IF ADVISED OF THE POSSIBILITY THEREOF.
6. This License Agreement will automatically terminate upon a material breach of its terms and conditions.
7. This License Agreement shall be governed by the federal intellectual property law of the United States, including without limitation the federal copyright law, and, to the extent such U.S. federal law does not apply, by the law of the Commonwealth of Virginia, excluding Virginia’s conflict of law provisions. Notwithstanding the foregoing, with regard to derivative works based on Python 1.6.1 that incorporate non-separable material that was previously distributed under the GNU General Public License (GPL), the law of the Commonwealth of Virginia shall govern this License Agreement only as to issues arising under or with respect to Paragraphs 4, 5, and 7 of this License Agreement. Nothing in this License Agreement shall be deemed to create any relationship of agency, partnership, or joint venture between CNRI and Licensee. This License Agreement does not grant permission to use CNRI trademarks or trade name in a trademark sense to endorse or promote products or services of Licensee, or any third party.
8. By clicking on the “ACCEPT” button where indicated, or by copying, installing or otherwise using Python 1.6.1, Licensee agrees to be bound by the terms and conditions of this License Agreement.

ACCEPT

#### CWI LICENSE AGREEMENT FOR PYTHON 0.9.0 THROUGH 1.2

Copyright © 1991 - 1995, Stichting Mathematisch Centrum Amsterdam, The Netherlands. All rights reserved.

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of Stichting Mathematisch Centrum or CWI not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

STICHTING MATHEMATISCH CENTRUM DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL STICHTING MATHEMATISCH CENTRUM BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

## C.3 Licenses and Acknowledgements for Incorporated Software

This section is an incomplete, but growing list of licenses and acknowledgements for third-party software incorporated in the Python distribution.

### C.3.1 Mersenne Twister

The `_random` module includes code based on a download from <http://www.math.keio.ac.jp/matumoto/MT2002/emt19937ar.html>. The following are the verbatim comments from the original code:

A C-program for MT19937, with initialization improved 2002/1/26.  
Coded by Takuji Nishimura and Makoto Matsumoto.

Before using, initialize the state by using `init_genrand(seed)`  
or `init_by_array(init_key, key_length)`.

Copyright (C) 1997 - 2002, Makoto Matsumoto and Takuji Nishimura,  
All rights reserved.

Redistribution and use in source and binary forms, with or without  
modification, are permitted provided that the following conditions  
are met:

1. Redistributions of source code must retain the above copyright  
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright  
notice, this list of conditions and the following disclaimer in the  
documentation and/or other materials provided with the distribution.
3. The names of its contributors may not be used to endorse or promote  
products derived from this software without specific prior written  
permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS  
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT  
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR  
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR  
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,  
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,  
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR  
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF  
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING  
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS  
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Any feedback is very welcome.  
<http://www.math.keio.ac.jp/matsumoto/emt.html>  
email: [matsumoto@math.keio.ac.jp](mailto:matsumoto@math.keio.ac.jp)

### C.3.2 Sockets

The `socket` module uses the functions, `getaddrinfo()`, and `getnameinfo()`, which are coded in separate  
source files from the WIDE Project, <http://www.wide.ad.jp/>.

Copyright (C) 1995, 1996, 1997, and 1998 WIDE Project.  
All rights reserved.

Redistribution and use in source and binary forms, with or without  
modification, are permitted provided that the following conditions  
are met:

1. Redistributions of source code must retain the above copyright

- notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
  3. Neither the name of the project nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE PROJECT AND CONTRIBUTORS ``AS IS'' AND GAI\_ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE PROJECT OR CONTRIBUTORS BE LIABLE FOR GAI\_ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON GAI\_ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN GAI\_ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

### C.3.3 Floating point exception control

The source for the `fpectl` module includes the following notice:

```
-----
/                               Copyright (c) 1996.                               \
|           The Regents of the University of California.                         |
|           All rights reserved.                                                  |
|                                                                                 |
|  Permission to use, copy, modify, and distribute this software for             |
|  any purpose without fee is hereby granted, provided that this en-            |
|  tire notice is included in all copies of any software which is or            |
|  includes a copy or modification of this software and in all                  |
|  copies of the supporting documentation for such software.                     |
|                                                                                 |
|  This work was produced at the University of California, Lawrence               |
|  Livermore National Laboratory under contract no. W-7405-ENG-48               |
|  between the U.S. Department of Energy and The Regents of the                 |
|  University of California for the operation of UC LLNL.                       |
|                                                                                 |
|                               DISCLAIMER                                         |
|                                                                                 |
|  This software was prepared as an account of work sponsored by an             |
|  agency of the United States Government. Neither the United States            |
|  Government nor the University of California nor any of their em-             |
|  ployees, makes any warranty, express or implied, or assumes any              |
|  liability or responsibility for the accuracy, completeness, or               |
|  usefulness of any information, apparatus, product, or process                |
|  disclosed, or represents that its use would not infringe                    |
|  privately-owned rights. Reference herein to any specific commer-            |
|  cial products, process, or service by trade name, trademark,                 |
|  manufacturer, or otherwise, does not necessarily constitute or               |
|  imply its endorsement, recommendation, or favoring by the United            |
|  States Government or the University of California. The views and             |
|  opinions of authors expressed herein do not necessarily state or             |
|  reflect those of the United States Government or the University              |
|  of California, and shall not be used for advertising or product              |
|  \ endorsement purposes.                                                       /
```

### C.3.4 Asynchronous socket services

The `asynchat` and `asyncore` modules contain the following notice:

Copyright 1996 by Sam Rushing

All Rights Reserved

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of Sam Rushing not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

SAM RUSHING DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL SAM RUSHING BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

### C.3.5 Cookie management

The `http.cookies` module contains the following notice:

Copyright 2000 by Timothy O'Malley <timo@alum.mit.edu>

All Rights Reserved

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of Timothy O'Malley not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

Timothy O'Malley DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL Timothy O'Malley BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

### C.3.6 Execution tracing

The `trace` module contains the following notice:

portions copyright 2001, Autonomous Zones Industries, Inc., all rights...  
err... reserved and offered to the public under the terms of the  
Python 2.2 license.  
Author: Zooko O'Whielacronx  
<http://zooko.com/>  
<mailto:zooko@zooko.com>

Copyright 2000, Mojam Media, Inc., all rights reserved.  
Author: Skip Montanaro

Copyright 1999, Bioreason, Inc., all rights reserved.  
Author: Andrew Dalke

Copyright 1995-1997, Automatrix, Inc., all rights reserved.  
Author: Skip Montanaro

Copyright 1991-1995, Stichting Mathematisch Centrum, all rights reserved.

Permission to use, copy, modify, and distribute this Python software and its associated documentation for any purpose without fee is hereby granted, provided that the above copyright notice appears in all copies, and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of neither Automatrix, Bioreason or Mojam Media be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

### C.3.7 UUencode and UUdecode functions

The uu module contains the following notice:

Copyright 1994 by Lance Ellinghouse  
Cathedral City, California Republic, United States of America.  
All Rights Reserved

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of Lance Ellinghouse not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

LANCE ELLINGHOUSE DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL LANCE ELLINGHOUSE CENTRUM BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Modified by Jack Jansen, CWI, July 1995:

- Use binascii module to do the actual line-by-line conversion between ascii and binary. This results in a 1000-fold speedup. The C version is still 5 times faster, though.
- Arguments more compliant with Python standard

### C.3.8 XML Remote Procedure Calls

The `xmlrpc.client` module contains the following notice:

The XML-RPC client interface is

Copyright (c) 1999-2002 by Secret Labs AB  
Copyright (c) 1999-2002 by Fredrik Lundh

By obtaining, using, and/or copying this software and/or its associated documentation, you agree that you have read, understood, and will comply with the following terms and conditions:

Permission to use, copy, modify, and distribute this software and its associated documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appears in all copies, and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of Secret Labs AB or the author not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

SECRET LABS AB AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL SECRET LABS AB OR THE AUTHOR BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

### C.3.9 test\_epoll

The `test_epoll` contains the following notice:

Copyright (c) 2001-2006 Twisted Matrix Laboratories.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

### C.3.10 Select kqueue

The `select` and contains the following notice for the `kqueue` interface:

Copyright (c) 2000 Doug White, 2006 James Knight, 2007 Christian Heimes  
All rights reserved.

Redistribution and use in source and binary forms, with or without  
modification, are permitted provided that the following conditions  
are met:

1. Redistributions of source code must retain the above copyright  
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright  
notice, this list of conditions and the following disclaimer in the  
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND  
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE  
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE  
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE  
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL  
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS  
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)  
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT  
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY  
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF  
SUCH DAMAGE.

### C.3.11 strtod and dtoa

The file `Python/dtoa.c`, which supplies C functions `dtoa` and `strtod` for conversion of C doubles to  
and from strings, is derived from the file of the same name by David M. Gay, currently available from  
<http://www.netlib.org/fp/>. The original file, as retrieved on March 16, 2009, contains the following copyright  
and licensing notice:

```
/* *****  
*  
* The author of this software is David M. Gay.  
*  
* Copyright (c) 1991, 2000, 2001 by Lucent Technologies.  
*  
* Permission to use, copy, modify, and distribute this software for any  
* purpose without fee is hereby granted, provided that this entire notice  
* is included in all copies of any software which is or includes a copy  
* or modification of this software and in all copies of the supporting  
* documentation for such software.  
*  
* THIS SOFTWARE IS BEING PROVIDED "AS IS", WITHOUT ANY EXPRESS OR IMPLIED  
* WARRANTY. IN PARTICULAR, NEITHER THE AUTHOR NOR LUCENT MAKES ANY  
* REPRESENTATION OR WARRANTY OF ANY KIND CONCERNING THE MERCHANTABILITY  
* OF THIS SOFTWARE OR ITS FITNESS FOR ANY PARTICULAR PURPOSE.  
*  
***** */
```

### C.3.12 OpenSSL

The modules `hashlib`, `posix`, `ssl`, `crypt` use the OpenSSL library for added performance if made available by the operating system. Additionally, the Windows installers for Python include a copy of the OpenSSL libraries, so we include a copy of the OpenSSL license here:

```
LICENSE ISSUES
=====
```

The OpenSSL toolkit stays under a dual license, i.e. both the conditions of the OpenSSL License and the original SSLeay license apply to the toolkit. See below for the actual license texts. Actually both licenses are BSD-style Open Source licenses. In case of any license issues related to OpenSSL please contact [openssl-core@openssl.org](mailto:openssl-core@openssl.org).

```
OpenSSL License
-----
```

```
/* =====
 * Copyright (c) 1998-2008 The OpenSSL Project. All rights reserved.
 *
 * Redistribution and use in source and binary forms, with or without
 * modification, are permitted provided that the following conditions
 * are met:
 *
 * 1. Redistributions of source code must retain the above copyright
 *    notice, this list of conditions and the following disclaimer.
 *
 * 2. Redistributions in binary form must reproduce the above copyright
 *    notice, this list of conditions and the following disclaimer in
 *    the documentation and/or other materials provided with the
 *    distribution.
 *
 * 3. All advertising materials mentioning features or use of this
 *    software must display the following acknowledgment:
 *    "This product includes software developed by the OpenSSL Project
 *    for use in the OpenSSL Toolkit. (http://www.openssl.org/)"
 *
 * 4. The names "OpenSSL Toolkit" and "OpenSSL Project" must not be used to
 *    endorse or promote products derived from this software without
 *    prior written permission. For written permission, please contact
 *    openssl-core@openssl.org.
 *
 * 5. Products derived from this software may not be called "OpenSSL"
 *    nor may "OpenSSL" appear in their names without prior written
 *    permission of the OpenSSL Project.
 *
 * 6. Redistributions of any form whatsoever must retain the following
 *    acknowledgment:
 *    "This product includes software developed by the OpenSSL Project
 *    for use in the OpenSSL Toolkit (http://www.openssl.org/)"
 *
 * THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT ``AS IS'' AND ANY
 * EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
 * IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
 * PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE OpenSSL PROJECT OR
 * ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
 * SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
 * NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
```

```
* LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
* STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
* OF THE POSSIBILITY OF SUCH DAMAGE.
* =====
*
* This product includes cryptographic software written by Eric Young
* (eay@cryptsoft.com). This product includes software written by Tim
* Hudson (tjh@cryptsoft.com).
*
*/
```

Original SSLeay License

-----

```
/* Copyright (C) 1995-1998 Eric Young (eay@cryptsoft.com)
 * All rights reserved.
 *
 * This package is an SSL implementation written
 * by Eric Young (eay@cryptsoft.com).
 * The implementation was written so as to conform with Netscapes SSL.
 *
 * This library is free for commercial and non-commercial use as long as
 * the following conditions are aheared to. The following conditions
 * apply to all code found in this distribution, be it the RC4, RSA,
 * lhash, DES, etc., code; not just the SSL code. The SSL documentation
 * included with this distribution is covered by the same copyright terms
 * except that the holder is Tim Hudson (tjh@cryptsoft.com).
 *
 * Copyright remains Eric Young's, and as such any Copyright notices in
 * the code are not to be removed.
 * If this package is used in a product, Eric Young should be given attribution
 * as the author of the parts of the library used.
 * This can be in the form of a textual message at program startup or
 * in documentation (online or textual) provided with the package.
 *
 * Redistribution and use in source and binary forms, with or without
 * modification, are permitted provided that the following conditions
 * are met:
 * 1. Redistributions of source code must retain the copyright
 * notice, this list of conditions and the following disclaimer.
 * 2. Redistributions in binary form must reproduce the above copyright
 * notice, this list of conditions and the following disclaimer in the
 * documentation and/or other materials provided with the distribution.
 * 3. All advertising materials mentioning features or use of this software
 * must display the following acknowledgement:
 * "This product includes cryptographic software written by
 * Eric Young (eay@cryptsoft.com)"
 * The word 'cryptographic' can be left out if the rouines from the library
 * being used are not cryptographic related :-).
 * 4. If you include any Windows specific code (or a derivative thereof) from
 * the apps directory (application code) you must include an acknowledgement:
 * "This product includes software written by Tim Hudson (tjh@cryptsoft.com)"
 *
 * THIS SOFTWARE IS PROVIDED BY ERIC YOUNG ``AS IS'' AND
 * ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
 * IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
```

```
* ARE DISCLAIMED.  IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* The licence and distribution terms for any publically available version or
* derivative of this code cannot be changed.  i.e. this code cannot simply be
* copied and put under another distribution licence
* [including the GNU Public Licence.]
*/
```

### C.3.13 expat

The pyexpat extension is built using an included copy of the expat sources unless the build is configured `--with-system-expat`:

```
Copyright (c) 1998, 1999, 2000 Thai Open Source Software Center Ltd
                        and Clark Cooper
```

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

### C.3.14 libffi

The `_ctypes` extension is built using an included copy of the libffi sources unless the build is configured `--with-system-libffi`:

```
Copyright (c) 1996-2008 Red Hat, Inc and others.
```

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the ``Software''), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED ``AS IS'', WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

### C.3.15 zlib

The `zlib` extension is built using an included copy of the `zlib` sources if the `zlib` version found on the system is too old to be used for the build:

Copyright (C) 1995–2011 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly  
jloup@gzip.org

Mark Adler  
madler@alumni.caltech.edu

# COPYRIGHT

Python and this documentation is:

Copyright © 2001-2012 Python Software Foundation. All rights reserved.

Copyright © 2000 BeOpen.com. All rights reserved.

Copyright © 1995-2000 Corporation for National Research Initiatives. All rights reserved.

Copyright © 1991-1995 Stichting Mathematisch Centrum. All rights reserved.

---

See *[History and License](#)* for complete license and permissions information.



# INDEX

## Symbols

..., 85  
\_\_future\_\_, 87  
\_\_slots\_\_, 91  
>>>, 85  
2to3, 85

## A

abstract base class, 85  
argument, 85  
attribute, 85

## B

BDFL, 85  
bytecode, 85

## C

class, 85  
coercion, 85  
complex number, 85  
context manager, 86  
CPython, 86

## D

decorator, 86  
descriptor, 86  
dictionary, 86  
docstring, 86  
duck-typing, 86

## E

EAFP, 86  
environment variable  
    PATH, 50  
    TCL\_LIBRARY, 81  
    TK\_LIBRARY, 81  
expression, 86  
extension module, 87

## F

file object, 87  
file-like object, 87  
finder, 87  
floor division, 87  
function, 87

## G

garbage collection, 87  
generator, 87  
generator expression, 87  
GIL, 87  
global interpreter lock, 87

## H

hashable, 88

## I

IDLE, 88  
immutable, 88  
import path, 88  
importer, 88  
importing, 88  
interactive, 88  
interpreted, 88  
iterable, 88  
iterator, 88

## K

key function, 88  
keyword argument, 89

## L

lambda, 89  
LBYL, 89  
list, 89  
list comprehension, 89  
loader, 89

## M

mapping, 89  
meta path finder, 89  
metaclass, 89  
method, 89  
method resolution order, 89  
module, 89  
MRO, 89  
mutable, 89

## N

named tuple, 90  
namespace, 90

namespace package, [90](#)  
nested scope, [90](#)  
new-style class, [90](#)

## O

object, [90](#)

## P

package, [90](#)  
PATH, [50](#)  
path based finder, [90](#)  
path entry, [90](#)  
path entry finder, [90](#)  
path entry hook, [90](#)  
portion, [90](#)  
positional argument, [90](#)  
provisional package, [90](#)  
Python 3000, [90](#)  
Python Enhancement Proposals  
    PEP 238, [87](#)  
    PEP 275, [39](#)  
    PEP 278, [92](#)  
    PEP 302, [87](#), [89](#)  
    PEP 3116, [92](#)  
    PEP 3155, [91](#)  
    PEP 328, [16](#)  
    PEP 343, [86](#)  
    PEP 411, [90](#)  
    PEP 420, [87](#), [90](#)  
    PEP 5, [8](#)  
    PEP 6, [5](#)  
    PEP 8, [14](#), [75](#)  
Pythonic, [90](#)

## Q

qualified name, [91](#)

## R

reference count, [91](#)  
regular package, [91](#)

## S

sequence, [91](#)  
slice, [91](#)  
special method, [91](#)  
statement, [91](#)  
struct sequence, [91](#)

## T

TCL\_LIBRARY, [81](#)  
TK\_LIBRARY, [81](#)  
triple-quoted string, [92](#)  
type, [92](#)

## U

universal newlines, [92](#)

## V

view, [92](#)  
virtual machine, [92](#)

## Z

Zen of Python, [92](#)